

クローラクレーン[油圧駆動式ウインチ・ラチェンブ型]【70t吊】 (2/2)

作業半径 (m)	33.5		36.5		39.5		42.5		45.5		48.5		51.5		54.5	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
3.5		(t)		(t)		(t)		(t)		(t)						
4.0																
4.5																
5.0																
5.5																
6.0																
7.0																
8.0	29.7	29.1	33.5	28.0												
9.0	29.4	24.6	32.5	24.5	35.6	24.6	39.4	21.2								
10.0	29.1	21.2	32.2	21.2	35.4	21.0	38.5	21.0	41.5	20.7	45.4	19.5				
12.0	28.4	16.5	31.6	16.4	34.8	16.3	37.9	16.3	41.0	16.1	44.3	15.9	47.4		50.5	13.3
14.0	27.6	13.4	30.9	13.3	34.1	13.2	37.3	13.1	40.4	13.0	43.8	12.7	46.9		50.0	12.0
16.0	26.6	11.1	30.0	11.0	33.3	10.9	36.5	10.8	39.7	10.7	43.1	10.5	46.3		49.4	10.3
18.0	25.4	9.4	28.9	9.3	32.3	9.2	35.6	9.1	38.9	9.0	42.4	8.9	45.6		48.8	8.7
20.0	24.0	8.1	27.7	8.0	31.2	7.9	34.6	7.8	38.0	7.7	41.5	7.6	44.8		48.0	7.3
22.0	22.4	7.1	26.3	7.0	30.0	6.9	33.5	6.8	37.0	6.6	40.6	6.5	43.9		47.2	6.3
24.0	20.5	6.2	24.6	6.1	28.5	6.0	32.2	5.9	35.8	5.8	39.5	5.6	42.9		46.3	5.4
26.0	18.3	5.5	22.8	5.4	26.9	5.3	30.8	5.2	34.5	5.1	38.3	4.9	41.8		45.2	4.7
28.0	15.5	4.9	20.6	4.8	25.0	4.7	29.1	4.6	33.0	4.5	36.9	4.3	40.6		44.1	4.1
30.0	12.1	4.5	17.9	4.3	22.8	4.2	27.2	4.1	31.4	3.9	35.4	3.8	39.2		42.8	3.6
32.0			14.2	3.9	20.3	3.8	25.1	3.9	29.5	3.6	33.8	3.3	37.7		41.4	3.1
34.0					16.8	3.5	22.6	3.2	27.4	3.1	31.9	2.9	36.0		39.9	2.6
36.0							19.3	3.0	25.0	2.7	29.8	2.5	34.2		38.2	2.3
38.0							15.7	2.7	22.2	2.4	27.5	2.2	32.1		36.4	1.9
40.0									18.3	2.1	24.8	1.9	29.8		34.3	1.6
42.0											20.9	1.7	27.1		32.1	1.3
44.0													23.4		29.5	1.1

クローラクレーン[油圧駆動式ウインチ・ラフジブ型]【80t吊】(1/2)

作業半径 (m)	12.2		12.5		15.5		18.5		21.5		24.5		27.5		30.5		33.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.8	11.4	80.0																
4.0	9.4	80.0																
4.5	9.1	72.6	9.8	72.2														
5.0	8.9	60.8	9.3	60.8	12.8	60.7												
5.5	8.5	51.0	8.8	51.0	12.1	50.9	15.3	50.8										
6.0	8.4	45.7	8.8	45.6	12.1	45.6	15.3	45.6	18.8	45.7								
7.0	7.8	36.4	8.2	36.4	11.6	36.3	14.9	36.2	18.1	36.2	21.3	36.1	24.2	36.6	27.3	38.6		
8.0	7.0	30.2	7.4	30.2	11.1	30.1	14.5	30.0	17.8	29.8	21.0	29.8	24.1	29.7	27.2	29.6	30.3	29.5
9.0	6.0	25.7	6.5	25.7	10.4	25.6	14.0	25.5	17.3	25.4	20.6	25.3	23.8	25.2	27.0	25.1	30.1	25.0
10.0	4.8	22.2	5.3	22.2	9.7	22.1	13.4	22.0	16.8	21.9	20.2	21.8	23.4	21.8	26.6	21.7	29.8	21.6
12.0	2.2	17.4	1.3	17.4	7.6	17.3	11.9	17.3	15.6	17.2	19.2	17.1	22.6	17.0	25.9	17.0	29.1	16.9
14.0					4.5	14.3	9.9	14.2	14.1	14.1	17.9	13.9	21.5	13.8	24.9	13.8	28.2	13.7
16.0							7.1	11.9	12.2	11.8	16.4	11.7	20.2	11.6	23.8	11.5	27.2	11.4
18.0							2.7	10.5	9.6	10.1	14.4	9.9	18.6	9.9	22.4	9.8	26.1	9.7
20.0									5.7	8.8	12.0	8.6	16.7	8.6	20.8	8.4	24.7	8.3
22.0											8.6	7.6	14.3	7.5	18.9	7.4	23.1	7.3
24.0											2.5	7.2	11.2	6.7	16.6	6.6	21.2	6.4
26.0													6.6	6.3	13.8	5.8	18.9	5.7
28.0															9.9	5.2	16.2	5.1
30.0															3.1	4.8	12.3	4.7
32.0																	7.5	4.4
34.0																		
36.0																		
38.0																		
40.0																		
42.0																		
44.0																		

クローラクレーン[油圧駆動式ウインチ・ラチスジブ型]【80t吊】(2/2)

作業半径 (m)	フーム長さ (m)	36.5		39.5		42.5		45.5		48.5		51.5		54.5		57.5	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.8																	
4.0																	
4.5																	
5.0																	
5.5																	
6.0																	
7.0																	
8.0		33.2	29.1														
9.0		33.2	25.0	36.3	24.9	39.1	23.4										
10.0		32.9	21.6	36.0	21.5	39.1	21.3	42.2	21.2								
12.0		32.3	16.8	35.4	16.7	38.6	16.6	41.7	16.5	44.8	16.4	48.2	16.4	51.3	16.2	53.8	15.8
14.0		31.5	13.6	34.7	13.5	37.9	13.4	41.1	13.3	44.2	13.2	47.7	13.2	50.8	13.1	53.9	12.9
16.0		30.6	11.3	33.9	11.2	37.2	11.1	40.4	11.0	43.6	10.9	47.1	10.9	50.2	10.8	53.3	10.7
18.0		29.6	9.6	33.0	9.5	36.3	9.4	39.6	9.3	42.8	9.2	46.4	9.2	49.6	9.1	52.7	9.0
20.0		28.3	8.3	31.9	8.2	35.3	8.1	38.7	8.0	42.0	7.9	45.6	7.8	48.8	7.7	52.0	7.6
22.0		26.9	7.2	30.6	7.1	34.2	7.0	37.6	6.9	41.0	6.9	44.7	6.7	48.0	6.6	51.2	6.5
24.0		25.3	6.4	29.2	6.3	32.9	6.1	36.5	6.1	40.0	5.9	43.7	5.8	47.0	5.8	50.4	5.6
26.0		23.4	5.6	27.5	5.5	31.4	5.4	35.1	5.3	38.8	5.2	42.6	5.1	46.0	5.0	49.4	4.8
28.0		21.2	5.0	25.7	4.9	29.8	4.8	33.7	4.7	37.4	4.6	41.3	4.5	44.9	4.4	48.3	4.2
30.0		18.6	4.5	23.5	4.4	27.9	4.3	32.0	4.2	35.9	4.1	40.0	3.9	43.6	3.8	47.2	3.7
32.0		15.2	4.3	21.0	3.9	25.8	3.8	30.2	3.7	34.3	3.6	38.5	3.4	42.2	3.3	45.9	3.2
34.0				17.7	3.8	23.3	3.4	28.0	3.3	32.4	3.2	36.8	3.0	40.7	2.9	44.5	2.7
36.0						20.7	3.0	25.6	3.0	30.3	2.8	34.9	2.7	39.0	2.5	42.9	2.3
38.0						16.6	2.9	22.8	2.6	27.9	2.5	32.9	2.3	37.2	2.1	41.3	2.0
40.0								19.3	2.5	24.9	2.2	30.0	2.0	34.6	1.8	38.9	1.6
42.0										21.8	2.0	27.4	1.7	32.3	1.5		
44.0										18.0	1.6						

クローラクレーン[油圧駆動式ウインチ・ラチスジブ型]【90t吊】(1/2)

作業半径 (m)	12.0		12.5		15.5		18.5		21.5		24.5		27.5		30.5		33.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
4.0	8.7	90.0																
4.5	8.5	81.8	9.0	81.5	12.9	78.7												
5.0	8.3	77.3	8.8	76.3	12.1	73.1	15.2	70.5										
5.5	8.0	65.5	8.6	65.5	11.9	64.8	15.4	60.3	19.1	59.8								
6.0	7.7	57.3	8.3	57.2	11.6	56.5	14.9	56.5	18.0	54.6	21.1	54.6						
7.0	7.1	45.4	7.7	45.4	11.2	45.0	14.5	44.9	17.7	44.9	20.8	44.8	24.0	43.5	27.1	43.6		
8.0	6.3	37.5	6.9	37.5	10.6	37.1	14.0	37.0	17.3	36.9	20.5	36.8	23.7	36.8	26.8	36.7	29.9	35.6
9.0	5.3	31.8	6.0	31.8	10.0	31.4	13.5	31.3	16.9	31.3	20.1	31.2	23.3	31.1	26.5	30.9	29.6	30.8
10.0	4.0	27.5	4.8	27.5	9.2	27.3	12.9	27.1	16.4	27.0	19.7	26.9	23.0	26.8	26.2	26.7	29.3	26.6
12.0			0.8	20.9	7.2	21.3	11.4	21.2	15.2	21.1	18.7	21.0	22.1	20.9	25.4	20.7	28.6	20.6
14.0					4.0	17.5	9.4	17.2	13.7	17.2	17.5	17.0	21.0	16.9	24.5	16.8	27.8	16.8
16.0							6.6	14.6	11.7	14.4	15.9	14.2	19.7	14.1	23.3	14.0	26.8	13.8
18.0									9.1	12.3	14.0	12.2	18.1	12.1	22.0	11.9	25.6	11.8
20.0									5.2	10.6	11.5	10.6	16.2	10.5	20.4	10.3	24.2	10.1
22.0											8.1	9.3	13.9	9.1	18.5	9.0	22.6	8.8
24.0													10.8	8.2	16.2	7.9	20.7	7.8
26.0															13.3	7.1	18.5	6.9
28.0															9.4	6.2	15.7	6.2
30.0																	12.3	5.6
32.0																		
34.0																		
36.0																		
38.0																		
40.0																		
42.0																		
44.0																		
46.0																		

クローラクレーン[油圧駆動式ウインチ・ラチスジブ型]【90t吊】(2/2)

作業半径 (m)	36.5		39.5		42.5		45.5		48.5		51.5		54.5		57.5		60.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
4.0																		
4.5																		
5.0																		
5.5																		
6.0																		
7.0																		
8.0	33.0	35.6																
9.0	32.7	30.7	35.8	29.9		26.7												
10.0	32.5	26.4	35.5	26.4	38.6	26.3	41.7	25.5	45.8	20.7								
12.0	31.8	20.5	35.0	20.4	38.1	20.3	41.2	20.2	44.3	20.1	47.3	46.8	19.8	19.6	53.4	19.4		
14.0	31.1	16.5	34.3	16.4	37.5	16.3	40.6	16.2	43.8	16.1	46.8	46.2	15.9	15.7	53.0	15.6	56.1	15.3
16.0	30.2	13.7	33.4	13.6	36.7	13.5	39.9	13.4	43.1	13.3	46.2	45.5	13.1	12.9	52.5	12.8	55.6	12.6
18.0	29.1	11.6	32.5	11.5	35.8	11.4	39.1	11.3	42.4	11.2	45.5	44.7	11.0	10.9	51.9	10.8	55.0	8.4
20.0	27.9	10.0	31.4	9.9	34.8	9.7	38.2	9.6	41.5	9.5	44.7	43.8	9.4	9.3	51.2	9.2	54.3	9.0
22.0	26.5	8.7	30.1	8.6	33.7	8.4	37.2	8.3	40.6	8.2	43.8	42.8	8.1	8.0	50.4	7.9	53.6	7.7
24.0	24.9	7.6	28.7	7.5	32.4	7.4	36.0	7.3	39.5	7.1	42.8	41.7	7.1	7.0	49.5	6.8	52.8	6.7
26.0	23.0	6.8	27.1	6.7	31.0	6.5	34.7	6.3	38.3	6.2	41.7	40.5	6.2	6.1	48.5	5.9	51.9	5.8
28.0	20.8	6.0	25.2	5.9	29.3	5.8	33.2	5.6	36.9	5.5	40.5	39.1	5.5	5.3	47.5	5.2	50.9	5.0
30.0	18.1	5.4	23.0	5.3	27.4	5.1	31.5	5.0	35.4	4.9	39.1	37.6	4.8	4.7	46.3	4.5	49.8	4.4
32.0	14.9	4.9	20.5	4.7	25.3	4.6	29.7	4.4	33.8	4.3	37.6	36.4	4.3	4.1	45.0	4.0	48.6	3.8
34.0			17.4	4.3	22.8	4.1	27.6	3.9	31.9	3.8	35.9	34.7	3.8	3.6	43.6	3.5	47.3	3.3
36.0					19.9	3.7	25.2	3.5	29.8	3.3	34.1	32.9	3.2	3.1	42.1	3.1	45.9	2.9
38.0							22.4	3.1	27.5	3.0	32.0	30.7	3.0	2.8	40.4	2.6	44.3	2.4
40.0							19.0	2.7	24.8	2.6	29.7	28.3	2.6	2.4	38.6	2.2	42.6	2.0
42.0									21.6	2.3	27.0	25.5	2.3	2.1	36.5	1.9	40.8	1.7
44.0											24.0	22.4	2.0	1.8	34.3	1.6	39.1	1.5
46.0														1.5				

クローラクレーン[油圧駆動式ウインチ・ラチェンギブ型]【100t吊】（1／2）

作業半径 (m)	16.0		18.5		21.5		24.5		27.5		30.5		33.5		36.5		39.5		42.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
4.6	12.3	100.0																		
5.0	13.9	87.5	15.5	71.6	18.6	68.4														
5.5	13.7	84.7	16.1	87.0	18.5	63.4	21.5	60.5												
6.0	13.5	77.6	15.4	86.9	18.7	82.1	21.4	62.7	24.5	52.6	50.5									
7.0	13.0	64.7	15.0	73.2	18.2	72.6	21.3	71.1	25.4	58.9	27.4	42.9	30.4	41.5	33.5	40.1	36.5	34.4		
8.0	12.5	53.2	14.5	60.2	17.8	60.0	21.0	59.8	24.2	59.0	27.3	56.1	30.4	51.4	33.8	38.6	36.4	33.9		
9.0	11.9	44.8	14.0	50.5	17.4	50.8	20.7	50.6	23.9	50.4	27.0	50.0	30.1	48.7	33.2	46.5	36.0	41.5	40.8	36.8
10.0	11.1	38.7	13.4	43.4	16.9	43.8	20.2	43.7	23.5	43.6	26.7	43.3	29.8	43.0	33.0	42.5	36.1	39.9	39.2	39.4
12.0	9.2	30.2	11.9	33.8	15.7	34.3	19.2	34.2	22.6	34.1	25.9	33.9	29.1	33.7	32.3	33.6	35.5	33.4	38.7	34.9
14.0	6.4	24.4	10.0	27.5	14.2	27.9	18.0	27.8	21.5	27.7	25.0	27.5	28.3	27.4	31.6	27.2	34.8	27.1	38.0	28.3
16.0			6.8	22.5	12.2	23.4	16.4	23.2	20.2	23.1	23.8	23.0	27.3	22.8	30.7	22.6	34.0	22.5	37.3	23.5
18.0					9.6	20.1	14.5	19.9	18.7	19.8	22.5	19.6	26.1	19.5	29.6	19.3	33.0	19.2	36.4	20.0
20.0					5.4	17.9	12.0	17.3	16.7	17.2	20.9	17.0	24.7	16.8	28.4	16.7	31.9	16.6	35.4	17.2
22.0							8.3	15.0	14.4	15.2	19.0	15.0	23.1	14.9	27.0	14.7	30.7	14.5	34.3	15.1
24.0									11.0	13.4	16.7	13.3	21.2	13.2	25.4	13.1	29.2	12.9	33.0	13.3
26.0											13.5	11.8	19.0	11.8	23.5	11.7	27.6	11.5	31.5	11.9
28.0											9.8	10.8	16.3	10.7	21.3	10.5	25.7	10.3	29.9	10.6
30.0													12.3	9.6	18.7	9.5	23.6	9.3	28.0	9.6
32.0															15.1	10.2	21.0	8.4	25.9	8.7
34.0																	17.6	9.1	23.4	7.9
36.0																			21.6	7.4
38.0																				
40.0																				
42.0																				
44.0																				
46.0																				
48.0																				
50.0																				
52.0																				
54.0																				

クローラクレーン〔油圧駆動式ウインチ・ラジジブ型〕【100t吊】（2／2）

作業半径 (m)	45.5		48.5		51.5		54.5		57.5		60.5		63.5		66.5		69.5		72.5	
	フックの 地上高さ		フックの 地上高さ		フックの 地上高さ		フックの 地上高さ		フックの 地上高さ		フックの 地上高さ		フックの 地上高さ		フックの 地上高さ		フックの 地上高さ		フックの 地上高さ	
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
4.6																				
5.0																				
5.5																				
6.0																				
7.0																				
8.0																				
9.0																				
10.0	41.9	39.0	46.7	30.2																
12.0	41.4	34.6	44.5	30.2	47.6	29.5	50.7	26.7	53.5	25.8										
14.0	40.8	28.1	43.9	27.8	47.1	27.7	50.2	25.9	53.1	25.1	56.2	20.5	59.2	19.9	62.3	18.9	65.0	15.8		
16.0	40.1	23.3	43.3	23.1	46.4	22.9	49.6	22.7	52.5	23.0	55.7	20.2	58.8	19.8	61.9	18.3	64.9	16.7	68.0	15.2
18.0	39.3	19.7	42.5	19.6	45.7	19.5	48.9	19.3	51.9	19.7	55.1	19.3	58.2	18.9	61.3	17.5	64.4	16.0	67.5	14.6
20.0	38.4	17.0	41.7	16.9	45.0	16.7	48.2	16.6	51.2	16.9	54.4	16.7	57.6	16.5	60.7	16.2	63.9	15.2	67.0	13.8
22.0	37.3	14.9	40.7	14.7	44.1	14.6	47.4	14.4	50.4	14.7	53.7	14.6	56.9	14.4	60.1	14.2	63.2	13.8	66.4	12.8
24.0	36.2	13.1	39.6	13.0	43.1	12.8	46.4	12.6	49.6	12.9	52.8	12.8	56.1	12.7	59.3	12.5	62.5	12.1	65.7	11.7
26.0	34.8	11.6	38.4	11.5	42.0	11.3	45.4	11.1	48.6	11.4	51.9	11.4	55.2	11.2	58.5	11.0	61.8	10.7	65.0	10.3
28.0	33.4	10.4	37.1	10.3	40.7	10.1	44.3	9.9	47.5	10.2	50.9	10.1	54.3	10.0	57.6	9.8	60.9	9.6	64.2	9.2
30.0	31.7	9.3	35.6	9.2	39.4	9.0	43.0	8.9	46.4	9.1	49.8	9.0	53.3	8.9	56.7	8.7	60.0	8.5	63.3	8.1
32.0	29.8	8.4	33.9	8.3	37.8	8.1	41.6	7.9	45.1	8.2	48.7	8.1	52.2	8.0	55.6	7.8	59.0	7.5	62.4	7.2
34.0	27.7	7.7	32.1	7.5	36.2	7.3	40.1	7.2	43.7	7.4	47.3	7.3	50.9	7.1	54.5	7.0	57.9	6.7	61.3	6.5
36.0	25.3	7.1	30.0	6.9	34.3	6.7	38.4	6.6	42.1	6.7	45.9	6.6	49.6	6.4	53.2	6.2	56.8	6.0	60.2	5.8
38.0	22.5	6.5	27.6	6.3	32.3	6.1	36.6	6.0	40.5	6.1	44.4	6.0	48.2	5.8	51.9	5.6	55.5	5.4	59.0	5.1
40.0	19.2	6.8	24.9	5.8	29.9	5.6	34.5	5.4	38.6	5.5	42.7	5.4	46.6	5.2	50.4	5.0	54.1	4.7	57.8	4.4
42.0			21.8	6.2	27.3	5.1	32.2	4.9	36.6	5.0	40.9	4.9	44.9	4.7	48.9	4.4	52.7	4.2	56.4	3.9
44.0					24.9	4.7	29.7	4.5	34.3	4.5	38.8	4.4	43.1	4.2	47.2	4.0	51.1	3.6	54.9	3.3
46.0							26.7	4.1	31.8	4.1	36.6	3.9	41.1	3.7	45.3	3.3	49.4	3.1	53.3	2.9
48.0							23.3	4.5	29.0	3.6	34.1	3.5	38.9	3.3	43.3	3.0	47.6	2.7	51.6	2.4
50.0									25.9	4.0	31.4	3.1	36.4	2.9	41.1	2.7	45.6	2.4	49.8	2.0
52.0											28.4	3.6	33.8	2.6	38.8	2.2	43.4	2.1		
54.0													30.7	2.6	36.1	2.1				

クローラクレーン[油圧駆動式ウインチ・ラフスジブ型]【120t吊】 (1/2)

作業半径 (m)	15.0		15.5		18.5		21.5		24.5		27.5		30.5		33.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
4.5	10.2	120.0														
5.0	10.4	119.5	10.5	117.1												
5.5	10.5	110.5	11.0	110.3	15.2	112.7										
6.0	10.0	101.0	11.0	100.7	14.2	100.3										
7.0	9.6	87.0	10.5	86.6	13.8	86.4	17.0	86.1	20.1	84.4						
8.0	9.0	75.2	9.9	74.7	13.3	74.7	16.6	74.6	19.8	74.6	23.0	73.2	26.1	68.7	30.0	59.0
9.0	8.3	62.8	9.3	62.4	12.8	62.4	16.2	62.3	19.4	62.3	22.6	62.2	25.8	62.2	28.9	60.6
10.0	7.5	53.8	8.5	53.5	12.2	53.4	15.7	53.4	19.0	53.4	22.3	53.3	25.5	53.2	28.6	53.2
12.0	5.3	41.6	6.5	41.3	10.7	41.3	14.5	41.2	18.0	41.2	21.4	41.0	24.7	41.0	27.9	41.0
14.0	1.7	33.6	3.3	33.4	8.8	33.4	13.0	33.3	16.8	33.3	20.3	33.2	23.8	33.2	27.1	33.1
16.0					5.9	27.9	11.0	27.8	15.2	27.8	19.0	27.7	22.6	27.7	26.1	27.6
18.0							8.4	23.8	13.3	23.7	17.5	23.6	21.3	23.6	24.9	23.5
20.0							5.3	20.3	10.8	20.6	15.5	20.5	19.7	20.4	23.5	20.3
22.0									7.4	18.2	13.2	18.0	17.8	18.0	21.9	17.9
24.0											10.1	16.0	15.5	15.9	20.0	15.8
26.0													12.6	14.3	17.8	14.2
28.0													9.6	12.6	15.1	12.8
30.0															11.6	11.6
32.0																
34.0																
36.0																
38.0																
40.0																
42.0																
44.0																
46.0																
48.0																
50.0																
52.0																

クローラクレーン[油圧駆動式ウインチ・ラジジブ型]【120t吊】(2/2)

作業半径 (m)	36.5		39.5		42.5		45.5		48.5		51.5		54.5		57.5		60.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
4.5																		
5.0																		
5.5																		
6.0																		
7.0																		
8.0																		
9.0	32.0	56.8	35.9	48.2														
10.0	31.8	52.8	34.9	50.7	38.2	43.8	41.8	40.0										
12.0	31.1	40.9	34.3	40.8	37.4	40.6	40.5	39.4	43.7	35.2	46.7	34.1	50.7	29.9	53.8			
14.0	30.4	32.9	33.6	32.8	36.8	32.8	40.0	32.6	43.1	32.6	46.2	32.1	50.2	28.6	53.3	56.4	23.9	
16.0	29.5	27.4	32.8	27.3	36.0	27.3	39.3	27.1	42.4	27.0	45.6	26.9	49.6	26.2	52.8	55.9	23.2	
18.0	28.4	23.3	31.8	23.2	35.2	23.2	38.4	23.0	41.7	22.9	44.9	22.8	49.0	22.1	52.1	55.3	21.5	
20.0	27.2	20.2	30.7	20.1	34.2	20.0	37.5	19.8	40.8	19.8	44.1	19.7	48.2	19.0	51.4	54.6	18.7	
22.0	25.8	17.7	29.5	17.6	33.0	17.5	36.5	17.3	39.9	17.3	43.2	17.2	47.4	16.5	50.7	53.9	16.2	
24.0	24.2	15.7	28.0	15.6	31.7	15.5	35.3	15.3	38.8	15.3	42.2	15.1	46.5	14.5	49.8	53.1	14.2	
26.0	22.3	14.0	26.4	13.9	30.3	13.8	34.0	13.7	37.6	13.6	41.1	13.5	45.4	12.9	48.8	52.2	12.6	
28.0	20.1	12.7	24.5	12.5	28.6	12.4	32.5	12.2	36.3	12.2	39.9	12.0	44.3	11.5	47.8	51.2	11.2	
30.0	17.5	11.4	22.4	11.3	26.8	11.2	30.9	11.0	34.8	11.0	38.5	10.8	43.0	10.3	46.6	50.1	10.0	
32.0	13.8	10.6	19.8	10.3	24.6	10.2	29.0	10.0	33.1	10.0	37.0	9.8	41.6	9.3	45.3	48.9	9.0	
34.0			16.4	9.6	22.2	9.3	26.9	9.1	31.2	9.0	35.3	8.9	40.1	8.4	43.9	47.6	8.1	
36.0					19.2	8.5	24.5	8.3	29.2	8.2	33.5	8.1	38.4	7.6	42.4	46.2	7.3	
38.0							21.7	7.6	26.8	7.5	31.4	7.4	36.6	6.9	40.7	44.6	6.6	
40.0							18.0	7.1	24.1	6.9	29.1	6.8	34.5	6.3	38.8	42.9	6.0	
42.0									20.5	6.5	26.5	6.2	32.3	5.8	36.8	41.1	5.5	
44.0											23.0	5.8	29.7	5.3	34.5	39.1	5.0	
46.0													26.8	4.8	32.0	36.8	4.5	
48.0													23.3	4.9	29.2	34.4	4.0	
50.0															25.9	31.6	3.6	
52.0																28.4	3.5	

クローラクレーン[油圧駆動式ウインチ・ラチェスジブ型]【150t吊】(1/2)

ブーム長さ (m)		作業半径 (m)		18.0		18.5		21.5		24.5		27.5		30.5		33.5		36.5		39.5		42.5		45.5		48.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	
5.0	14.2	150.0																									
5.5	14.3	147.0	14.8	144.2																							
6.0	13.9	143.8	14.2	141.3	17.7	127.6																					
7.0	13.5	130.5	13.8	127.8	17.1	125.4	20.2	117.8	23.6	103.1	26.0	94.4															
8.0	13.1	107.9	13.4	103.9	16.7	103.6	19.9	103.4	23.0	101.8	26.2	97.5	29.6	83.9	32.7	77.9											
9.0	12.5	90.2	12.9	86.5	16.3	86.3	19.5	86.2	22.7	86.1	25.9	85.9	29.3	80.6	32.4	77.4	35.5	69.8	37.9	64.3							
10.0	11.9	77.2	12.3	73.9	15.8	73.7	19.1	73.7	22.3	73.6	25.5	73.4	29.0	71.1	32.1	70.5	35.2	68.3	38.3	64.7	41.4	58.1	43.8	52.8			
12.0	10.4	60.0	10.8	57.2	14.6	57.0	18.1	56.9	21.5	56.7	24.8	56.5	28.3	54.7	31.5	54.6	34.7	54.4	37.8	54.3	40.9	53.5	44.0	51.4			
14.0	8.3	48.5	8.8	46.5	13.0	46.2	16.8	46.0	20.4	45.9	23.8	45.7	27.5	44.3	30.7	44.0	34.0	43.9	37.2	43.7	40.3	43.5	43.5	43.4			
16.0	5.2	39.6	6.0	38.9	11.1	38.7	15.3	38.6	19.1	38.4	22.7	38.2	26.5	37.0	29.8	36.8	33.1	36.7	36.4	36.6	39.6	36.4	42.8	36.3			
18.0					8.5	33.3	13.3	33.1	17.5	33.0	21.3	32.7	25.3	31.6	28.8	31.4	32.2	31.3	35.5	31.2	38.8	31.0	42.1	30.9			
20.0					4.0	29.7	10.9	28.9	15.6	28.7	19.8	28.4	23.9	27.5	27.6	27.3	31.1	27.2	34.5	27.0	37.9	26.9	41.2	26.8			
22.0							7.5	25.5	13.2	25.4	17.8	25.1	22.3	24.4	26.1	24.1	29.8	23.9	33.4	23.8	36.9	23.6	40.2	23.5			
24.0									10.2	22.7	15.5	22.4	20.4	21.7	24.5	21.4	28.4	21.2	32.1	21.1	35.7	21.0	39.2	20.8			
26.0											12.7	20.2	18.1	19.6	22.6	19.3	26.8	19.1	30.6	19.0	34.4	18.8	38.0	18.6			
28.0											8.2	18.7	15.0	18.0	20.4	17.5	24.9	17.3	29.0	17.2	32.9	16.9	36.6	16.8			
30.0													11.5	16.4	17.8	15.9	22.7	15.7	27.1	15.6	31.2	15.4	35.1	15.2			
32.0																14.5	15.3	20.2	14.4	25.0	14.2	29.4	14.0	33.5	13.8		
34.0																		17.0	13.8	22.5	13.1	27.3	12.9	31.6	12.7		
36.0																			19.2	12.3	24.9	11.9	29.5	11.7			
38.0																			16.0	11.6	22.0	11.0	27.2	10.8			
40.0																					18.6	10.6	24.5	10.0			
42.0																							21.2	9.6			
44.0																											
46.0																											
48.0																											
50.0																											
52.0																											
54.0																											
56.0																											
58.0																											
60.0																											
62.0																											
64.0																											
66.0																											

クローラクレーン[油圧駆動式ウインチ・ラチェンブ型]【150t吊】(2/2)

作業半径 (m)	ブーム長さ (m)	51.5		54.5		57.5		60.5		63.5		66.5		69.5		72.5		75.5		78.5		81.5	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
5.0																							
5.5																							
6.0																							
7.0																							
8.0																							
9.0																							
10.0																							
12.0		47.1	49.1	50.2	45.9	53.3	41.5	55.6	43.5	58.7	43.5												
14.0		46.6	42.8	49.7	41.6	52.8	40.4	55.9	39.5	59.0	38.8	62.0	35.3	65.1	30.9								
16.0		46.0	36.1	49.1	36.0	52.3	35.3	55.4	36.0	55.5	36.0	61.6	33.9	64.6	31.2	67.7	28.7	70.8	26.3	73.9	24.1	77.0	21.0
18.0		45.3	30.8	48.5	30.6	51.6	30.5	54.8	30.8	57.9	30.7	61.0	30.6	64.1	29.6	67.2	27.7	70.3	25.7	73.4	23.5	76.5	21.0
20.0		44.5	26.6	47.7	26.4	50.9	26.3	54.1	26.6	57.3	26.5	60.4	26.4	63.6	26.3	66.7	26.2	69.8	24.8	72.9	22.8	76.0	20.5
22.0		43.6	23.3	46.9	23.1	50.1	23.0	53.4	23.2	56.6	23.2	59.8	23.1	62.9	23.0	66.1	22.8	69.2	22.7	72.4	21.7	75.5	19.8
24.0		42.6	20.7	46.0	20.4	49.3	20.3	52.6	20.5	55.8	20.5	59.0	20.3	62.2	20.3	65.4	20.1	68.6	19.9	71.8	19.8	74.9	18.7
26.0		41.5	18.4	44.9	18.2	48.3	18.1	51.7	18.3	54.9	18.2	58.2	18.1	61.5	18.0	64.7	17.8	67.9	17.7	71.1	17.5	74.3	17.1
28.0		40.2	16.6	43.8	16.4	47.2	16.3	50.7	16.4	54.0	16.3	57.3	16.2	60.6	16.1	63.9	15.9	67.1	15.8	70.4	15.6	73.6	15.5
30.0		38.9	15.0	42.5	14.8	46.1	14.7	49.6	14.8	53.0	14.7	56.4	14.5	59.7	14.5	63.0	14.3	66.3	14.1	69.6	14.0	72.8	13.9
32.0		37.4	13.7	41.1	13.5	44.8	13.3	48.4	13.4	51.9	13.4	55.3	13.2	58.7	13.1	62.1	12.9	65.4	12.7	68.7	12.6	72.0	12.5
34.0		35.7	12.5	39.6	12.2	43.4	12.1	47.1	12.2	50.6	12.1	54.2	12.0	57.6	11.9	61.0	11.6	64.4	11.5	67.8	11.3	71.1	11.3
36.0		33.9	11.4	37.9	11.2	41.9	11.1	45.6	11.2	49.3	11.1	52.9	10.9	56.5	10.9	59.9	10.6	63.4	10.5	66.8	10.3	70.1	10.1
38.0		31.8	10.5	36.1	10.4	40.2	10.2	44.1	10.2	47.9	10.1	51.6	10.0	55.2	9.9	58.8	9.7	62.3	9.5	65.7	9.3	69.1	9.2
40.0		29.5	9.8	34.0	9.5	38.3	9.4	42.4	9.4	46.3	9.3	50.1	9.2	53.9	9.0	57.5	8.8	61.0	8.6	64.6	8.4	68.0	8.3
42.0		26.8	9.0	31.8	8.8	36.3	8.6	40.6	8.6	44.6	8.5	48.6	8.3	52.4	8.3	56.1	8.0	59.8	7.9	63.3	7.7	66.9	7.6
44.0		23.7	8.7	29.2	8.1	34.0	8.0	38.5	8.0	42.8	7.9	46.9	7.7	50.8	7.6	54.6	7.3	58.4	7.2	62.0	7.0	65.6	6.9
46.0				26.3	7.6	31.5	7.4	36.3	7.4	40.8	7.3	45.0	7.1	49.1	7.0	53.1	6.7	56.9	6.6	60.6	6.3	64.3	6.2
48.0				22.8	7.2	28.7	6.8	33.9	6.8	38.6	6.7	43.0	6.5	47.3	6.4	51.3	6.1	55.3	6.0	59.1	5.7	62.9	5.5
50.0						25.3	6.4	31.3	6.2	36.5	6.0	40.9	6.0	45.3	5.9	49.5	5.6	53.6	5.4	57.5	5.1	61.4	5.0
52.0								27.9	5.7	33.8	5.6	38.5	5.5	43.1	5.3	47.5	5.0	51.8	4.8	55.8	4.6	59.8	4.4
54.0										30.7	5.1	35.8	5.0	40.8	4.9	45.4	4.5	49.8	4.3	54.0	4.1	58.1	3.9
56.0										26.7	5.2	32.9	4.6	38.2	4.4	43.1	4.1	47.7	3.9	52.0	3.6	56.2	3.5
58.0												29.3	4.5	35.3	4.0	40.5	3.7	45.3	3.5	49.9	3.2	54.3	3.0
60.0														31.8	3.8	37.7	3.3	42.8	3.1	47.6	2.8	52.2	2.6
62.0																34.6	2.9	40.1	2.7	45.2	2.5	49.9	2.3
64.0																							
66.0																30.8	2.8	36.8	2.6	42.2	2.4		
																33.4	2.2						

クローラクレーン[油圧駆動式ウインチ・ラジブ型]【200t吊】(1/2)

ブーム長さ (m)		作業半径 (m)		15.2		15.5		18.5		21.5		24.5		27.5		30.5		33.5		36.5		39.5		42.5		45.5		48.5	
フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)		
4.5	11.9	200.0																											
5.0	11.8	196.7	12.1	195.7																									
5.5	11.6	181.4	11.5	191.7																									
6.0	11.4	166.1	10.9	187.6	14.4	188.1				18.0	173.0																		
7.0	10.9	143.6	10.5	162.7	14.1	163.4	17.3	162.4	20.4	153.4																			
8.0	10.4	126.4	9.9	143.2	13.6	143.8	16.9	143.4	20.1	140.0	23.2	142.3	26.4	127.8	29.6	124.3													
9.0	9.7	107.9	9.3	127.6	13.1	128.2	16.5	127.8	19.7	127.4	22.9	127.1	26.1	124.6	29.2	122.9	32.3	103.6	35.5	99.7									
10.0	8.9	93.1	8.5	114.9	12.5	115.7	16.0	115.2	19.3	114.9	22.6	114.6	25.7	114.2	28.9	113.9	32.0	101.8	35.1	99.8	38.2	96.6	41.4	87.4					
12.0	6.8	70.6	6.5	88.3	11.0	90.2	14.8	90.0	18.3	89.8	21.7	88.6	25.0	88.4	28.2	88.2	31.4	88.2	34.6	88.9	37.7	88.7	40.8	85.2	44.0	76.6			
14.0	3.3	53.5	3.3	71.0	9.0	72.6	13.3	72.4	17.0	72.2	20.6	20.6	24.0	71.8	27.4	71.6	30.6	71.5	33.9	71.3	37.1	71.1	40.2	70.9	43.5	70.5			
16.0					6.3	60.5	11.3	60.4	15.5	60.2	19.3	59.9	22.9	59.8	26.4	59.6	29.7	59.6	33.0	59.6	36.3	60.7	39.5	59.0	42.8	58.5			
18.0							8.7	51.9	13.6	51.6	17.7	51.3	21.6	51.1	25.2	50.8	28.7	50.8	32.1	50.6	35.4	50.4	38.7	50.3	42.1	49.7			
20.0							4.9	45.2	11.1	45.0	15.8	44.8	20.0	44.4	23.8	44.2	27.5	44.1	31.0	43.9	34.4	43.8	37.8	43.6	41.2	43.0			
22.0									7.8	39.5	13.4	39.3	18.1	39.3	22.2	39.0	26.1	38.9	29.7	38.7	33.3	38.6	36.8	38.3	40.3	37.7			
24.0											10.5	35.1	15.8	35.1	20.3	34.9	24.4	34.7	28.3	34.5	32.0	34.3	35.6	34.1	39.2	33.4			
26.0											5.7	27.7	12.9	31.5	18.1	31.3	22.6	31.4	26.7	31.0	30.6	30.7	34.3	30.5	38.0	29.9			
28.0												9.2	28.5	15.3	28.4	20.3	28.4	24.8	24.8	24.8	28.2	27.8	32.8	27.6	36.5	27.0			
30.0															11.9	25.8	17.7	25.8	22.6	25.6	27.0	25.3	31.1	25.1	35.1	24.6			
32.0																	14.1	22.7	20.1	23.3	24.9	23.2	29.3	23.0	33.5	22.5			
34.0																			16.7	20.7	22.4	21.2	27.2	21.0	31.6	20.7			
36.0																					19.3	19.7	24.8	19.4	29.5	19.0			
38.0																					15.6	17.1	22.0	17.9	27.2	17.6			
40.0																							18.2	15.8	24.5	16.3			
42.0																													
44.0																									20.8	14.5			
46.0																													
48.0																													
50.0																													
52.0																													
54.0																													
56.0																													
58.0																													
60.0																													
62.0																													
64.0																													

クローラクレーン【油圧駆動式ウインチ・チスジブ型】【200t吊】（2／2）

ブーム長さ (m) 作業半径 (m)		51.5		54.5		57.5		60.5		63.5		66.5		69.5		72.5		75.5		78.5		81.5		84.5		87.5	
フックの 地上高さ (m)	定格 総荷重 (t)	51.5		54.5		57.5		60.5		63.5		66.5		69.5		72.5		75.5		78.5		81.5		84.5		87.5	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
4.5																											
5.0																											
5.5																											
6.0																											
7.0																											
8.0																											
9.0																											
10.0																											
12.0	47.1	74.4	50.2	70.5	53.3	63.3																					
14.0	46.6	70.0	49.7	66.5	52.8	62.0	55.9	58.4	51.3	59.0	51.3	62.1	49.7	65.4	48.0												
16.0	46.0	58.3	49.1	58.0	52.3	57.8	55.4	55.1	58.5	50.6	51.6	61.6	47.9	64.7	45.3	67.8	39.1	70.3	34.4	73.4	32.4						
18.0	45.3	49.5	48.5	49.2	51.6	49.2	54.8	49.0	57.9	48.1	61.1	45.5	64.2	64.2	42.8	67.3	38.6	69.8	33.0	72.9	30.7	76.0	29.9	79.1	26.3	82.1	25.0
20.0	44.5	42.7	47.7	42.6	50.9	42.4	54.1	42.3	57.3	42.2	60.5	42.1	63.6	40.7	66.7	36.8	69.3	31.7	72.4	29.2	75.5	28.4	78.6	25.9	81.7	24.4	
22.0	43.6	37.5	46.9	37.3	50.2	37.1	53.4	37.0	56.6	36.9	59.8	36.7	63.0	36.6	66.1	34.2	68.7	30.1	71.9	27.8	75.0	27.1	78.1	25.5	81.2	23.7	
24.0	42.6	33.2	46.0	33.0	49.3	32.8	52.6	32.7	55.8	32.6	59.1	32.4	62.3	32.3	65.5	31.5	68.1	28.6	71.2	26.6	74.4	25.9	77.5	24.6	80.6	22.7	
26.0	41.5	29.7	44.9	29.5	48.3	28.3	51.7	29.1	55.0	29.0	58.3	28.9	61.5	28.7	64.7	28.5	67.4	26.7	70.6	25.5	73.7	24.8	76.9	23.5	80.1	21.6	
28.0	40.3	26.8	43.8	26.6	47.3	26.4	50.7	26.2	54.0	26.1	57.4	25.9	60.7	25.7	63.9	25.6	66.6	25.2	69.8	24.5	73.0	23.7	76.2	22.5	79.4	20.6	
30.0	38.9	24.3	42.5	24.1	46.1	23.9	49.6	23.7	53.0	23.6	56.4	23.3	59.7	23.2	63.1	23.0	65.8	23.5	69.0	23.2	72.3	22.5	75.5	21.4	78.7	19.5	
32.0	37.4	22.2	41.1	21.9	44.8	21.7	48.4	21.5	51.9	21.5	55.3	21.2	58.7	21.0	62.1	20.9	64.9	21.7	68.2	21.6	71.5	21.1	74.7	20.2	77.9	18.5	
34.0	35.7	20.4	39.6	20.1	43.4	19.8	47.1	19.7	50.7	19.6	54.2	19.3	57.7	19.1	61.1	19.0	63.9	19.8	67.3	19.7	70.6	19.7	73.9	19.0	77.1	17.4	
36.0	33.9	18.8	37.9	18.5	41.9	18.2	45.7	18.1	49.4	17.9	53.0	17.6	56.5	17.5	60.0	17.4	62.9	18.1	66.3	18.1	69.6	18.1	73.0	17.7	76.3	16.4	
38.0	31.8	17.3	36.1	17.2	40.2	16.9	44.1	16.6	47.9	16.5	51.6	16.2	55.2	16.0	58.8	15.8	61.7	16.6	65.2	16.6	68.6	16.6	72.0	16.4	75.3	15.2	
40.0	29.5	16.1	34.0	15.8	38.3	15.6	42.4	15.4	46.4	15.2	50.2	14.9	53.9	14.7	57.5	14.5	60.5	15.3	64.0	15.2	67.5	15.2	70.9	15.2	74.3	14.3	
42.0	26.8	14.9	31.8	14.6	36.3	14.5	40.6	14.2	44.7	14.1	48.6	13.7	52.4	13.5	56.1	13.4	59.2	14.1	62.8	14.1	66.3	14.1	69.8	14.0	73.3	13.4	
44.0	23.3	13.2	29.2	13.6	34.0	13.4	38.6	13.2	42.8	13.0	46.9	12.8	50.8	12.5	54.7	12.3	57.9	13.0	61.5	13.0	65.1	13.0	68.6	12.9	72.1	12.5	
46.0	19.9	13.5	26.3	12.7	31.5	12.5	36.3	12.2	40.8	12.1	45.1	11.8	49.1	11.6	53.1	11.5	56.4	11.2	60.1	12.0	63.8	12.0	67.4	12.0	70.9	11.7	
48.0			22.3	11.3	28.7	11.6	33.9	11.3	38.6	11.2	43.1	11.0	47.3	10.7	51.4	10.6	54.8	11.1	58.6	11.1	62.4	11.1	66.0	11.1	69.7	11.0	
50.0																											
52.0																											
54.0																											
56.0																											
58.0																											
60.0																											
62.0																											
64.0																											

クローラークレーン[油圧駆動式ウインチ・ラチェスジブ型]【350t吊】(1/2)

ブーム長さ (m)		18.0		24.0		30.0		36.0		42.0		48.0		54.0	
作業半径 (m)	フックの 地上高さ	定格 総荷重		フックの 地上高さ		定格 総荷重		フックの 地上高さ		定格 総荷重		フックの 地上高さ		定格 総荷重	
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
4.0	18.2	350.0													
4.5	18.1	330.0													
5.0	15.3	343.3	24.1	250.0											
5.5	17.8	298.0	22.9	309.5	30.1	250.0	36.2	250.0							
6.0	14.9	282.2	21.6	232.6	30.0	250.0	36.1	250.0	42.2	250.0					
7.0	14.5	247.3	21.1	229.1	27.5	191.4	34.8	199.9	42.0	211.0	48.1	196.0	54.2	172.0	
8.0	14.1	216.4	20.8	211.4	27.0	186.8	33.4	182.6	39.6	174.6	46.8	181.5	54.0	169.0	
9.0	13.6	184.9	20.4	195.1	26.8	182.3	33.0	180.1	39.3	174.2	45.5	162.2	52.7	153.1	
10.0	12.9	158.6	20.0	181.3	26.4	176.1	32.7	177.6	39.1	171.1	45.3	153.7	51.4	136.4	
12.0	11.4	120.7	18.9	149.8	25.6	152.1	32.1	150.6	38.6	147.8	44.8	143.3	51.0	130.5	
14.0	9.3	95.6	17.6	123.3	24.7	124.4	31.3	122.5	37.9	121.6	44.2	118.4	50.5	114.8	
16.0	6.2	77.8	16.0	101.5	23.5	103.3	30.4	102.1	37.2	101.7	43.6	99.7	49.9	97.2	
18.0	0.6	75.0	14.0	85.7	22.1	87.5	29.3	86.8	36.3	86.8	42.8	85.3	49.2	83.5	
20.0			11.4	73.5	20.5	75.5	28.1	74.8	35.3	75.1	42.0	74.0	48.5	72.5	
22.0			7.7	64.1	18.5	66.0	26.6	65.3	34.1	65.6	41.0	64.8	47.6	63.7	
24.0					16.1	58.3	25.0	57.7	32.8	57.9	39.9	57.3	46.7	56.3	
26.0					13.1	52.1	23.0	51.6	31.3	51.6	38.7	50.9	45.7	50.1	
28.0					9.1	47.4	20.8	46.4	29.6	46.3	37.3	45.7	44.5	44.8	
30.0							18.0	42.0	27.7	41.8	35.8	41.2	43.2	40.3	
32.0							14.8	38.6	25.5	38.0	34.1	37.4	41.8	36.5	
34.0							12.5	35.0	23.0	34.7	32.2	34.0	40.3	33.2	
36.0									20.0	31.7	29.9	31.3	38.5	30.4	
38.0									16.2	29.2	27.7	28.6	36.7	27.7	
40.0											24.2	26.2	34.1	25.3	
42.0											20.8	23.9	31.5	23.0	
44.0											19.8	23.3	28.6	21.2	
46.0													25.8	19.4	
48.0													23.1	18.5	
50.0															
52.0															
54.0															
56.0															
58.0															

クローラクレーン[油圧駆動式ウインチ・ラジジブ型]【350t吊】(2/2)

作業半径 (m)	60.0		66.0		72.0		78.0		84.0		90.0		96.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
4.0														
4.5														
5.0														
5.5														
6.0														
7.0	60.2	142.0												
8.0	60.1	138.0	66.1	120.0	72.2	101.0								
9.0	60.0	135.0	66.0	118.0	69.6	100.0	78.1	85.0	84.2	73.0				
10.0	57.5	122.1	64.7	112.4	71.9	98.0	78.0	84.0	84.0	72.0	90.1	62.0	96.1	53.0
12.0	57.1	118.0	63.2	105.4	69.3	98.6	77.7	82.0	83.8	71.0	89.8	60.0	95.9	51.0
14.0	56.7	111.3	62.8	101.6	69.0	94.9	77.4	80.0	83.5	70.0	89.5	59.0	95.6	49.5
16.0	56.2	94.2	62.4	91.4	68.5	87.8	77.0	77.0	83.1	68.0	89.2	57.0	95.3	48.0
18.0	55.6	81.3	61.8	79.0	68.0	76.4	76.5	68.0	82.7	65.0	88.8	56.0	94.9	46.5
20.0	54.9	70.9	61.2	68.9	67.5	66.8	76.0	61.0	82.2	58.0	88.4	54.0	94.5	44.5
22.0	54.1	62.3	60.6	60.9	66.9	58.9	75.5	54.0	81.7	52.0	87.9	50.0	94.1	43.5
24.0	53.3	55.2	59.8	53.9	66.2	52.4	74.9	49.0	81.1	47.5	87.4	45.5	93.6	42.0
26.0	52.4	49.1	59.0	48.1	65.5	46.6	74.2	44.5	80.5	43.0	86.8	41.0	93.0	39.5
28.0	51.4	43.9	58.1	43.0	64.7	41.8	73.4	40.5	79.8	39.0	86.2	37.5	92.5	36.0
30.0	50.3	39.4	57.1	38.6	63.8	37.4	72.6	37.0	79.1	36.0	85.5	34.0	91.8	33.0
32.0	49.1	35.6	56.0	34.8	62.8	33.7	71.8	34.0	78.3	33.0	84.8	31.0	91.1	30.0
34.0	47.8	32.3	54.9	31.5	61.8	30.4	70.8	31.5	77.4	30.0	84.0	28.7	90.4	27.5
36.0	46.3	29.5	53.6	28.7	60.7	27.5	69.8	29.0	76.5	27.8	83.1	26.3	89.6	25.3
38.0	44.8	26.8	52.3	26.0	59.5	25.0	68.8	26.7	75.5	25.6	82.2	24.2	88.8	23.2
40.0	42.6	24.3	50.4	23.4	58.2	22.8	67.6	24.6	74.5	23.7	81.3	22.3	87.9	21.3
42.0	40.4	21.9	48.4	20.9	56.0	19.6	66.3	22.8	73.3	22.0	80.2	20.7	86.9	19.7
44.0	38.2	20.2	46.6	19.1	55.3	18.8	65.0	20.9	72.2	20.3	79.1	19.0	86.0	18.1
46.0	36.0	18.4	44.8	17.3	52.9	15.6	63.6	19.4	70.9	18.9	78.0	17.6	84.9	16.7
48.0	33.4	16.8	42.7	15.7	52.0	15.4	62.1	17.9	69.6	17.4	76.8	16.2	83.8	15.3
50.0	30.7	15.2	40.6	14.0	49.3	12.4	60.4	16.6	68.1	16.1	75.4	15.0	82.6	14.1
52.0	28.3	14.8	38.0	12.7	48.1	12.6	58.8	15.3	66.6	14.7	74.1	13.8	81.3	12.9
54.0	23.7	12.5	35.5	11.3	45.1	9.7	56.9	14.2	64.9	13.6	72.6	12.8	80.0	11.9
56.0	22.2	14.8	32.2	10.2	43.6	10.2	54.9	13.1	63.2	12.5	71.1	11.7	78.6	10.9
58.0			29.0	9.0	40.2	7.4								

クローラクレーン[油圧駆動式ウインチ・リフティング型]【450t吊】(1/2)

ブーム長さ (m) 作業半径 (m)	18.29		21.0		24.0		30.0		36.0		42.0		48.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
5.8	16.1	450.0												
6.0	16.0	439.0												
7.0	15.6	383.0	18.5	382.8	21.7	382.6								
8.0	15.2	335.0	18.2	335.0	21.4	335.0	27.6	330.4						
9.0	14.7	295.0	17.7	295.0	21.0	295.0	27.4	295.0						
10.0	14.0	263.0	17.2	263.0	20.6	263.0	27.0	263.0	33.3	262.0				
12.0	12.5	208.0	16.0	207.1	19.5	206.1	26.2	206.0	32.7	205.2	39.0	201.5	45.2	198.6
14.0	10.5	165.9	14.4	165.9	18.2	165.9	25.3	165.9	31.9	165.7	38.3	164.4	44.6	162.2
16.0	7.6	136.3	12.3	136.3	16.6	136.2	24.1	136.1	31.0	135.8	37.6	135.5	44.0	135.9
18.0	2.0	115.2	9.6	115.2	14.6	115.2	22.7	114.9	29.9	114.5	36.7	114.2	43.2	114.5
20.0							21.1	99.0	28.7	98.6	35.7	98.2	42.4	98.5
22.0							19.1	86.7	27.2	86.2	34.5	85.7	41.4	86.0
24.0									25.6	76.3	33.2	75.8	40.3	76.0
26.0									23.6	68.2	31.7	67.7	39.1	67.8
28.0									21.4	61.5	30.0	61.0	37.7	61.1
30.0											28.1	55.3	36.2	55.3
32.0											25.8	50.8	34.4	50.7
34.0											23.4	46.3	32.6	46.2
36.0													30.3	42.8
38.0													28.1	39.3
40.0														
42.0														
44.0														
46.0														
48.0														
50.0														
52.0														
54.0														
56.0														
58.0														
60.0														
62.0														

クローラクレーン[油圧駆動式ウインチ・ラチェット型]【450t吊】(2/2)

作業半径 (m)	ブーム長さ (m)		54.0		60.0		66.0		72.0		78.0		84.0		90.0	
	フックの 地上高さ	(m)	定格 総荷重	(t)	フックの 地上高さ	(m)	定格 総荷重	(t)	フックの 地上高さ	(m)	定格 総荷重	(t)	フックの 地上高さ	(m)	定格 総荷重	(t)
5.8																
6.0																
7.0																
8.0																
9.0																
10.0																
12.0																
14.0	50.9	159.8	57.1	157.7												
16.0	50.3	134.2	56.6	132.1	62.8	130.3	122.5	68.9	122.5							
18.0	49.6	114.2	56.0	113.0	62.2	111.4	109.7	68.4	109.7	74.6	101.1	80.8	93.9			
20.0	48.9	98.2	55.3	97.7	61.6	96.7	95.1	67.9	95.1	74.1	93.7	80.3	90.6	86.5	81.9	
22.0	48.1	85.7	54.6	85.2	61.0	84.7	83.5	67.3	83.5	73.6	82.2	79.8	80.7	86.0	77.8	
24.0	47.1	75.7	53.7	75.2	60.2	74.7	74.0	66.6	74.0	73.0	72.8	79.2	71.3	85.5	70.2	
26.0	46.1	67.5	52.8	61.9	59.4	65.4	65.8	65.9	65.8	72.3	64.8	78.6	63.5	84.9	62.4	
28.0	44.9	60.7	51.8	60.1	58.5	59.6	58.9	65.1	58.9	71.5	58.2	77.9	56.9	84.3	55.8	
30.0	43.6	55.0	50.7	54.4	57.5	53.8	53.1	64.2	53.1	70.7	52.5	77.2	51.3	83.6	50.2	
32.0	42.2	50.4	49.4	49.8	56.4	49.2	48.5	63.2	48.5	69.8	47.9	76.4	46.7	82.8	45.6	
34.0	40.7	45.8	48.2	45.1	55.3	44.6	43.9	62.2	43.9	68.9	43.3	75.5	42.1	82.1	41.0	
36.0	38.9	42.3	46.7	41.6	54.0	41.0	40.3	61.0	40.3	67.9	39.8	74.6	38.6	81.2	37.5	
38.0	37.1	38.8	45.2	38.1	52.7	37.5	36.8	59.9	36.8	66.9	36.2	73.6	35.0	80.3	33.9	
40.0	34.9	36.0	43.4	35.4	51.2	34.8	34.0	58.6	34.0	65.7	33.3	72.6	32.2	79.3	31.1	
42.0	32.7	33.3	41.6	32.6	49.6	32.0	31.3	57.2	31.3	64.5	30.5	71.5	29.3	78.3	28.2	
44.0			39.4	30.4	47.9	29.8	29.0	55.7	29.0	63.1	28.1	70.3	26.9	77.2	25.9	
46.0			37.3	28.2	46.1	27.5	26.8	54.1	26.8	61.7	25.8	69.0	24.6	76.1	23.5	
48.0					43.9	25.7	24.8	52.3	24.8	60.2	23.8	67.6	22.6	74.8	21.6	
50.0					41.8	23.8	22.8	50.5	22.8	58.6	21.9	66.2	20.7	73.6	19.6	
52.0					39.2	22.1	21.1	48.4	21.1	56.8	20.2	64.7	19.0	72.1	18.0	
54.0					36.7	20.4	19.4	46.4	19.4	55.0	18.5	63.1	17.4	70.7	16.3	
56.0							17.9	43.9	17.9	52.9	17.0	61.3	15.9	69.1	14.9	
58.0							16.4	41.4	16.4	50.9	15.6	59.5	14.5	67.6	13.5	
60.0										48.5	14.3	57.4	13.2	65.8	12.3	
62.0										46.1	12.9	55.4	11.9	64.0	11.0	

クローラークレーン[油圧駆動式ウインチ・ラチェンギブ型]【500t吊】(1/2)

作業半径 (m)	ブーム長さ (m)		21.0		24.0		30.0		36.0		42.0		48.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
5.8	15.4	500.0	20.8	500.0										
7.0	15.0	429.9	19.7	432.2	26.7	435.3								
8.0	14.7	376.2	19.4	375.3	25.6	370.7	32.7	370.8	38.8	368.5				
9.0	14.2	334.3	19.0	324.8	25.3	321.9	31.6	319.6	38.6	315.0	44.7	313.0		
10.0	13.7	297.3	18.5	285.6	25.0	283.7	31.3	281.8	37.5	277.1	44.5	273.2		
12.0	12.5	233.8	17.5	231.2	24.2	225.4	30.7	223.9	37.0	220.2	44.0	216.0		
14.0	10.9	191.0	16.2	186.5	23.3	185.1	29.9	184.1	36.3	181.5	43.4	177.0		
16.0	8.8	158.6	14.6	157.9	22.1	151.7	29.0	151.6	35.6	151.1	42.8	147.0		
18.0	6.1	133.3	12.6	134.7	20.7	127.3	27.9	127.0	34.7	126.5	42.0	122.6		
20.0	1.6	114.5	10.0	111.1	19.1	109.0	26.7	108.7	33.7	108.1	41.1	104.5		
22.0			6.3	89.5	17.1	94.0	25.2	93.6	32.5	93.1	40.2	90.5		
24.0					14.7	83.2	23.6	82.8	31.2	82.1	39.1	79.3		
26.0					11.7	74.5	21.6	73.9	29.7	73.2	37.9	70.1		
28.0					7.5	65.2	19.4	66.3	28.0	65.5	36.5	62.5		
30.0							16.6	59.9	26.1	59.0	35.0	56.2		
32.0							14.0	52.7	24.7	51.6	33.3	50.6		
34.0									21.4	48.7	31.4	46.0		
36.0									19.1	42.9	29.3	41.9		
38.0									14.6	41.1	26.8	38.3		
40.0											24.0	35.2		
42.0											20.8	32.0		
44.0											16.7	29.9		
46.0														
48.0														
50.0														
52.0														
54.0														
56.0														
58.0														
60.0														
62.0														
64.0														

クローラクレーン[油圧駆動式ウインチ・ラジジブ型]【500t吊】 (2/2)

作業半径 (m)	54.0		60.0		66.0		72.0		78.0		84.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
5.8												
7.0												
8.0												
9.0												
10.0	50.6	270.7	56.7	249.1								
12.0	50.2	213.9	56.3	212.1	62.5	207.0	68.6	188.8				
14.0	49.7	175.1	55.8	173.5	62.0	172.0	68.1	172.1	74.3	162.1	80.4	141.5
16.0	49.1	146.3	55.3	145.7	61.5	144.2	67.7	144.0	73.8	143.1	80.0	137.6
18.0	48.4	122.0	54.7	121.8	61.0	121.2	67.2	119.8	73.4	120.0	79.6	119.3
20.0	47.7	103.8	54.1	103.6	60.4	103.0	66.7	101.8	72.9	101.8	79.1	101.2
22.0	46.8	89.8	53.3	89.4	59.7	88.8	66.1	87.7	72.3	87.7	78.6	87.0
24.0	45.9	78.5	52.5	78.1	59.0	77.5	65.4	76.4	71.7	76.4	78.0	75.7
26.0	44.8	69.4	51.6	68.9	58.2	68.2	64.6	67.1	71.0	67.1	77.4	66.5
28.0	43.7	61.8	50.6	61.3	57.3	60.6	63.8	59.4	70.3	59.4	76.7	58.8
30.0	42.4	55.4	49.5	54.8	56.3	54.1	63.0	53.0	69.5	52.9	76.0	52.1
32.0	41.0	49.8	48.3	49.2	55.2	48.4	62.0	47.4	68.6	47.3	75.2	46.6
34.0	39.5	45.0	46.9	44.5	54.1	43.7	61.0	42.6	67.7	42.4	74.3	41.7
36.0	37.8	40.9	45.5	40.3	52.8	39.5	59.9	38.5	66.7	38.2	73.4	37.5
38.0	35.9	37.3	43.9	36.7	51.5	35.8	58.7	34.8	65.6	34.4	72.4	33.8
40.0	33.8	34.1	42.2	33.4	50.0	32.6	57.4	31.5	64.5	31.1	71.4	30.4
42.0	31.5	30.9	40.4	30.2	48.5	29.3	56.0	28.2	63.3	27.9	70.3	27.0
44.0	28.8	28.7	38.3	27.8	46.7	27.0	54.5	25.8	61.9	25.3	69.1	24.3
46.0	25.8	26.1	36.1	25.2	44.9	24.3	53.0	22.9	60.6	22.4	67.9	21.3
48.0	22.2	24.5	33.5	23.2	42.8	22.2	51.2	20.9	59.0	20.3	66.4	19.2
50.0			30.7	20.8	40.6	19.8	49.4	18.5	57.4	17.8	65.1	16.7
52.0			27.4	19.2	38.1	18.1	47.3	16.9	55.6	16.0	63.5	15.0
54.0			23.7	17.1	35.5	16.0	45.2	14.8	53.8	14.0	61.9	12.8
56.0					32.4	14.7	42.8	13.6	51.8	12.7	60.1	11.6
58.0					29.1	12.9	40.2	11.8	49.7	10.9	58.3	9.7
60.0							37.3	10.7	47.3	9.7	56.3	8.6
62.0							34.2	9.0	44.9	8.1	54.2	6.9
64.0							30.5	8.1	42.1	7.1	52.0	5.6

クローラクレーン[油圧駆動式ウインチ・ラジジブ型・基礎工事用]【70t吊】(1/2)

ブーム長さ (m) 作業半径 (m)	12.2		12.5		15.5		18.5		21.5		24.5		27.5		30.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.7	9.7	70.0														
4.0	9.6	65.0														
5.0	9.2	53.2	9.5	53.1												
6.0	8.7	41.3	9.0	41.2	12.7	41.1	15.6	41.1	18.7	41.1						
7.0	8.0	32.6	8.4	32.5	11.9	32.4	15.2	32.4	18.4	32.4	21.5	32.3	24.6	32.2	27.7	32.1
8.0	7.3	26.9	7.7	26.8	11.3	26.7	14.7	26.7	18.0	26.7	21.2	26.6	24.4	26.5	27.5	26.4
9.0	6.3	22.8	6.7	22.7	10.7	22.6	14.2	22.6	17.6	22.6	20.8	22.5	24.0	22.4	27.2	22.3
10.0	5.0	19.7	5.6	19.6	9.9	19.5	13.6	19.5	17.1	19.5	20.4	19.4	23.7	19.3	26.9	19.2
12.0				15.7	7.9	15.6	12.1	15.6	15.9	15.5	19.4	15.4	22.8	15.3	26.1	15.2
14.0				12.9	4.7	12.8	10.1	12.8	14.4	12.6	18.2	12.5	21.7	12.4	25.2	12.3
16.0						10.7	7.3	10.7	12.4	10.6	16.6	10.5	20.4	10.3	24.0	10.2
18.0									9.8	9.0	14.7	8.9	18.8	8.8	22.7	8.7
20.0											12.2	7.7	16.9	7.6	21.1	7.5
22.0											8.8	6.8	14.6	6.7	19.2	6.5
24.0													11.5	5.9	16.9	5.8
26.0															14.0	5.1
28.0																
30.0																
32.0																
34.0																
36.0																
38.0																
40.0																
42.0																

クローラクレーン[油圧駆動式ウインチ・リフティング型・基礎工事用]【70t吊】（2／2）

ブーム長さ (m) 作業半径 (m)	33.5		36.5		39.5		42.5		45.5		48.5		51.5		54.5	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)		
3.7																
4.0																
5.0																
6.0																
7.0																
8.0	30.6	26.3														
9.0	30.3	22.2	33.4	22.1	36.5	22.0										
10.0	30.0	19.1	33.2	19.0	36.3	18.9	39.4	18.8	42.4	18.7						
12.0	29.3	15.1	32.5	15.0	35.7	14.9	38.8	14.9	41.9	14.7	45.0	14.6	48.1	13.6	51.2	13.2
14.0	28.5	12.2	31.8	12.1	35.0	12.0	38.2	12.0	41.3	11.8	44.5	11.7	47.6	11.6	50.7	11.2
16.0	27.5	10.1	30.9	10.0	34.2	9.9	37.4	9.9	40.6	9.7	43.8	9.6	47.0	9.5	50.2	9.4
18.0	26.3	8.6	29.8	8.5	33.2	8.3	36.6	8.3	39.8	8.2	43.1	8.1	46.3	7.9	49.5	7.8
20.0	24.9	7.4	28.6	7.3	32.1	7.1	35.6	7.1	38.9	7.0	42.2	6.8	45.5	6.7	48.8	6.6
22.0	23.3	6.4	27.2	6.3	30.9	6.2	34.4	6.1	37.9	6.0	41.3	5.8	44.6	5.7	47.9	5.6
24.0	21.4	5.6	25.6	5.5	29.4	5.4	33.1	5.3	36.7	5.2	40.2	5.0	43.6	4.9	47.0	4.8
26.0	19.2	5.0	23.7	4.9	27.8	4.7	31.7	4.7	35.4	4.5	39.0	4.4	42.5	4.3	46.0	4.2
28.0	16.4	4.5	21.5	4.3	25.9	4.2	30.0	4.1	33.9	4.0	37.7	3.8	41.3	3.7	44.8	3.6
30.0	13.0	4.0	18.8	3.9	23.8	3.7	28.2	3.7	32.3	3.5	36.2	3.3	39.9	3.2	43.6	3.1
32.0					21.2	3.3	26.0	3.2	30.4	3.1	34.5	2.9	38.4	2.8	42.2	2.6
34.0							23.6	2.9	28.3	2.7	32.6	2.5	36.7	2.4	40.6	2.2
36.0									25.9	2.4	30.6	2.2	34.9	2.0	39.0	1.8
38.0									23.1	2.0	28.2	1.9	32.8	1.7	37.1	1.5
40.0											25.5	1.6	30.5	1.4	35.1	1.2
42.0													27.9	1.1		

クローラクレーン[油圧駆動式ウインチ・ラチェット型・基礎工事用]【80t吊】(1/2)

ブーム長さ (m) 作業半径 (m)		9.5		12.5		15.5		18.5		21.5		24.5		27.5		30.5	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
	3.4	5.6	80.0														
	4.0	5.3	70.0	8.5	69.5												
	5.0	4.8	56.3	9.3	56.5	12.5	56.4	14.5	54.2								
	6.0	4.1	46.4	8.8	45.7	12.1	45.6	15.4	45.4	18.5	45.2						
	7.0	3.1	36.8	8.2	36.3	11.7	36.2	15.0	36.2	18.2	36.1	21.3	36.1	24.4	36.0	27.6	35.8
	8.0	1.8	30.4	7.5	30.0	11.1	29.9	14.5	29.8	17.8	29.7	21.0	29.7	24.2	29.6	27.3	29.5
	9.0	1.5	25.9	6.5	25.5	10.5	25.4	14.0	25.3	17.4	25.2	20.6	25.1	23.8	25.0	27.0	24.9
	10.0			5.4	22.2	9.7	22.0	13.4	21.9	16.9	21.9	20.2	21.7	23.5	21.7	26.7	21.5
	12.0			0.2	17.6	7.7	17.3	11.9	17.2	15.7	17.1	19.2	17.0	22.6	16.9	25.9	16.8
	14.0					4.5	14.1	9.9	14.1	14.2	14.0	18.0	13.8	21.5	13.8	24.9	13.6
	16.0							7.1	11.9	12.2	11.8	16.4	11.6	20.2	11.5	23.8	11.4
	18.0									9.6	10.1	14.5	9.9	18.6	9.9	22.5	9.7
	20.0											12.0	8.6	16.7	8.6	20.9	8.4
	22.0											8.6	7.6	14.4	7.5	19.0	7.4
	24.0													11.3	6.7	16.7	6.5
	26.0															13.8	5.8
	28.0																
	30.0																
	32.0																
	34.0																
	36.0																
	38.0																
	40.0																
	42.0																
	44.0																
	46.0																

クローラクレーン[油圧駆動式ウインチ・リフスジブ型・基礎工事用]【80t吊】（2／2）

ブーム長さ (m) 作業半径 (m)	33.5		36.5		39.5		42.5		45.5		48.5		51.5		54.5	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)				
3.4																
4.0																
5.0																
6.0																
7.0																
8.0	30.4	29.5	33.6	29.3												
9.0	30.1	24.9	33.2	24.8	36.3	24.7	39.5	22.2								
10.0	29.8	21.5	33.0	21.4	36.1	21.3	39.2	21.3	42.2	19.0						
12.0	29.1	16.7	32.3	16.6	35.5	16.5	38.6	16.5	41.7	16.4	44.8	16.3	47.9	13.8	51.0	13.2
14.0	28.3	13.6	31.6	13.4	34.8	13.3	38.0	13.3	41.1	13.2	44.3	13.1	47.4	13.0	50.5	12.7
16.0	27.3	11.3	30.7	11.2	34.0	11.1	37.2	11.0	40.4	10.9	43.6	10.8	46.8	10.7	49.9	10.6
18.0	26.1	9.7	29.6	9.5	33.0	9.4	36.4	9.3	39.6	9.2	42.9	9.1	46.1	9.0	49.3	8.9
20.0	24.7	8.3	28.4	8.2	31.9	8.1	35.4	8.0	38.7	7.9	42.0	7.8	45.3	7.7	48.5	7.6
22.0	23.1	7.3	27.0	7.2	30.7	7.0	34.2	7.0	37.7	6.9	41.1	6.7	44.4	6.6	47.7	6.5
24.0	21.2	6.5	25.4	6.3	29.2	6.2	32.9	6.1	36.5	6.0	40.0	5.9	43.4	5.8	46.8	5.6
26.0	19.0	5.8	23.5	5.6	27.6	5.5	31.5	5.4	35.2	5.3	38.8	5.1	42.3	5.0	45.7	4.9
28.0	16.2	5.2	21.3	5.0	25.7	4.9	29.8	4.8	33.7	4.7	37.5	4.5	41.1	4.4	44.6	4.3
30.0	12.8	4.7	18.6	4.5	23.5	4.4	28.0	4.3	32.1	4.2	36.0	4.0	39.7	3.9	43.4	3.8
32.0			14.2	4.1	21.0	3.9	25.8	3.8	30.2	3.7	34.3	3.6	38.2	3.5	42.0	3.3
34.0					16.8	3.6	23.4	3.5	28.1	3.3	32.4	3.2	36.5	3.1	40.4	2.9
36.0							19.3	3.1	25.7	3.0	30.4	2.9	34.7	2.7	38.8	2.5
38.0							15.7	2.8	22.9	2.7	28.0	2.5	32.6	2.4	36.9	2.2
40.0									18.4	2.4	25.3	2.2	30.3	2.1	34.9	1.9
42.0											20.9	2.0	27.7	1.8	32.6	1.6
44.0													23.5	1.6	30.0	1.3
46.0															27.2	1.1

クローラクレーン[油圧駆動式ワインチ・リフティング型・基礎工事用]【90t吊】（1／2）

作業半径 (m)	12.2		12.5		15.5		18.5		21.5		24.5		27.5		30.5		33.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.7	9.5	90.0																
4.0	9.4	84.0																
4.5	9.2	77.1																
5.0	9.0	70.2	9.4	70.2	12.3	70.3	15.0	70.8										
6.0	8.5	55.1	8.9	55.1	12.0	55.0	15.2	54.9	18.3	54.8	21.0	54.9						
7.0	7.9	43.5	8.3	43.5	11.5	43.7	14.8	43.6	18.0	43.5	21.2	43.4	24.3	43.3	27.4	43.3		
8.0	7.1	35.9	7.5	35.9	11.0	36.0	14.4	35.9	17.6	35.7	20.8	35.7	24.0	35.6	27.1	35.5	30.2	35.4
9.0	6.1	30.4	6.6	30.4	10.3	30.5	13.8	30.3	17.2	30.2	20.5	30.1	23.7	30.0	26.8	30.0	29.9	29.9
10.0	4.9	26.4	5.4	26.4	9.5	26.4	13.2	26.3	16.7	26.2	20.0	26.0	23.3	25.9	26.5	25.9	29.6	25.7
12.0					7.5	20.7	11.8	20.6	15.5	20.4	19.0	20.3	22.4	20.2	25.7	20.2	29.0	20.0
14.0					4.6	16.9	9.8	16.8	14.0	16.6	17.8	16.5	21.3	16.4	24.8	16.3	28.1	16.2
16.0							7.2	14.0	12.0	14.0	16.2	13.8	20.0	13.7	23.6	13.6	27.1	13.5
18.0									9.4	12.0	14.3	11.8	18.5	11.7	22.3	11.6	25.9	11.4
20.0											11.8	10.3	16.5	10.1	20.7	10.1	24.5	9.9
22.0											8.7	8.9	14.2	8.9	18.8	8.8	22.9	8.6
24.0													11.3	7.8	16.5	7.8	21.0	7.6
26.0															13.6	7.0	18.8	6.8
28.0																	16.1	6.1
30.0																	12.8	5.4
32.0																		
34.0																		
36.0																		
38.0																		
40.0																		
42.0																		

クローラークレーン[油圧駆動式ウインチ・ラフジブ型・基礎工専用]【90t吊】（2／2）

作業半径 (m)	36.5		39.5		42.5		45.5		48.5		51.5		54.5		57.5		60.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.7																		
4.0																		
4.5																		
5.0																		
6.0																		
7.0																		
8.0	33.3	35.3																
9.0	33.0	29.8	36.1	29.7	39.4	29.3												
10.0	32.8	25.6	35.9	25.5	39.0	25.5	42.1	25.3	45.4	19.5	47.8	19.4	50.8	19.2	53.9	19.1		
12.0	32.1	19.9	35.3	19.8	38.4	19.7	41.6	19.5	44.7	15.7	47.2	15.5	50.3	15.4	53.4	15.3	56.5	15.1
14.0	31.4	16.1	34.6	16.0	37.8	15.9	41.0	15.7	44.1	12.9	46.6	12.8	49.8	12.7	52.9	12.6	56.0	12.4
16.0	30.5	13.4	33.8	13.2	37.0	13.2	40.3	13.0	43.5	10.9	45.9	10.8	49.1	10.6	52.3	10.5	55.4	10.4
18.0	29.4	11.3	32.8	11.2	36.2	11.1	39.5	10.9	42.7	9.3	45.1	9.2	48.4	9.0	51.6	8.9	54.8	8.8
20.0	28.2	9.8	31.7	9.7	35.2	9.5	38.5	9.3	41.9	8.1	44.2	7.9	47.5	7.7	50.8	7.6	54.0	7.5
22.0	26.8	8.5	30.5	8.4	34.0	8.2	37.5	8.1	40.9	7.0	43.2	6.9	46.6	6.7	49.9	6.6	53.2	6.4
24.0	25.2	7.5	29.0	7.4	32.7	7.2	36.3	7.1	39.8	6.2	42.1	6.0	45.6	5.9	49.0	5.7	52.3	5.6
26.0	23.3	6.7	27.4	6.6	31.3	6.4	35.0	6.2	38.6	5.5	40.9	5.3	44.4	5.1	47.9	5.0	51.3	4.8
28.0	21.1	6.0	25.5	5.8	29.6	5.7	33.5	5.5	37.3	4.9	39.5	4.7	43.2	4.5	46.7	4.4	50.2	4.2
30.0	18.5	5.4	23.4	5.2	27.8	5.0	31.9	4.9	35.8	4.3	38.0	4.1	41.8	4.0	45.4	3.9	49.0	3.7
32.0			20.8	4.7	25.6	4.5	30.0	4.4	34.1	3.9	36.4	3.7	40.3	3.5	44.0	3.4	47.7	3.2
34.0			17.3	4.4	23.2	4.1	27.9	3.9	32.3	3.4	34.5	3.3	38.6	3.1	42.5	2.9	46.3	2.7
36.0					19.8	3.8	25.5	3.5	30.2	3.1	32.4	2.9	36.7	2.7	40.8	2.5	44.8	2.3
38.0							22.7	3.2	27.8	2.7	30.1	2.5	34.7	2.3	39.0	2.1	43.1	1.9
40.0									25.1	2.5	27.5	2.1	32.4	1.9	36.9	1.7	40.8	1.7
42.0									21.5	2.5								

クローラクレーン[油圧駆動式ウインチ・ラジジブ型・基礎工事用]【100t吊】（1／2）

ブーム長さ (m) 作業半径 (m)	12.0		12.5		15.5		18.5		21.5		24.5		27.5		30.5		33.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.8	8.9	100.0																
4.0	8.8	95.0																
5.0	8.4	75.9	9.0	75.9	12.0	74.7	15.0	73.7										
6.0	7.9	63.2	8.5	63.2	11.6	62.1	14.9	63.2	17.9	62.6	21.0	61.3						
7.0	7.3	53.8	7.9	53.8	11.2	52.2	14.5	52.7	17.7	52.4	20.8	52.1	23.9	51.5	26.9	50.4		
8.0	6.5	44.4	7.1	44.4	10.6	43.1	14.0	43.5	17.3	43.4	20.5	43.2	23.7	42.9	26.8	42.7	29.8	42.2
9.0	5.5	37.7	6.2	37.7	9.9	36.6	13.5	36.9	16.9	36.8	20.1	36.7	23.3	36.5	26.5	36.3	29.6	36.1
10.0	4.1	32.7	5.0	32.6	9.2	31.7	12.9	31.9	16.4	31.9	19.7	31.8	23.0	31.7	26.2	31.5	29.3	31.3
12.0					7.1	24.2	11.4	25.1	15.2	25.0	18.7	24.9	22.1	24.8	25.4	24.7	28.6	24.6
14.0					4.2	20.9	9.4	20.5	13.7	20.4	17.5	20.3	21.0	20.2	24.5	20.1	27.8	20.0
16.0								17.9	11.7	17.2	15.9	17.0	19.7	16.9	23.3	16.8	26.8	16.7
18.0									9.1	14.5	14.0	14.6	18.1	14.5	22.0	14.4	25.6	14.2
20.0									6.3	16.7	11.5	12.8	16.2	12.6	20.4	12.5	24.2	12.4
22.0											8.4	11.6	13.9	11.1	18.5	11.0	22.6	10.8
24.0													11.0	10.2	16.2	9.7	20.7	9.6
26.0															13.3	8.8	18.5	8.6
28.0															10.5	10.2	15.7	7.7
30.0																	12.4	6.9
32.0																		
34.0																		
36.0																		
38.0																		
40.0																		
42.0																		
44.0																		
46.0																		

クローラークレーン[油圧駆動式ウインチ・リフティング型・基礎工事用]【100t吊】(2/2)

ブーム長さ (m) 作業半径 (m)	36.5		39.5		42.5		45.5		48.5		51.5		54.5		57.5		60.5	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
3.8																		
4.0																		
5.0																		
6.0																		
7.0																		
8.0	32.9	41.8																
9.0	32.7	35.8	35.7	35.4	40.0	36.8												
10.0	32.5	31.1	35.6	30.9	38.7	30.6	41.7	30.3	45.9	30.2								
12.0	31.8	24.4	35.0	24.3	38.1	24.1	41.2	23.9	44.3	23.7	47.4	23.3	50.4	22.0	53.5	19.6		
14.0	31.1	19.8	34.3	19.7	37.5	19.6	40.6	19.4	43.8	19.3	46.9	19.2	50.0	18.9	53.1	18.1	56.1	17.3
16.0	30.2	16.5	33.5	16.5	36.7	16.3	39.9	16.2	43.1	16.1	46.3	16.0	49.5	15.8	52.6	15.5	55.6	15.0
18.0	29.1	14.1	32.5	14.0	35.9	13.9	39.1	13.8	42.4	13.7	45.6	13.6	48.8	13.4	52.0	13.2	55.0	13.1
20.0	27.9	12.2	31.4	12.1	34.9	12.0	38.2	11.8	41.5	11.7	44.8	11.7	48.1	11.5	51.3	11.3	54.4	11.2
22.0	26.5	10.7	30.2	10.6	33.7	10.5	37.2	10.3	40.6	10.2	43.9	10.1	47.2	9.9	50.5	9.8	53.6	9.7
24.0	24.9	9.4	28.7	9.3	32.4	9.2	36.0	9.1	39.5	9.0	42.9	8.9	46.3	8.7	49.6	8.6	52.8	8.5
26.0	23.0	8.4	27.1	8.3	31.0	8.2	34.7	8.1	38.3	7.9	41.8	7.9	45.3	7.7	48.6	7.5	51.9	7.4
28.0	20.8	7.6	25.2	7.5	29.3	7.3	33.2	7.2	37.0	7.1	40.6	7.0	44.1	6.8	47.6	6.7	50.9	6.6
30.0	18.1	6.8	23.1	6.7	27.5	6.6	31.6	6.4	35.5	6.3	39.2	6.2	42.9	6.1	46.4	5.9	49.8	5.9
32.0	15.1	6.1	20.5	6.1	25.3	6.0	29.7	5.8	33.8	5.7	37.7	5.6	41.5	5.4	45.1	5.3	48.6	5.2
34.0			17.4	5.5	22.9	5.4	27.6	5.2	31.9	5.1	36.0	5.0	39.9	4.8	43.7	4.7	47.3	4.6
36.0					19.9	4.9	25.2	4.7	29.9	4.6	34.2	4.5	38.3	4.4	42.2	4.2	45.9	4.1
38.0							22.4	4.3	27.5	4.2	32.1	4.1	36.4	3.9	40.5	3.8	44.4	3.7
40.0							19.2	3.8	24.8	3.8	29.8	3.7	34.4	3.5	38.7	3.4	42.7	3.3
42.0									21.6	3.4	27.2	3.3	32.1	3.1	36.6	3.0	40.8	2.9
44.0											24.1	3.0	29.5	2.8	34.4	2.6	40.0	3.6
46.0													26.8	2.4	32.1	2.2	37.7	3.2

クローラクレーン[油圧駆動式ウインチ・ラチェンブ型・基礎工事用]【150t吊】(1/2)

フーム長さ (m) 作業半径 (m)	15.0		15.5		18.5		21.5		24.5		27.5		30.5		33.5		36.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
4.5	10.6	150.0																
5.0	10.4	135.1																
6.0	10.0	113.4	10.6	113.4	14.1	118.8	18.3	127.4										
7.0	9.6	97.5	10.1	97.5	13.7	102.9	16.9	102.6	20.0	99.5								
8.0	9.0	85.5	9.6	85.4	13.2	87.8	16.5	87.6	19.7	87.3	22.9	85.8	26.0	80.6	30.1	83.8		
9.0	8.3	71.7	8.9	71.7	12.7	74.1	16.1	74.3	19.4	74.3	22.6	74.1	25.7	73.7	28.8	70.6	31.9	65.6
10.0	7.5	61.4	8.1	61.4	12.1	64.3	15.6	64.5	18.9	64.4	22.2	64.3	25.4	64.3	28.5	64.2	31.7	63.0
12.0	5.3	47.4	6.1	47.4	10.6	49.9	14.4	50.0	17.9	50.0	21.3	50.0	24.6	49.9	27.8	49.8	31.0	49.7
14.0	1.7	38.4	2.9	38.4	8.7	40.3	12.9	40.5	16.7	40.4	20.2	40.4	23.7	40.3	27.0	40.1	30.3	40.1
16.0					5.9	33.7	10.9	33.9	15.1	33.8	18.9	33.7	22.5	33.6	26.0	33.5	29.4	33.4
18.0							8.3	28.9	13.2	28.9	17.4	28.8	21.2	28.7	24.8	28.5	28.3	28.5
20.0							5.5	28.8	10.7	25.1	15.4	25.0	19.6	24.9	23.4	24.7	27.1	24.6
22.0									7.3	22.1	13.1	22.0	17.7	21.9	21.8	21.7	25.7	21.6
24.0											10.0	19.6	15.4	19.4	19.9	19.3	24.1	19.2
26.0													12.5	17.4	17.7	17.3	22.2	17.2
28.0													9.7	18.0	15.0	15.6	20.0	15.5
30.0															11.5	14.2	17.4	14.0
32.0																	13.8	12.4
34.0																		
36.0																		
38.0																		
40.0																		
42.0																		
44.0																		
46.0																		
48.0																		
50.0																		
52.0																		
54.0																		

クローラクレーン【油圧駆動式ウインチ・ラチェット型・基礎工事用】【150t吊】（2／2）

作業半径 (m)	39.5		42.5		45.5		48.5		51.5		54.5		57.5		60.5		63.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
4.5																		
5.0																		
6.0																		
7.0																		
8.0																		
9.0	36.1	70.2																
10.0	34.8	58.9	38.9	70.0	42.0	56.9												
12.0	34.2	49.6	37.3	49.2	40.5	46.7	43.6	43.4	46.6	41.4	50.8	43.7	53.8	42.0				
14.0	33.5	40.0	36.7	39.9	39.9	39.8	43.0	39.4	46.1	37.4	49.2	34.7	52.3	32.5	55.4	30.0	58.2	25.8
16.0	32.7	33.3	35.9	33.2	39.2	33.0	42.3	33.0	45.5	32.8	48.7	31.9	51.8	30.0	54.9	28.0	57.7	24.3
18.0	31.7	28.3	35.1	28.2	38.4	28.1	41.6	28.0	44.8	27.8	48.0	27.7	51.2	27.3	54.3	25.4	57.2	22.8
20.0	30.6	24.5	34.1	24.4	37.4	24.3	40.7	24.2	44.0	24.1	47.3	23.9	50.5	23.7	53.7	23.2	56.6	20.7
22.0	29.4	21.5	32.9	21.4	36.4	21.2	39.8	21.2	43.1	21.0	46.4	20.9	49.7	20.7	52.9	20.5	55.9	18.8
24.0	27.9	19.0	31.6	18.9	35.2	18.8	38.7	18.7	42.1	18.5	45.5	18.4	48.8	18.2	52.1	18.1	55.1	17.2
26.0	26.3	17.0	30.2	16.9	33.9	16.8	37.5	16.7	41.0	16.5	44.5	16.4	47.9	16.3	51.2	16.2	54.2	15.6
28.0	24.4	15.3	28.5	15.2	32.4	15.1	36.2	15.0	39.8	14.8	43.3	14.6	46.8	14.5	50.2	14.4	53.3	13.9
30.0	22.3	13.9	26.7	13.8	30.8	13.6	34.7	13.5	38.4	13.3	42.1	13.1	45.6	13.0	49.1	13.0	52.3	12.5
32.0	19.7	12.7	24.5	12.5	28.9	12.4	33.0	12.3	36.9	12.1	40.7	11.9	44.3	11.8	47.9	11.7	51.1	11.3
34.0	16.4	11.2	22.1	11.5	26.8	11.3	31.2	11.2	35.2	11.0	39.2	10.8	42.9	10.6	46.6	10.6	49.9	10.3
36.0			18.9	10.2	24.4	10.3	29.1	10.2	33.4	10.1	37.5	9.9	41.4	9.7	45.2	9.6	48.6	9.3
38.0					21.6	9.5	26.7	9.4	31.3	9.2	35.6	9.0	39.7	8.9	43.6	8.8	47.2	8.5
40.0					18.0	8.5	24.0	8.6	29.0	8.4	33.6	8.2	37.9	8.1	42.0	8.0	45.6	7.8
42.0							20.5	7.8	26.4	7.8	31.3	7.6	35.8	7.4	40.1	7.3	43.9	7.1
44.0									23.0	7.1	28.7	7.0	33.6	6.8	38.1	6.7	42.1	6.4
46.0											25.8	6.4	31.1	6.2	35.9	6.1	40.1	5.8
48.0											22.1	5.8	28.2	5.6	33.4	5.5	37.9	5.3
50.0													24.7	5.1	30.6	4.9	35.4	4.8
52.0															27.2	4.6	32.7	4.3
54.0																	29.7	3.9

クローラークレーン[油圧伸縮ジブ型]【4.9t吊】

ブーム長さ (m) 作業半径 (m)	4.25		7.0		10.0		13.0		15.9	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
1.0	5.0	4.9								
1.5	4.9	4.9	7.8	4.8						
2.0	4.7	4.9	7.6	4.8	10.7	2.5				
2.5	4.4	4.9	7.3	4.8	10.6	2.5	13.7	1.8		
3.0	3.9	4.7	7.2	4.6	10.5	2.5	13.6	1.8		
3.5	3.3	3.7	6.9	4.0	10.2	2.7	13.3	2.1		
4.0			6.5	3.3	10.0	2.7	13.2	2.1	15.9	2.6
4.5			6.3	2.7	9.7	2.6	13.0	2.1	15.8	2.6
5.0			5.8	2.3	9.5	2.4	12.8	2.0	15.6	2.6
6.0			4.5	1.7	8.8	1.9	12.3	1.7	15.2	2.0
7.0			0.9	1.6	8.1	1.5	11.9	1.4	14.7	1.7
8.0					6.9	1.2	11.0	1.3	14.2	1.4
9.0					5.3	1.0	10.2	1.1	13.6	1.2
10.0							9.1	0.9	12.9	1.0
12.0							5.8	0.7	10.9	0.8
14.0									8.0	0.6

クローラクレーン[油圧伸縮ジブ型]【40t吊】

ブーム長さ (m) 作業半径 (m)	10.5		12.0		13.0		16.0		18.0		21.0	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.0	8.4	40.0										
2.5	8.3	40.0	9.9	35.4	10.9	32.4						
3.0	8.2	40.0	9.8	35.4	10.8	32.4						
3.5	8.0	40.0	9.6	35.4	10.7	32.4	13.8	23.2	15.8	20.5		
4.0	7.8	40.0	9.5	34.6	10.5	31.1	13.6	23.2	15.7	20.5	18.8	17.0
4.5	7.6	36.5	9.3	32.1	10.3	29.2	13.5	21.8	15.6	20.3	18.7	17.0
5.0	7.4	30.5	9.0	28.5	10.1	27.2	13.3	20.1	15.4	18.6	18.5	15.3
6.0	6.8	22.7	8.5	22.7	9.7	22.7	13.0	17.4	15.1	15.8	18.3	13.1
7.0	6.0	17.8	7.9	17.8	9.1	17.8	12.5	15.4	14.7	13.7	17.9	11.4
8.0	4.9	14.5	7.1	14.5	8.4	14.5	12.0	13.7	14.3	12.0	17.6	10.1
9.0							11.4	12.0	13.7	10.7	17.1	8.9
10.0							10.6	10.3	13.1	9.5	16.6	7.9
12.0							8.7	7.8	11.6	7.7	15.4	6.4
14.0											13.8	5.3
16.0											11.7	4.5

クローラクレーン[油圧伸縮ジブ型]【50t吊】(1/2)

ブーム長さ (m) 作業半径 (m)	11.3		13.0		16.0		18.0		21.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.0	11.4	50.0								
2.5	11.3	50.0	13.0	45.6	16.1	37.8	18.1	32.6		
3.0	11.1	50.0	12.9	45.6	16.0	37.8	18.0	32.6		
3.5	11.0	50.0	12.8	45.6	15.9	37.8	17.9	32.6		
4.0	10.8	46.4	12.6	42.8	15.7	36.4	17.8	32.1	20.9	27.9
4.5	10.6	42.0	12.5	39.4	15.6	34.7	17.7	31.6	20.8	27.9
5.0	10.4	36.4	12.3	35.0	15.5	32.5	17.5	30.8	20.7	27.9
6.0	9.8	26.7	11.8	26.6	15.1	26.6	17.2	26.6	20.4	25.3
6.5	9.5	23.4	11.5	23.4	14.9	23.4	17.0	23.4	20.2	22.6
7.0	9.1	20.6	11.2	20.6	14.6	20.6	16.8	20.6	20.1	20.2
8.0	8.2	15.8	10.5	16.0	14.1	16.3	16.4	16.5	19.7	16.5
9.0	7.1	11.4	9.6	11.9	13.5	12.8	15.8	13.4	19.2	13.8
10.0									18.7	11.6
12.0									17.5	8.5
14.0									15.9	6.4
16.0									13.9	4.9
18.0										
20.0										
22.0										
24.0										

クローラクレーン[油圧伸縮ジブ型]【50t吊】(2/2)

ブーム長さ (m) 作業半径 (m)	24.0		27.0		30.0		33.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.0								
2.5								
3.0								
3.5								
4.0	23.9	24.8						
4.5	23.8	24.8						
5.0	23.7	24.8						
6.0	23.5	23.4	26.6	21.3	29.6	17.5	32.7	13.8
6.5	23.4	21.4	26.5	20.0	29.5	16.8	32.6	13.5
7.0	23.2	19.6	26.3	18.7	29.4	16.0	32.5	13.3
8.0	22.9	16.3	26.0	16.0	29.2	14.4	32.3	12.8
9.0	22.5	13.8	25.7	13.7	28.9	12.9	32.0	12.0
10.0	22.1	11.6	25.3	11.5	28.5	11.1	31.7	10.7
12.0	21.0	8.5	24.4	8.5	27.8	8.5	31.0	8.5
14.0	19.7	6.4	23.3	6.4	26.8	6.6	30.1	6.8
16.0	18.1	4.9	22.0	5.0	25.6	5.2	29.1	5.4
18.0			20.4	3.7	24.3	4.1	27.9	4.4
20.0			18.4	2.7	22.6	3.1	26.5	3.4
22.0			15.9	1.9	20.7	2.2	24.9	2.6
24.0			12.6	1.2	18.3	1.5	22.9	1.9

クローラクレーン[油圧伸縮ジブ型]【55t吊】 (1/2)

ブーム長さ (m) 作業半径 (m)	9.97		12.0		13.0		16.0		18.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0	9.9	55.0	12.1	46.9	13.1	42.9	16.2	30.8	18.2	26.8
3.5	9.7	50.0	11.9	43.4	13.0	40.1	16.1	30.3	18.1	26.8
4.0	9.5	42.5	11.8	38.1	12.8	36.0	15.9	29.5	18.0	26.8
4.5	9.3	36.5	11.6	33.9	12.7	32.7	15.8	28.9	17.9	26.8
5.0	9.0	31.7	11.4	30.6	12.5	30.0	15.7	28.4	17.7	26.8
6.0	8.3	23.4	10.8	23.4	12.0	23.3	15.3	23.2	17.4	22.9
7.0	7.5	18.3	10.2	18.3	11.4	18.3	14.8	18.1	17.0	18.0
8.0									16.6	14.6
9.0									16.0	12.3
10.0									15.4	10.4
12.0									13.9	7.8
14.0									11.8	6.0
16.0										
18.0										
20.0										

クローラクレーン[油圧伸縮ジブ型]【55t吊】(2/2)

ブーム長さ (m) 作業半径 (m)	21.0		24.0		27.0		30.0	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
3.0	21.2	24.2	24.3	21.3	27.3	17.7	30.3	14.1
3.5	21.2	24.2	24.2	21.3	27.2	17.7	30.3	14.1
4.0	21.1	24.2	24.1	21.3	27.2	17.7	30.2	14.1
4.5	21.0	24.2	24.0	21.3	27.1	17.7	30.1	14.1
5.0	20.9	24.2	23.9	21.3	27.0	17.7	30.0	14.1
6.0	20.6	22.4	23.7	21.3	26.8	17.7	29.8	14.1
7.0	20.3	17.9	23.4	17.5	26.5	15.5	29.6	13.6
8.0	19.9	14.5	23.1	14.3	26.2	13.4	29.4	12.6
9.0	19.4	12.2	22.7	12.0	25.9	11.8	29.1	11.6
10.0	18.9	10.3	22.3	10.3	25.5	10.5	28.7	10.7
12.0	17.7	7.7	21.2	7.7	24.6	7.9	28.0	8.1
14.0	16.1	5.9	19.9	5.9	23.5	6.1	27.0	6.3
16.0			18.3	4.7	22.2	4.8	25.8	5.0
18.0			16.3	3.7	20.6	3.9	24.5	4.1
20.0			13.7	3.0	18.6	3.2	22.8	3.3

クローラクレーン[油圧伸縮ジブ型]【65t吊】 (1/2)

作業半径 (m)	10.0		12.0		13.0		16.0		18.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.0	8.4	65.0								
2.5	8.3	65.0								
3.0	8.2	65.0	10.2	55.2	11.3	50.2	14.3	35.5		
3.5	8.0	55.0	10.1	48.1	11.1	44.7	14.2	34.4		
4.0	7.8	48.0	9.9	43.2	11.0	40.8	14.1	33.7	16.2	30.8
4.5	7.6	41.5	9.7	38.7	10.8	37.3	14.0	33.0	16.0	30.8
5.0	7.3	37.0	9.5	35.1	10.6	34.1	13.8	31.2	15.9	29.6
5.5	7.0	34.0	9.3	32.5	10.4	31.7	13.6	29.3	15.8	28.1
6.0	6.6	32.5	9.0	30.7	10.2	29.8	13.5	27.1	15.6	25.8
7.0	5.8	26.3	8.4	25.3	9.6	24.8	13.0	23.3	15.2	22.5
8.0									14.7	19.3
9.0									14.2	16.5
10.0									13.6	14.1
12.0									12.0	10.5
14.0										
16.0										
18.0										

クローラクレーン[油圧伸縮ジブ型]【65t吊】 (2/2)

ブーム長さ (m) 作業半径 (m)	21.0		24.0		27.0		30.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.0								
2.5								
3.0								
3.5								
4.0	19.2	28.2						
4.5	19.1	28.2						
5.0	19.0	27.6	22.1	25.1	25.2	20.6	28.2	16.2
5.5	18.9	26.4	22.0	24.2	25.1	20.2	28.1	16.1
6.0	18.7	24.3	21.9	22.4	24.9	19.2	28.0	16.1
7.0	18.4	21.2	21.6	19.8	24.7	17.9	27.8	16.1
8.0	18.0	18.5	21.2	17.6	24.4	16.3	27.5	15.0
9.0	17.6	15.9	20.9	15.3	24.1	14.4	27.2	13.4
10.0	17.1	13.8	20.4	13.4	23.7	12.7	26.9	12.0
12.0	15.9	10.4	19.4	10.3	22.8	10.1	26.1	9.9
14.0			18.1	7.9	21.7	8.0	25.2	8.0
16.0			16.5	6.0	20.4	6.3	24.0	6.5
18.0			14.5	4.7	18.7	4.9	22.6	5.2

クローラークレーン[油圧伸縮ジブ型]【75t吊】 (1/2)

ブーム長さ (m) 作業半径 (m)	9.99		12.0		13.0		16.0		18.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0	9.9	75.0	12.0	63.3	13.0	57.5	16.1	40.1	18.1	34.6
3.5	9.8	60.0	11.9	52.8	12.9	49.2	16.0	38.5	18.0	34.6
4.0	9.6	51.0	11.7	46.5	12.8	44.3	15.9	37.6	17.9	34.6
4.5	9.3	44.5	11.5	42.5	12.6	41.2	15.7	37.0	17.8	34.6
5.0	9.1	39.5	11.3	39.0	12.4	38.2	15.6	35.6	17.7	33.8
5.5	8.7	36.0	11.1	35.8	12.2	35.2	15.4	33.4	17.5	32.2
6.0	8.4	34.4	10.8	33.5	11.9	32.9	15.2	31.1	17.4	30.4
7.0	7.5	28.9	10.1	28.4	11.3	28.2	14.8	27.4	17.0	26.4
8.0									16.5	22.7
9.0									16.0	19.2
10.0									15.4	16.5
12.0									13.8	12.4
14.0									11.7	9.7
16.0										
18.0										
20.0										

クローラクレーン[油圧伸縮ジブ型]【75t吊】(2/2)

作業半径 (m)	ブーム長さ (m)	21.0		24.0		27.0		30.0	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0		21.2	31.5	24.2	28.1	27.2	23.4	30.2	18.7
3.5		21.1	31.5	24.1	28.1	27.2	23.4	30.2	18.7
4.0		21.0	31.5	24.1	28.1	27.1	23.4	30.1	18.7
4.5		20.9	31.5	24.0	28.1	27.0	23.4	30.1	18.7
5.0		20.8	31.2	23.9	28.1	26.9	23.4	30.0	18.7
5.5		20.7	30.4	23.8	28.1	26.8	23.4	29.9	18.7
6.0		20.5	29.6	23.6	28.1	26.7	23.4	29.8	18.7
7.0		20.2	24.6	23.3	22.8	26.5	20.7	29.6	18.6
8.0		19.8	21.2	23.0	19.9	26.2	19.2	29.3	18.5
9.0		19.4	18.6	22.6	17.9	25.8	16.7	29.0	15.5
10.0		18.9	16.4	22.2	16.1	25.5	14.8	28.7	13.5
12.0		17.6	12.4	21.2	12.3	24.6	12.1	27.9	11.8
14.0		16.0	9.6	19.9	9.6	23.5	9.7	26.9	9.9
16.0				18.3	7.7	22.1	7.9	25.8	8.2
18.0				16.3	6.2	20.5	6.5	24.4	6.7
20.0				13.7	5.0	18.5	5.3	22.8	5.5

トラックスレーン[油圧伸縮ジブ型]【4.9t吊】

作業半径 (m) ブーム長 (m)	5.6		8.0		10.0		12.0		14.0		16.0		18.0		20.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.0	6.7	4.9	9.2	3.9	11.2	3.2	13.3	3.1								
2.5	6.4	4.9	8.5	4.7	10.6	4.6	12.6	4.5	14.5	4.4	16.6	4.0				
3.0	6.2	4.0	8.1	4.8	10.2	4.7	12.5	4.5	14.6	4.1	16.6	3.7	18.5	3.3	20.5	2.6
3.5	5.8	3.2	7.8	4.7	10.0	4.7	12.1	4.7	14.2	4.3	16.3	3.8	18.4	3.3	20.5	2.6
4.0	5.3	2.7	7.6	4.4	9.8	4.4	12.0	4.3	14.1	3.9	16.1	3.5	18.3	3.1	20.4	2.5
4.5	4.8	2.2	7.3	3.6	9.6	3.7	11.8	3.7	13.9	3.5	16.0	3.2	18.0	2.9	20.1	2.4
5.0	3.9	1.8	6.9	3.1	9.3	3.1	11.6	3.1	13.7	3.0	15.9	3.0	17.9	2.7	19.9	2.3
5.5			6.4	2.7	9.0	2.7	11.3	2.7	13.5	2.7	15.7	2.7	17.7	2.5	19.8	2.1
6.0			5.9	2.4	8.7	2.3	11.0	2.4	13.3	2.4	15.5	2.4	17.5	2.2	19.7	1.9
7.0					8.6	1.1	10.4	1.8	12.8	1.9	15.0	1.9	17.2	1.8	19.3	1.6
8.0					7.4	0.9	9.6	1.5	12.1	1.5	14.5	1.5	16.7	1.5	18.9	1.3
9.0					5.8	0.7	8.6	1.2	11.4	1.2	13.9	1.3	16.2	1.3	18.4	1.2
10.0							7.2	1.1	10.5	1.0	13.1	1.1	15.5	1.1	17.9	1.0
11.0							5.6	0.9	9.5	0.8	12.5	0.9	15.0	0.9	17.5	0.9
12.0									8.6	0.4	12.0	0.4	14.0	0.8	16.6	0.8
13.0									6.6	0.4	10.8	0.4	13.0	0.7	15.8	0.7
14.0													11.9	0.6	14.9	0.6

トラッククレーン[油圧伸縮ジブ型]【7.0t吊】

作業半径 (m) ブーム長 (m)	6.6		8.0		10.0		12.0		14.0		16.0		18.0		20.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.0	6.7	7.0														
2.5	6.5	7.0														
3.0	6.3	6.1	7.8	5.8	10.0	5.3										
3.5	6.0	5.3	7.6	5.2	9.8	5.0	11.9	4.8	14.0	4.4	16.0	4.0				
4.0	5.7	4.6	7.3	4.5	9.6	4.5	11.7	4.4	13.8	4.0	15.9	3.7				
4.5	5.2	3.8	7.0	3.8	9.3	3.8	11.5	3.8	13.7	3.6	15.8	3.3	17.8	2.9	19.9	2.3
5.0	4.7	3.2	6.7	3.2	9.1	3.2	11.3	3.2	13.5	3.2	15.6	3.1	17.7	2.7	19.8	2.3
5.5	4.1	2.7	6.2	2.7	8.8	2.8	11.1	2.8	13.3	2.8	15.4	2.8	17.6	2.5	19.6	2.1
6.0	3.2	2.4	5.7	2.4	8.4	2.4	10.8	2.5	13.1	2.5	15.2	2.5	17.4	2.2	19.5	1.9
7.0							10.2	1.9	12.5	1.9	14.8	2.0	17.0	1.8	19.1	1.6
8.0							9.4	1.6	11.9	1.6	14.3	1.6	16.5	1.5	18.7	1.3
9.0							8.4	1.3	11.1	1.3	13.6	1.3	16.0	1.2	18.3	1.2
10.0							7.0	1.1	10.2	1.1	12.9	1.1	15.4	1.1	17.7	1.0
12.0													13.8	0.8	16.4	0.8
14.0													11.7	0.6	14.7	0.6

トラッククレーン[油圧伸縮ジブ型]【16t吊】

ブーム長 (m) 作業半径 (m)	5.9		8.0		10.0		12.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0	5.6	16.0						
3.5	5.3	16.0	7.7	13.0				
4.0	4.9	13.0	7.5	11.8				
4.5	4.4	10.5	7.2	10.1				
5.0	3.7	8.5	6.8	8.7	9.2	8.7	11.5	8.2
5.5					8.9	8.0	11.2	7.2
6.0					8.6	7.4	10.9	6.7
7.0					7.7	6.2	10.3	5.7
8.0					6.6	4.9	9.5	4.9

トラッククレーン[油圧伸縮ジブ型]【20t吊】 (1/2)

作業半径 (m)	フーム長 (m)	5.7		8.0		10.0		12.0		14.0		16.0		18.0	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.0		6.2	20.0												
2.5		5.9	20.0	8.4	20.0	10.1	20.0	12.2	18.6	14.2	17.1	16.2	15.4		
3.0		5.7	20.0	8.2	13.8	9.9	19.9	11.9	18.5	14.0	17.0	16.0	15.3	18.1	13.0
3.5		5.3	16.0	8.0	12.6	9.7	19.9	11.8	18.5	13.9	17.0	15.9	15.3	18.0	13.0
4.0		4.9	13.0	7.7	11.6	9.5	18.0	11.6	17.7	13.7	17.0	15.8	15.3	17.9	13.0
4.5		4.3	10.5	7.4	10.0	9.6	10.8	11.8	9.9	13.6	15.6	15.7	14.9	17.7	13.0
5.0						9.4	9.9	11.6	9.2	13.4	14.2	15.5	13.6	17.6	12.1
5.5						9.2	9.5	11.5	8.8	13.3	13.6	15.4	13.0	17.5	11.8
6.0						9.1	9.2	11.4	8.4	13.2	13.1	15.3	12.5	17.5	11.4
7.0						8.7	8.4	11.1	7.8	13.0	12.1	15.1	11.6	17.3	10.8
8.0						7.8	7.1	10.5	6.6	12.4	10.0	14.7	9.9	16.9	9.5
9.0						6.3	8.7	9.3	8.5	11.8	8.4	14.2	8.4	16.4	8.2
10.0										11.0	7.1	13.5	7.1	15.9	7.1
12.0										10.1	6.1	12.8	6.0	15.3	6.1
14.0														13.7	4.2
16.0														11.6	3.1
18.0															
20.0															
22.0															
24.0															
26.0															

トラッククレーン[油圧伸縮ジブ型]【20t吊】(2/2)

作業半径 (m) ブーム長 (m)	20.0		22.0		24.0		26.0		28.0		30.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.0												
2.5												
3.0	20.1	10.1										
3.5	20.0	10.1	22.1	8.6	24.2	7.5						
4.0	19.9	10.1	21.9	8.6	24.0	7.5	26.0	6.9				
4.5	19.8	10.1	21.8	8.6	23.9	7.5	25.9	6.9				
5.0	19.7	10.0	21.7	8.6	23.8	7.5	25.8	6.9	27.9	6.4	29.9	6.1
5.5	19.6	9.9	21.7	8.6	23.7	7.5	25.8	6.9	27.8	6.4	29.8	6.1
6.0	19.5	9.9	21.6	8.6	23.7	7.5	25.7	6.9	27.8	6.4	29.8	6.1
7.0	19.4	9.7	21.5	8.6	23.6	7.5	25.6	6.9	27.7	6.4	29.7	6.1
8.0	19.0	9.0	21.2	8.3	23.3	7.5	25.4	6.9	27.4	6.4	29.5	6.1
9.0	18.6	8.0	20.8	7.6	22.9	7.1	25.1	6.6	27.1	6.1	29.2	5.8
10.0	18.2	7.0	20.4	6.8	22.6	6.5	24.7	6.0	26.8	5.6	28.9	5.3
12.0	17.6	6.3	19.9	6.2	22.1	5.9	24.3	5.5	26.5	5.1	28.6	4.8
14.0	16.3	4.4	18.8	4.6	21.1	4.7	23.4	4.5	25.6	4.3	27.8	4.1
16.0	14.6	3.2	17.3	3.4	19.8	3.5	22.2	3.5	24.6	3.6	26.8	3.5
18.0			15.4	2.5	18.2	2.6	20.8	2.7	23.3	2.8	25.7	2.8
20.0			13.0	1.9	16.2	2.0	19.1	2.1	21.8	2.1	24.3	2.2
22.0					13.6	1.5	16.9	1.6	19.9	1.7	22.7	1.8
24.0					9.9	1.1	14.2	1.2	17.6	1.3	20.7	1.3
26.0									14.7	0.9	18.3	1.0

トラッククレーン[油圧伸縮ジブ型]【25t吊】(1/2)

ブーム長 (m) 作業半径 (m)	10.5		12.0		14.0		16.0		18.0		20.0	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.5	10.7	25.0	12.2	23.0	14.2	20.3	16.3	18.1	18.3	16.0		
3.0	10.8	25.0	12.4	23.0	14.4	20.3	16.5	18.1	18.5	16.0		
3.5	10.7	25.0	12.2	23.0	14.3	20.3	16.4	18.1	18.4	16.0	20.4	13.8
4.0	10.5	22.9	12.1	21.7	14.2	20.2	16.2	18.1	18.3	16.0	20.3	13.8
4.5	10.2	21.0	11.9	20.6	14.0	20.1	16.1	18.1	18.2	16.0	20.2	13.8
5.0	10.0	19.4	11.7	19.0	13.8	18.5	16.0	17.3	18.0	16.0	20.1	13.8
5.5	10.0	17.7	11.7	17.3	13.9	16.9	16.0	15.8	18.2	14.8	20.3	13.3
6.0	9.4	16.2	11.1	15.8	13.4	15.4	15.6	14.5	17.7	13.7	19.8	12.8
7.0	8.6	13.7	10.5	13.3	12.9	12.7	15.1	12.3	17.3	12.0	19.5	11.4
8.0	7.6	11.5	9.7	11.1	12.2	10.7	14.6	10.6	16.9	10.6	19.1	10.4
9.0							14.0	8.9	16.3	8.8	18.6	9.0
10.0							13.2	7.2	15.7	7.2	18.1	7.4
12.0							11.3	5.0	14.2	5.0	16.8	5.2
14.0									12.1	3.6	15.0	3.8
16.0									9.0	2.5	12.8	2.7
18.0												
20.0												
22.0												
24.0												
26.0												

トラッククレーン[油圧伸縮ジブ型]【25t吊】 (2/2)

作業半径 (m) ジブ全長 (m)	22.0		24.0		26.0		28.0		30.0		32.0	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.5												
3.0												
3.5												
4.0	22.4	12.0	24.4	11.7								
4.5	22.3	12.0	24.3	11.7								
5.0	22.2	12.0	24.2	11.7	26.3	11.2	28.3	9.8				
5.5	22.3	12.0	24.4	11.7	26.4	11.2	28.5	9.8	30.5	8.6	32.5	7.5
6.0	21.9	12.0	24.0	11.7	26.1	11.2	28.1	9.8	30.1	8.6	32.2	7.5
7.0	21.6	10.9	23.7	10.4	25.8	9.9	27.9	9.3	29.9	8.6	32.0	7.5
8.0	21.2	10.1	23.4	9.4	25.5	8.8	27.6	8.4	29.7	8.0	31.7	7.3
9.0	20.8	9.1	23.0	8.5	25.1	8.0	27.3	7.6	29.4	7.2	31.5	6.6
10.0	20.3	7.6	22.6	7.4	24.8	7.2	26.9	6.9	29.0	6.5	31.2	6.0
12.0	19.2	5.4	21.5	5.6	23.8	5.7	26.1	5.7	28.2	5.5	30.4	5.0
14.0	17.7	4.0	20.2	4.1	22.7	4.2	25.0	4.3	27.3	4.3	29.5	4.2
16.0	15.9	3.0	18.6	3.1	21.2	3.2	23.7	3.3	26.1	3.4	28.5	3.4
18.0	13.4	2.2	16.6	2.3	19.5	2.5	22.2	2.6	24.8	2.7	27.2	2.7
20.0	9.9	1.6	14.0	1.7	17.4	1.9	20.3	2.0	23.1	2.1	25.7	2.1
22.0					14.6	1.4	18.1	1.5	21.2	1.6	24.0	1.6
24.0									19.0	1.2	22.2	1.3
26.0									15.7	0.9	19.4	0.9

トラックスクレーン（油圧伸縮ジブ型）【30t吊】（1／2）

作業半径 (m) ブーム長 (m)	10.75		12		14		16		18		20		22	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.5	10.8	30.0												
3.0	10.6	30.0	11.9	27.9	14.0	24.5	16.0	21.7	18.1	19.1				
3.5	10.5	30.0	11.8	27.9	13.9	24.5	15.9	21.7	18.0	19.1	20.0	17.1	22.0	15.3
4.0	10.3	26.4	11.6	25.5	13.7	24.0	15.8	21.7	17.9	19.1	19.9	17.1	22.0	15.3
4.5	10.1	23.9	11.5	23.3	13.6	22.4	15.7	20.8	17.8	19.0	19.8	17.1	21.9	15.3
5.0	9.8	21.4	11.2	21.2	13.4	20.9	15.5	20.0	17.6	18.8	19.7	17.1	21.8	15.3
5.5	9.6	19.2	11.0	19.1	13.2	18.9	15.4	18.3	17.5	17.6	19.6	16.5	21.6	15.2
6.0	9.2	17.1	10.7	17.0	13.0	16.9	15.2	16.7	17.3	16.4	19.4	15.8	21.5	15.1
7.0	8.5	14.8	10.1	14.7	12.5	14.6	14.7	14.6	16.9	14.6	19.1	14.2	21.2	13.6
8.0	7.5	12.4	9.3	12.4	11.8	12.4	14.2	12.4	16.5	12.4	18.7	12.3	20.8	12.0
9.0	6.2	10.4	8.3	10.3	11.0	10.1	13.6	10.1	15.9	10.1	18.2	10.1	20.4	10.1
10.0							12.8	8.5	15.3	8.4	17.6	8.4	19.9	8.4
12.0							10.9	6.1	13.7	6.0	16.3	6.0	18.8	6.0
14.0											14.6	4.5	17.3	4.5
16.0											12.3	3.3	15.4	3.3
18.0														
20.0														
22.0														
24.0														
26.0														
28.0														
30.0														
32.0														

トラッククレーン（油圧伸縮ジブ型）【30t吊】（2/2）

作業半径 (m)	ブーム長 (m)	24		26		28		30		32		34	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.5													
3.0													
3.5													
4.0													
4.5													
5.0		23.8	14.1	25.8	13.1	27.9	11.6	29.9	10.1				
5.5		23.7	14.1	25.7	13.1	27.8	11.6	29.8	10.1				
6.0		23.6	14.1	25.6	13.1	27.7	11.6	29.7	10.1	31.8	9.0	33.8	8.0
7.0		23.3	13.0	25.4	12.3	27.4	11.2	29.5	10.1	31.6	9.0	33.6	8.0
8.0		23.0	11.5	25.1	11.0	27.2	10.5	29.2	10.0	31.3	9.0	33.4	8.0
9.0		22.6	10.1	24.7	9.8	26.8	9.4	28.9	8.9	31.0	8.5	33.1	8.0
10.0		22.1	8.4	24.3	8.4	26.5	8.4	28.6	8.1	30.7	7.8	32.8	7.4
12.0		21.1	6.0	23.4	6.0	25.6	6.0	27.8	6.0	30.0	6.0	32.1	6.0
14.0		19.8	4.5	22.2	4.5	24.6	4.5	26.9	4.5	29.1	4.5	31.3	4.5
16.0		18.2	3.3	20.8	3.3	23.3	3.3	25.7	3.3	28.0	3.3	30.3	3.3
18.0		16.2	2.8	19.1	2.8	21.8	2.8	24.3	2.8	26.8	2.8	29.2	2.8
20.0		13.6	2.2	16.9	2.2	19.9	2.2	22.7	2.2	25.3	2.2	27.8	2.2
22.0						17.6	1.9	20.7	1.9	23.6	1.9	26.2	1.9
24.0						14.7	1.5	18.3	1.5	21.5	1.5	24.4	1.5
26.0										19.0	1.3	22.2	1.3
28.0										15.8	1.0	19.6	1.0
30.0												16.3	0.8
32.0												11.8	0.6

トラッククレーン[油圧伸縮ジブ型]【35t吊】(1/2)

作業半径 (m)	フーム長 (m)	11.0		12.0		14.0		16.0		18.0		20.0		22.0	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0		11.2	35.0	12.2	33.3	14.3	29.8	16.3	26.5	18.4	23.5				
3.5		11.0	35.0	12.1	33.3	14.2	29.8	16.2	26.5	18.3	23.5				
4.0		10.8	31.8	11.9	30.6	14.0	28.9	16.1	26.5	18.2	23.5				
4.5		10.6	28.5	11.7	28.0	13.9	27.1	16.0	25.5	18.0	23.2	20.1	21.1	22.1	19.4
5.0		10.4	26.2	11.5	25.8	13.7	25.0	15.8	23.8	17.9	22.6	20.0	21.1	22.0	19.4
5.5		10.1	23.8	11.3	23.5	13.5	22.8	15.6	22.1	17.7	21.4	19.8	20.3	21.9	18.8
6.0		9.8	21.6	10.8	21.5	13.1	20.7	15.4	20.2	17.6	19.5	19.7	18.6	21.8	17.6
7.0		9.1	20.0	10.4	19.5	12.7	18.5	15.0	17.7	17.2	17.0	19.3	16.3	21.5	15.6
8.0		8.2	15.6	9.5	15.6	12.1	15.7	14.5	15.4	16.7	14.9	18.9	14.3	21.1	13.7
9.0		6.9	13.1	8.5	13.1	11.3	13.0	13.8	12.9	16.2	12.8	18.5	12.6	20.7	12.1
10.0								13.1	10.7	15.6	10.6	17.9	10.5	20.2	10.3
12.0								11.2	7.4	14.0	7.4	16.6	7.5	19.0	7.7
14.0												14.9	5.4	17.6	5.6
16.0												12.6	4.0	15.7	4.2
18.0															
20.0															
22.0															
24.0															

トラックスレーン[油圧伸縮ジブ型]【35t吊】(2/2)

作業半径 (m) フーム長 (m)	24.0		26.0		28.0		30.0		32.0		34.0	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
3.0												
3.5												
4.0												
4.5	24.2	17.6	26.2	15.9								
5.0	24.1	17.6	26.1	15.9								
5.5	24.0	17.3	26.0	15.8								
6.0	23.8	16.5	25.9	15.5								
7.0	23.6	15.0	25.6	14.3	27.7	13.4	29.8	12.1	31.8	10.9	33.9	9.6
8.0	23.2	13.2	25.3	12.6	27.4	11.9	29.5	11.1	31.6	10.2	33.7	9.4
9.0	22.9	11.6	25.0	11.1	27.1	10.6	29.2	10.0	31.3	9.5	33.4	8.9
10.0	22.4	10.2	24.6	10.0	26.8	9.7	28.9	9.2	31.0	8.7	33.1	8.2
12.0	21.4	7.9	23.7	8.1	25.9	8.0	28.1	7.6	30.3	7.3	32.4	7.0
14.0	20.1	5.8	22.5	6.0	24.9	6.1	27.1	6.0	29.4	5.9	31.6	5.8
16.0	18.5	4.4	21.1	4.6	23.6	4.7	26.0	4.8	28.3	4.9	30.6	5.0
18.0					22.1	3.7	24.6	3.8	27.1	3.9	29.4	4.0
20.0					20.2	2.9	23.0	3.0	25.6	3.1	28.1	3.2
22.0					17.9	2.3	21.0	2.4	23.8	2.5	26.5	2.6
24.0					15.0	1.7	18.6	1.8	21.8	1.9	24.7	2.0

トラックスレーン[油圧伸縮ジブ型]【45t吊】(1/2)

作業半径 (m)	ブーム長 (m)	11.0		12.0		14.0		16.0		18.0		20.0		22.0	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
3.0	11.0	45.0													
3.5	10.8	40.0	11.9	37.1	31.3	13.9	25.5	16.0	25.5						
4.0	10.6	36.4	11.7	34.2	29.6	13.8	25.1	15.9	25.1	17.9	22.9	20.0	21.5	22.0	20.0
4.5	10.4	33.0	11.5	31.3	28.1	13.6	24.8	15.7	24.8	17.8	22.9	19.9	21.5	21.9	20.0
5.0	10.2	29.5	11.3	28.5	26.5	13.5	24.5	15.6	24.5	17.7	22.9	19.8	21.5	21.8	20.0
5.5	9.9	26.4	11.0	25.9	24.9	13.3	23.9	15.4	23.9	17.5	22.7	19.6	21.3	21.7	20.0
6.0	9.6	23.3	10.8	23.3	23.3	13.0	23.3	15.2	23.3	17.4	22.4	19.5	21.2	21.6	20.0
7.0	8.9	18.0	10.1	18.0	18.0	12.5	18.0	14.8	18.0	17.0	18.0	19.1	18.0	21.2	18.0
8.0	7.9	14.0	9.3	14.0	14.0	11.9	14.0	14.2	14.0	16.5	14.0	18.7	14.0	20.9	14.0
9.0	6.7	11.3	8.3	11.3	11.3	11.1	11.3	13.6	11.3	16.0	11.3	18.3	11.3	20.5	11.3
10.0										15.4	9.3	17.7	9.3	20.0	9.3
12.0										13.8	6.4	16.4	6.4	18.8	6.4
14.0										11.7	4.6	14.7	4.6	17.4	4.6
16.0														15.5	3.1
18.0														13.0	2.1
20.0														9.6	1.3
22.0															
24.0															

トラックスレーン[油圧伸縮ジブ型]【45t吊】(2/2)

作業半径 (m)	ブーム長 (m)	24.0		26.0		28.0		30.0		32.0		34.0	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
3.0													
3.5													
4.0													
4.5													
5.0		23.9	18.4	25.9	16.8								
5.5		23.7	18.4	25.8	16.8								
6.0		23.6	18.4	25.7	16.8	27.7	15.0	29.8	13.0	31.8	11.0	33.9	9.0
7.0		23.3	17.2	25.4	16.4	27.5	15.0	29.6	13.0	31.6	11.0	33.7	9.0
8.0		23.0	13.8	25.1	13.7	27.2	13.2	29.3	12.4	31.4	11.0	33.4	9.0
9.0		22.6	11.2	24.8	11.2	26.9	11.1	29.0	11.0	31.1	10.2	33.2	8.7
10.0		22.2	9.2	24.4	9.2	26.5	9.3	28.7	9.5	30.8	9.2	32.9	8.4
12.0		21.2	6.4	23.5	6.4	25.7	6.5	27.9	6.7	30.1	6.8	32.2	6.8
14.0		19.9	4.5	22.3	4.5	24.6	4.6	26.9	4.8	29.2	5.1	31.4	5.3
16.0		18.3	3.0	20.9	3.0	23.4	3.1	25.8	3.4	28.1	3.7	30.4	3.9
18.0		16.3	2.0	19.2	2.0	21.8	2.1	24.4	2.4	26.8	2.6	29.2	2.8
20.0		13.7	1.3	17.0	1.2	20.0	1.3	22.8	1.6	25.4	1.8	27.9	2.0
22.0						17.7	0.7	20.8	1.0	23.6	1.2	26.3	1.3
24.0										21.6	0.6	24.5	0.8

トラッククレーン[油圧伸縮ジブ型]【50t吊】 (1/2)

作業半径 (m)	ブーム長 (m)	10.65		12.0		14.0		16.0		18.0		20.0		22.0		24.0	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
3.0		10.4	50.0	11.8	46.3	13.8	40.4	15.9	34.5	17.9	28.6						
3.5		10.2	43.0	11.6	40.5	13.7	36.4	15.7	32.4	17.8	28.4						
4.0		10.0	38.0	11.4	36.3	13.6	33.6	15.6	30.9	17.7	28.3	19.7	25.9	21.8	23.6	23.8	21.2
4.5		9.8	34.0	11.3	33.0	13.4	31.4	15.5	29.8	17.6	28.2	19.6	25.9	21.7	23.6	23.7	21.2
5.0		9.5	30.2	11.0	29.8	13.2	29.2	15.3	28.7	17.4	28.1	19.5	25.9	21.6	23.6	23.6	21.2
5.5		9.3	27.5	10.8	27.2	13.0	26.7	15.2	26.2	17.3	25.7	19.4	24.2	21.4	22.4	23.5	20.7
6.0		8.9	25.0	10.5	24.8	12.8	24.4	15.0	24.0	17.1	23.6	19.2	22.6	21.3	21.4	23.4	20.3
7.0		8.2	20.7	9.9	20.6	12.3	20.4	14.5	20.3	16.7	20.1	18.9	19.4	21.0	18.7	23.1	17.9
8.0		7.2	17.4	9.1	17.3	11.6	17.2	14.0	17.1	16.3	17.0	18.5	16.6	20.6	16.2	22.8	15.7
9.0		5.8	14.9	8.1	14.7	10.9	14.7	13.4	14.6	15.7	14.5	18.0	14.3	20.2	14.1	22.4	13.8
10.0										15.1	12.2	17.5	12.0	19.7	11.9	22.0	11.9
12.0										13.6	8.6	16.1	8.4	18.6	8.4	20.9	8.3
14.0										11.5	6.3	14.4	6.1	17.1	6.1	19.6	6.0
16.0										8.4	4.5	12.1	4.4	15.2	4.4	18.0	4.4
18.0																	
20.0																	
22.0																	
24.0																	
26.0																	
28.0																	
30.0																	
32.0																	
34.0																	
36.0																	
38.0																	
40.0																	

トラッククレーン[油圧伸縮ジブ型]【50t吊】(2/2)

作業半径 (m)	ブーム長 (m)	26.0		28.0		30.0		32.0		34.0		36.0		38.0		40.0	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
3.0																	
3.5																	
4.0		25.8	18.3														
4.5		25.7	18.3														
5.0		25.6	18.3	27.7	16.9	29.7	15.8	31.7	14.6								
5.5		25.5	19.0	27.6	17.5	29.6	16.0	31.7	14.6								
6.0		25.4	19.0	27.5	17.5	29.5	16.0	31.6	14.6	33.6	13.4	35.6	11.8	37.6	10.3	39.7	8.7
7.0		25.2	17.1	27.2	16.1	29.3	15.1	31.4	14.1	33.4	12.8	35.4	11.3	37.5	9.8	39.5	8.2
8.0		24.9	15.2	27.0	14.5	29.0	13.7	31.1	13.0	33.2	12.0	35.2	10.8	37.3	9.5	39.3	8.2
9.0		24.5	13.5	26.6	12.9	28.8	12.3	30.8	11.7	32.9	11.0	35.0	10.0	37.1	9.1	39.1	8.1
10.0		24.1	11.7	26.3	11.4	28.4	11.0	30.5	10.6	32.6	10.0	34.7	9.3	36.8	8.5	38.9	7.7
12.0		23.2	8.3	25.4	8.4	27.6	8.5	29.8	8.6	31.9	8.4	34.1	7.8	36.2	7.2	38.3	6.7
14.0		22.0	6.0	24.4	6.2	26.7	6.4	28.9	6.6	31.1	6.6	33.3	6.3	35.5	6.0	37.6	5.7
16.0		20.6	4.4	23.1	4.6	25.5	4.8	27.8	5.0	30.1	5.1	32.4	5.0	34.6	5.0	36.8	4.9
18.0		18.9	3.3	21.6	3.4	24.1	3.6	26.6	3.8	29.0	4.0	31.3	4.1	33.6	4.1	35.9	4.2
20.0		16.8	2.4	19.7	2.2	22.5	2.5	25.1	2.8	27.6	3.1	30.1	3.2	32.4	3.3	34.8	3.5
22.0		14.0	1.7	17.5	1.5	20.5	1.8	23.4	2.0	26.1	2.3	28.6	2.4	31.1	2.6	33.5	2.7
24.0										24.2	1.7	27.0	1.8	29.6	2.0	32.1	2.1
26.0										22.0	1.2	25.0	1.3	27.8	1.5	30.5	1.6
28.0										19.4	0.8	22.8	0.9	25.8	1.0	28.7	1.2
30.0																26.6	1.0
32.0																24.1	0.7
34.0																21.2	0.4
36.0																	
38.0																	
40.0																	

トラッククレーン[油圧伸縮ジブ型]【80t吊】(1/2)

作業半径 (m) ブーム長さ (m)	10.6		12.0		14.0		16.0		18.0		20.0		22.0		24.0		26.0	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
3.0	10.5	80.0	11.9	74.2	14.0	61.7	16.0	49.2	18.1	43.8	20.1	41.4	22.1	38.3	24.1	35.0		
3.5	10.3	80.0	11.8	74.2	13.9	61.7	15.9	49.2	18.0	43.8	20.0	41.4	22.0	38.3	24.1	35.0		
4.0	10.1	70.0	11.6	65.8	13.7	56.9	15.8	48.0	17.9	43.8	19.9	41.4	21.9	38.6	24.0	34.9	26.0	31.6
4.5	9.9	62.0	11.4	59.2	13.6	53.1	15.7	47.0	17.7	43.8	19.8	41.4	21.8	38.6	23.9	34.9	25.9	31.6
5.0	9.7	56.0	11.2	54.2	13.4	49.6	15.5	45.1	17.6	42.0	19.7	39.8	21.7	37.3	23.8	33.9	25.8	30.8
5.5	9.4	50.0	11.0	49.2	13.2	46.4	15.3	43.7	17.5	40.9	19.5	38.8	21.6	36.2	23.7	32.9	25.7	30.2
6.0	9.1	45.0	10.7	44.5	13.0	42.5	15.1	40.5	17.3	38.3	19.4	36.5	21.5	34.2	23.6	31.0	25.6	28.5
7.0	8.3	38.0	10.1	37.0	12.4	36.0	14.7	35.0	16.9	33.6	19.0	32.3	21.2	30.5	23.3	27.8	25.4	25.4
8.0	7.3	30.5	9.3	29.6	11.8	29.5	14.2	29.3	16.4	29.1	18.6	28.7	20.8	27.6	22.9	25.0	25.1	22.6
9.0			8.2	23.1	11.0	22.8	13.5	25.0	15.9	25.0	18.2	24.7	20.4	23.8	22.6	22.0	24.7	20.3
10.0			6.9	19.2	10.1	19.2	12.8	20.8	15.3	20.9	17.6	20.7	19.9	20.2	22.1	19.2	24.3	18.3
12.0							10.9	15.4	13.7	15.0	16.3	15.0	18.8	15.1	21.1	15.1	23.4	14.9
14.0							8.1	11.5	11.6	11.3	14.6	11.3	17.3	11.4	19.8	11.4	22.2	11.4
16.0													15.4	8.9	18.2	8.7	20.8	8.7
18.0													13.0	6.9	16.2	6.6	19.1	6.6
20.0															13.6	4.5	16.9	4.5
22.0																		
24.0																		
26.0																		
28.0																		
30.0																		
32.0																		

トラックスレーン[油圧伸縮ジブ型]【80t吊】(2/2)

作業半径 (m)	ブーム長 (m)	28.0		30.0		32.0		34.0		36.0		38.0		40.0		42.0		44.0	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
3.0																			
3.5																			
4.0		28.0	29.7	30.0	27.0														
4.5		27.9	29.7	30.0	27.0														
5.0		27.9	28.7	29.9	26.9														
5.5		27.8	28.3	29.8	26.9	31.8	25.3	33.9	23.7	35.9	22.0								
6.0		27.7	26.9	29.7	25.8	31.7	24.6	33.8	23.2	35.8	22.0								
7.0		27.4	24.0	29.5	23.1	31.5	22.3	33.6	21.4	35.6	20.6	37.7	19.4	39.7	18.0				
8.0		27.1	21.4	29.2	20.6	31.3	19.9	33.4	19.1	35.4	18.4	37.5	17.4	39.5	15.7	41.5	13.9	43.6	12.0
9.0		26.8	19.2	28.9	18.4	31.0	17.7	33.1	17.2	35.2	16.6	37.2	15.8	39.3	14.0	41.3	13.0	43.4	12.0
10.0		26.5	17.4	28.6	16.6	30.7	15.9	32.8	15.4	34.9	15.0	37.0	14.4	39.0	12.6	41.1	12.0	43.2	11.4
12.0		25.6	14.4	27.8	13.7	30.0	13.1	32.1	12.7	34.3	12.3	36.4	12.0	38.5	10.4	40.6	10.0	42.6	9.5
14.0		24.6	11.3	26.8	11.1	29.1	10.9	31.3	10.6	33.5	10.4	35.6	10.2	37.8	8.9	39.9	8.6	42.0	8.2
16.0		23.3	8.7	25.7	8.7	28.0	8.7	30.3	8.8	32.6	8.9	34.8	8.7	37.0	7.7	39.1	7.4	41.3	7.1
18.0		21.8	6.6	24.3	6.6	26.8	6.7	29.2	6.9	31.5	7.1	33.8	7.3	36.0	6.6	38.3	6.4	40.5	6.2
20.0		19.9	5.1	22.7	5.1	25.3	5.1	27.8	5.3	30.2	5.5	32.6	5.8	35.0	5.1	37.2	5.4	39.5	5.6
22.0		17.6	4.1	20.7	3.9	23.6	3.9	26.2	4.1	28.8	4.3	31.3	4.6	33.7	4.0	36.1	4.2	38.4	4.4
24.0		14.7	3.0	18.3	3.0	21.5	3.0	24.4	3.4	27.1	3.3	29.8	3.6	32.3	3.1	34.8	3.3	37.2	3.5
26.0						19.0	2.1	22.2	2.5	25.2	2.4	28.0	2.7	30.7	2.2	33.3	2.4	35.8	2.6
28.0						15.8	1.4	19.6	1.8	22.9	2.1	26.0	2.4	28.9	1.6	31.6	1.8	34.3	1.9
30.0										20.2	1.5	23.6	1.8	26.8	1.0	29.7	1.2	32.5	1.3
32.0										16.8	0.9	20.8	1.3						

トラックスレーン[油圧伸縮ジブ型]【100t吊】 (1/2)

ブーム長 (m) 作業半径 (m)	12.0		14.0		16.0		18.0		20.0		22.0		24.0		26.0		28.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0	11.7	100.0	13.8	77.3	15.8	54.6	17.9	45.6	19.9	40.1								
3.5	11.6	85.0	13.7	69.1	15.7	53.2	17.8	45.6	19.8	40.1								
4.0	11.4	77.0	13.5	64.7	15.6	52.5	17.7	45.6	19.7	40.1	21.7	37.1	23.8	35.8	25.8	34.4	27.8	33.0
4.5	11.2	69.5	13.4	60.6	15.4	51.8	17.5	45.6	19.6	40.1	21.6	37.1	23.7	35.8	25.7	34.4	27.7	33.0
5.0	11.0	62.0	13.2	56.6	15.3	51.1	17.4	45.6	19.5	40.1	21.5	37.1	23.6	35.8	25.6	34.4	27.7	33.0
5.5	10.8	57.0	13.0	53.8	15.1	50.6	17.2	45.6	19.3	40.1	21.4	37.1	23.5	35.8	25.5	34.4	27.6	33.0
6.0	10.5	52.0	12.8	51.1	14.9	50.2	17.1	45.6	19.2	40.1	21.3	37.1	23.3	35.8	25.4	34.4	27.5	33.0
7.0	9.9	44.0	12.2	44.0	14.5	44.0	16.7	41.8	18.8	39.0	21.0	36.9	23.1	35.0	25.1	33.2	27.2	31.4
8.0	9.0	37.5	11.6	37.5	14.0	37.5	16.2	37.0	18.4	36.4	20.6	34.9	22.7	32.8	24.8	30.7	26.9	28.6
9.0	8.0	32.5	10.8	32.5	13.3	32.5	15.7	32.5	18.0	32.5	20.2	31.4	22.4	29.5	24.5	27.7	26.6	25.9
10.0							15.1	28.5	17.4	28.5	19.7	27.6	21.9	26.2	24.1	24.8	26.3	23.5
12.0							13.5	22.3	16.1	22.3	18.5	21.8	20.9	21.0	23.2	20.3	25.4	19.5
14.0											17.1	17.4	19.6	17.1	22.0	16.8	24.4	16.5
16.0											15.2	13.6	18.0	13.7	20.6	13.9	23.1	14.0
18.0																		
20.0																		
22.0																		
24.0																		
26.0																		
28.0																		
30.0																		
32.0																		
34.0																		

トラッククレーン[油圧伸縮ジブ型]【100t吊】 (2/2)

作業半径 (m)	30.0		32.0		34.0		36.0		38.0		40.0		42.0		44.0		46.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0																		
3.5																		
4.0																		
4.5																		
5.0																		
5.5																		
6.0	29.5	31.6	31.5	29.7	33.6	27.9	35.6	26.1	37.6	24.3								
7.0	29.3	29.7	31.3	28.3	33.4	26.9	35.4	25.6	37.5	24.2	39.5	21.7	41.5	18.9	43.5	16.1	45.6	13.4
8.0	29.0	26.8	31.1	25.9	33.2	25.1	35.2	24.2	37.3	23.3	39.3	21.0	41.3	18.4	43.4	15.9	45.4	13.3
9.0	28.7	24.3	30.8	23.5	32.9	22.7	35.0	21.9	37.0	21.1	39.1	19.2	41.1	17.2	43.2	15.1	45.2	13.0
10.0	28.4	22.2	30.5	21.5	32.6	20.7	34.7	20.0	36.8	19.2	38.8	17.7	40.9	16.1	43.0	14.5	45.0	12.8
12.0	27.6	18.8	29.8	18.1	31.9	17.5	34.0	16.9	36.2	16.3	38.3	15.4	40.4	14.4	42.4	13.5	44.5	12.5
14.0	26.6	16.2	28.9	15.6	31.1	15.1	33.3	14.5	35.4	14.0	37.6	13.4	39.7	12.8	41.8	12.1	43.9	11.5
16.0	25.5	14.0	27.8	13.6	30.1	13.1	32.4	12.7	34.6	12.3	36.8	11.7	38.9	11.2	41.1	10.6	43.2	10.1
18.0	24.1	11.9	26.6	11.7	28.9	11.4	31.3	11.1	33.6	10.8	35.8	10.4	38.1	9.9	40.3	9.4	42.4	8.9
20.0	22.5	9.7	25.1	9.7	27.6	9.7	30.0	9.6	32.4	9.6	34.7	9.2	37.0	8.8	39.3	8.3	41.5	7.8
22.0	20.5	7.9	23.3	8.0	26.0	8.2	28.6	8.3	31.1	8.4	33.5	8.1	35.9	7.7	38.2	7.3	40.5	6.9
24.0	18.1	6.5	21.3	6.6	24.2	6.8	26.9	7.0	29.6	7.2	32.1	7.0	34.6	6.7	37.0	6.4	39.3	6.1
26.0	15.1	5.3	18.8	5.5	22.0	5.7	25.0	5.8	27.8	6.0	30.5	5.9	33.1	5.7	35.6	5.5	38.1	5.4
28.0											28.7	4.9	31.4	4.9	34.0	4.8	36.6	4.7
30.0											26.6	4.0	29.5	4.1	32.3	4.1	35.0	4.2
32.0											24.1	3.2	27.3	3.3	30.3	3.4	33.2	3.5
34.0											21.2	2.5	24.8	2.6	28.0	2.7	31.1	2.8

トラッククレーン[油圧伸縮ジブ型]【120t吊】（1/2）

作業半径 (m)	ブーム長 (m)	12.0		14.0		16.0		18.0		20.0		22.0		24.0		26.0		28.0		30.0	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
3.2		11.9	120.0	14.0	95.4	16.0	70.9														
3.5		11.8	112.5	13.7	93.6	15.8	73.2														
4.0		11.7	105.0	13.5	91.8	15.5	75.5	17.0	80.8	19.1	77.6	21.1	74.9								
4.5		11.5	92.0	13.3	82.3	15.4	70.9	17.5	60.5	19.5	57.3	21.6	54.1								
5.0		11.3	82.0	13.1	74.8	15.2	66.6	17.3	59.1	19.4	55.9	21.5	52.6	23.0	66.6	25.0	61.3	27.0	56.0	29.1	50.8
5.5		11.0	73.0	13.2	64.9	15.4	56.9	17.5	49.5	19.6	46.0	21.6	42.5	23.1	56.5	25.2	52.3	27.2	48.2	29.0	49.9
6.0		10.7	66.0	12.7	63.0	14.9	58.9	17.0	55.0	19.1	52.3	21.2	49.5	23.3	46.4	25.3	43.4	27.4	40.3	28.9	49.1
7.0		10.1	55.0	12.2	54.6	14.4	53.2	16.6	51.7	18.8	49.2	20.9	46.8	23.0	44.1	25.1	41.5	27.1	38.9	29.2	36.4
8.0		9.3	47.0	11.5	47.0	13.9	46.4	16.2	45.6	18.4	44.5	20.5	43.4	22.7	41.8	24.8	39.4	26.9	37.0	28.9	34.7
9.0		8.3	40.0	10.8	40.7	13.3	40.6	15.6	40.4	17.9	39.6	20.1	38.7	22.3	37.5	24.4	35.8	26.5	34.1	28.7	32.4
10.0		7.0	35.0	9.8	35.7	12.5	35.7	15.0	35.6	17.4	35.1	19.6	34.6	21.9	33.8	24.0	32.2	26.2	30.7	28.3	29.5
12.0								13.8	27.6	16.0	27.6	18.5	27.4	20.8	27.0	23.1	26.1	25.3	25.2	27.5	24.5
14.0								11.7	21.4	14.3	21.8	17.0	21.9	19.5	21.8	21.9	21.4	24.3	21.0	26.6	20.5
16.0								8.6	16.2	12.0	17.0	15.1	17.1	17.9	17.2	20.5	17.2	23.0	17.3	25.4	17.2
18.0														15.9	13.7	18.8	13.9	21.5	14.1	24.0	14.2
20.0														13.3	10.9	16.6	11.2	19.6	11.4	22.4	11.6
22.0																				20.7	8.5
24.0																				18.3	6.6
26.0																				15.3	5.0
28.0																					
30.0																					
32.0																					
34.0																					
36.0																					
38.0																					
40.0																					
42.0																					
44.0																					

トラックスレーン[油圧伸縮ジブ型]【120t吊】(2/2)

作業半径 (m)	ブーム長 (m)	32.0		34.0		36.0		38.0		40.0		42.0		44.0		46.0		48.0		50.0	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
3.2																					
3.5																					
4.0																					
4.5																					
5.0																					
5.5																					
6.0		30.9	45.7	32.9	42.6	35.0	39.5	37.0	36.5	39.0	33.4										
7.0		31.3	34.1	33.3	31.5	35.3	29.0	37.4	26.6	39.4	24.2	41.4	21.7	42.9	26.9	44.9	23.6	47.0	20.3	49.0	17.0
8.0		31.0	32.5	33.1	30.2	35.1	28.1	37.2	25.9	39.2	23.8	41.3	21.4	42.7	26.3	44.8	23.2	46.8	20.1	48.8	17.0
9.0		30.7	30.7	32.8	28.8	34.9	26.8	37.0	24.7	39.0	22.6	41.1	20.4	42.5	24.3	44.6	21.8	46.6	19.4	48.7	17.0
10.0		30.4	28.5	32.5	27.4	34.6	25.7	36.7	23.7	38.8	21.7	40.8	19.6	42.9	18.3	44.9	17.3	47.0	16.2	49.0	15.1
12.0		29.7	23.9	31.8	22.9	34.0	21.8	36.1	20.6	38.2	19.4	40.3	18.3	42.4	17.4	44.4	16.6	46.5	15.9	48.6	15.1
14.0		28.8	20.1	31.0	19.3	33.2	18.7	35.4	18.1	37.5	17.6	39.6	17.1	41.7	16.2	43.9	15.2	45.9	14.3	48.0	13.3
16.0		27.7	17.1	30.0	16.5	32.3	16.0	34.5	15.6	36.7	15.1	38.9	14.6	41.0	14.0	43.2	13.3	45.3	12.6	47.4	11.9
18.0		26.5	14.3	28.9	14.0	31.2	13.7	33.5	13.4	35.8	13.1	38.0	12.8	40.2	12.3	42.4	11.8	44.5	11.4	46.7	10.9
20.0		25.0	11.8	27.5	11.7	30.0	11.6	32.3	11.5	34.7	11.4	37.0	11.3	39.2	10.9	41.5	10.5	43.7	10.2	45.9	9.8
22.0		23.3	9.6	26.0	9.6	28.5	9.7	31.0	9.8	33.4	9.9	35.8	9.9	38.1	9.7	40.4	9.4	42.7	9.1	44.9	8.8
24.0		21.2	7.7	24.1	7.8	26.9	8.0	29.5	8.3	32.0	8.6	34.5	8.8	36.9	8.6	39.3	8.4	41.6	8.1	43.9	7.9
26.0		18.7	6.1	21.9	6.2	24.9	6.5	27.7	6.8	30.4	7.2	33.0	7.5	35.5	7.4	38.0	7.3	40.4	7.2	42.7	7.1
28.0		15.0	6.4	18.8	6.7	22.7	5.1	25.7	5.5	28.6	5.9	31.3	6.2	34.0	6.2	36.5	6.3	39.0	6.3	41.5	6.3
30.0		10.6	4.5	15.5	4.9	19.9	3.8	23.4	4.3	26.5	4.7	29.4	5.0	32.2	5.2	34.9	5.4	37.5	5.5	40.0	5.7
32.0						16.8	2.1	20.8	2.5	24.3	2.9	27.2	4.0	30.2	4.2	33.1	4.5	35.8	4.7	38.5	4.9
34.0												24.1	4.4	28.0	3.4	31.0	3.7	33.9	3.9	36.7	4.1
36.0												21.1	3.6	25.3	2.6	28.7	2.9	31.8	3.1	34.7	3.4
38.0												17.4	2.8	22.2	2.0	26.0	2.2	29.4	2.4	32.5	2.7
40.0																				30.0	2.1
42.0																				27.2	1.5
44.0																				23.2	1.5

トトラックレーン[油圧伸縮ジブ型]【160t吊】（1/2）

作業半径 (m)	12.5		14.0		16.0		18.0		20.0		22.0		24.0		26.0		28.0		30.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.3	12.4	160.0																		
3.5	12.3	145.0	13.8	136.3	15.8	118.3	17.9	100.2	20.0	75.6										
4.0	12.2	135.0	13.7	126.8	15.7	112.4	17.8	98.0	19.8	85.9	21.7	101.5								
4.5	12.0	125.0	13.5	117.5	15.6	106.6	17.7	95.8	19.7	85.5	21.8	79.6	23.9	63.7	25.9	60.0	28.0	56.3		
5.0	11.8	115.0	13.3	108.3	15.4	100.4	17.5	92.6	19.6	84.4	21.7	79.4	23.7	74.9	25.8	69.8	27.8	64.6	29.7	71.9
5.5	11.5	107.0	13.2	100.2	15.3	91.0	17.5	81.9	19.5	72.7	21.6	67.4	23.7	63.7	25.7	60.0	27.8	56.3	29.7	65.7
6.0	11.3	100.0	12.9	95.9	15.1	90.9	17.2	85.8	19.3	79.2	21.4	74.0	23.5	70.0	25.5	66.1	27.6	62.2	29.6	59.4
7.0	10.7	84.0	12.4	82.8	14.6	80.7	16.8	78.6	19.0	74.6	21.1	70.2	23.2	66.6	25.3	63.3	27.3	60.0	29.4	57.7
8.0	9.9	73.0	11.7	73.1	14.1	72.6	16.4	72.0	18.6	69.6	20.7	65.6	22.9	61.7	25.0	58.1	27.1	54.6	29.2	52.7
9.0	9.0	65.0	11.0	65.8	13.5	66.0	15.8	66.1	18.1	64.9	20.3	61.2	22.5	57.0	24.6	53.2	26.8	49.3	28.9	47.4
10.0	7.8	58.0	10.0	59.4	12.7	59.1	15.2	58.8	17.6	57.7	19.8	54.7	22.1	51.3	24.2	48.1	26.4	44.9	28.5	43.4
12.0									16.1	47.1	18.7	44.3	21.0	42.1	23.3	39.9	25.5	37.8	27.7	36.7
14.0									14.4	39.7	17.2	36.1	19.7	34.8	22.1	33.6	24.5	32.4	26.8	31.7
16.0									12.1	26.7	15.3	30.2	18.1	30.0	20.7	29.2	23.2	28.4	25.6	27.7
18.0											13.0	25.7	16.1	26.1	19.0	25.6	21.7	25.1	24.2	24.6
20.0													13.4	19.8	16.7	20.2	19.7	20.6	22.6	21.6
22.0																			20.7	19.0
24.0																			18.3	16.0
26.0																			15.3	13.6
28.0																				
30.0																				
32.0																				
34.0																				
36.0																				
38.0																				
40.0																				
42.0																				
44.0																				
46.0																				

トラッククレーン[油圧伸縮ジブ型]【160t吊】(2/2)

作業半径 (m)	32.0		34.0		36.0		38.0		40.0		42.0		44.0		46.0		48.0		50.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.3																				
3.5																				
4.0																				
4.5																				
5.0																				
5.5																				
6.0	31.7	53.0	33.8	51.8	35.8	50.6														
7.0	31.5	56.0	33.5	54.1	35.5	52.1	37.6	48.6	39.6	43.8	41.7	35.5	43.8	29.8						
8.0	31.2	51.9	33.3	50.8	35.3	49.8	37.4	46.9	39.4	42.6	41.5	35.2	43.6	29.7						
9.0	30.9	46.7	33.0	45.9	35.1	45.1	37.2	42.8	39.2	39.3	41.3	35.7	43.3	32.1	45.2	34.8	47.2	32.4	49.3	30.0
10.0	30.6	42.7	32.7	42.0	34.8	41.3	36.9	39.4	39.0	36.5	41.0	33.7	43.1	30.9	45.0	33.2	47.0	31.6	49.1	30.0
12.0	29.9	36.2	32.0	35.7	34.2	35.1	36.3	33.9	38.4	32.2	40.5	30.6	42.6	29.0	44.5	30.1	46.6	29.3	48.6	28.5
14.0	29.0	31.3	31.2	30.9	33.4	30.5	35.6	29.6	37.7	28.3	39.8	27.1	42.0	25.9	43.9	26.2	46.0	25.4	48.1	24.6
16.0	27.9	27.2	30.2	26.7	32.5	26.3	34.7	25.6	36.9	24.6	39.1	23.7	41.2	22.7	43.2	23.0	45.4	22.2	47.5	21.4
18.0	26.7	24.1	29.1	23.6	31.4	23.2	33.7	22.6	36.0	21.7	38.2	20.9	40.4	20.0	42.4	20.3	44.6	19.6	46.7	19.0
20.0	25.2	21.5	27.7	21.2	30.2	20.9	32.5	20.3	34.9	19.5	37.2	18.6	39.4	17.8	41.5	18.0	43.7	17.5	45.9	17.0
22.0	23.5	19.0	26.2	18.8	28.7	18.7	31.2	18.2	33.6	17.5	36.0	16.8	38.3	16.1	40.5	16.1	42.8	15.7	45.0	15.3
24.0	21.4	16.3	24.3	16.2	27.1	16.0	29.7	15.7	32.2	15.3	34.7	14.8	37.1	14.4	39.3	14.4	41.7	14.1	44.0	13.8
26.0	18.9	14.0	22.1	14.0	25.1	14.0	27.9	13.8	30.6	13.5	33.2	13.3	35.7	13.0	38.0	12.9	40.4	12.7	42.8	12.5
28.0	15.6	12.6	19.4	12.5	22.7	12.4	25.9	12.0	28.8	11.9	31.5	11.7	34.2	11.5	36.6	11.6	39.1	11.4	41.5	11.2
30.0							23.6	10.1	26.8	10.2	29.6	10.5	32.4	10.5	35.0	10.4	37.6	10.2	40.1	10.0
32.0							20.8	9.1	24.3	9.2	27.4	9.5	30.4	9.5	33.1	9.4	35.9	9.2	38.5	9.0
34.0							17.3	7.6	21.4	7.8	24.9	8.3	28.2	8.4	31.1	8.4	34.0	8.3	36.8	8.1
36.0											21.7	7.7	25.4	7.6	28.7	7.5	31.8	7.4	34.8	7.3
38.0											18.0	6.1	22.3	6.2	26.0	6.3	29.4	6.4	32.6	6.5
40.0																			30.1	5.9
42.0																			27.2	5.2
44.0																			23.8	4.4
46.0																			19.7	3.6

トラックスレール[油圧伸縮ジブ型]【360t吊】 (1/2)

作業半径 (m)	ブーム長 (m)	13.0		14.0		16.0		18.0		20.0		22.0		24.0		26.0		28.0		30.0	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0		11.5	360.0	10.6	344.2	14.1	259.3	16.1	182.4	19.1	180.0	21.1	180.0								
3.5		11.4	240.0	10.5	289.5	14.0	234.1	16.1	181.6	19.0	180.0	21.1	180.0								
4.0		11.2	225.0	10.4	243.9	13.9	216.9	15.9	180.9	18.0	180.0	20.0	180.0								
4.5		11.1	200.0	11.1	207.0	13.9	200.7	15.9	180.4	18.0	180.0	20.0	180.0								
5.0		10.9	200.0	10.9	197.0	13.7	194.1	15.8	180.2	17.9	179.4	19.9	178.7	22.8	171.7	24.9	159.8	26.9	147.9	28.9	136.0
5.5		10.6	196.0	10.7	182.7	12.8	178.3	15.0	174.5	17.1	173.8	19.1	173.2	22.3	167.3	24.3	155.0	26.4	142.8	28.4	130.6
6.0		10.4	192.0	10.5	174.8	13.3	178.8	15.5	173.9	17.6	173.2	19.7	172.5	21.8	162.8	23.8	150.3	25.9	137.8	27.9	125.2
7.0		9.8	164.0	9.9	151.5	12.9	159.2	15.1	158.0	17.2	157.3	19.4	156.6	21.5	149.7	23.6	140.8	25.6	131.8	27.7	122.9
8.0		9.1	145.0	9.3	132.7	12.4	140.3	14.6	139.4	16.8	138.9	19.0	138.5	21.1	134.4	23.3	129.3	25.3	124.2	27.4	119.1
9.0		8.3	132.0	8.5	117.6	11.7	124.4	14.1	123.7	16.4	123.5	18.6	123.3	20.8	121.0	22.9	118.2	25.0	115.3	27.1	112.4
10.0		7.2	113.0	7.6	101.6	11.0	109.8	13.5	109.5	15.8	109.6	18.1	109.6	20.3	108.3	22.5	106.7	24.7	105.1	26.8	103.5
12.0								12.6	95.0	14.5	88.6	17.0	88.4	19.3	87.9	21.6	87.3	23.8	86.8	26.0	86.2
14.0								10.5	78.9	12.8	72.7	15.5	72.7	18.0	72.8	20.4	73.0	22.8	73.2	25.0	73.4
16.0												14.3	66.5	16.4	60.3	19.0	60.7	21.5	61.1	23.9	61.5
18.0												11.5	56.0	14.4	50.4	17.3	50.8	20.0	51.1	22.5	51.5
20.0																					
22.0																					
24.0																					
26.0																					
28.0																					
30.0																					
32.0																					
34.0																					
36.0																					
38.0																					
40.0																					
42.0																					
44.0																					
46.0																					

トトラッククレーン[油圧伸縮ジブ型]【360t吊】(2/2)

作業半径 (m) ブーム長 (m)		32.0		34.0		36.0		38.0		40.0		42.0		44.0		46.0		48.0		50.0	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
3.0																					
3.5																					
4.0																					
4.5																					
5.0																					
5.5																					
6.0	30.8	126.4	32.8	119.3	34.9	112.1	36.9	105.0													
	29.7	115.4	31.8	110.7	33.8	106.0	35.9	101.3	37.9	96.6	40.8	90.7	42.8	83.6	44.8	76.4					
	29.5	114.2	31.6	109.6	33.6	105.0	35.7	100.4	37.7	95.6	39.6	90.0	41.7	83.8	43.7	77.6	44.3	74.7	46.3	70.0	
	29.2	109.3	31.3	105.2	33.4	101.0	35.4	96.9	37.5	92.5	39.4	87.7	41.5	82.0	43.5	76.2	44.1	72.0	46.1	67.5	
	28.9	101.3	31.0	97.8	33.1	94.3	35.2	90.8	37.2	87.1	39.2	83.3	41.2	78.5	43.3	73.8	43.9	69.4	45.9	65.0	
7.0	28.2	84.9	30.3	82.3	32.5	79.8	34.6	77.2	36.7	74.6	38.6	72.0	40.7	68.3	42.8	64.7	43.4	60.9	45.5	57.5	
	27.3	72.6	29.5	70.6	31.7	68.6	33.8	66.6	36.0	64.6	38.0	62.6	40.1	59.7	42.2	56.9	42.9	53.4	45.0	51.0	
	26.2	61.1	28.5	59.8	30.8	58.5	33.0	57.3	35.2	55.9	37.2	54.0	39.4	51.9	41.5	49.7	42.2	46.3	44.3	45.0	
	25.0	51.4	27.4	50.7	29.7	50.1	32.0	49.4	34.2	48.5	36.3	46.7	38.5	45.1	40.7	43.5	41.5	40.3	43.6	40.0	
	23.5	43.5	26.0	43.3	28.4	43.2	30.8	43.0	33.2	42.6	35.3	40.8	37.6	39.5	39.8	38.2	40.6	34.9	42.8	35.0	
20.0	21.8	37.3	24.4	37.5	27.0	37.6	29.5	37.8	31.9	37.7	34.2	35.7	36.5	34.5	38.8	33.2	39.6	27.6	41.9	27.3	
	19.7	32.3	22.6	32.7	25.3	33.1	28.0	33.5	30.5	33.5	32.9	31.8	35.3	30.9	37.6	30.0	38.5	24.9	40.8	25.0	
	17.2	28.0	20.4	28.6	23.4	29.1	26.2	29.7	28.9	29.9	31.4	28.3	33.9	27.6	36.3	26.9	37.3	21.4	39.7	21.5	
	13.3	20.6	17.1	21.2	20.5	21.8	23.5	22.4	27.1	26.5	29.7	25.0	32.3	24.5	34.9	24.1	35.9	18.2	38.4	18.5	
										25.6	27.7	27.8	22.3	30.6	22.0	33.3	21.8	34.4	15.7	37.0	16.0
30.0																					
32.0																					
34.0																					
36.0																					
38.0																					
40.0																					
42.0																					
44.0																					
46.0																					

トラッククレーン[油圧伸縮ジブ型]【500t吊】

作業半径 (m)	13.35		14.0		16.0		18.0		20.0		22.0	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
3.0	11.1	500.0	11.7	485.6	13.8	441.1	15.8	396.7	17.8	352.2	19.9	307.8
3.5	11.0	400.0	11.6	392.8	13.7	370.6	15.7	348.3	17.8	326.1	19.8	303.9
4.0	10.8	350.0	11.5	346.4	13.6	335.3	15.6	324.2	17.7	313.1	19.7	301.9
4.5	10.6	320.0	11.3	318.6	13.4	314.1	15.5	309.7	17.6	305.2	19.6	300.8
5.0	10.5	300.0	11.1	300.0	13.3	300.0	15.4	300.0	17.4	300.0	19.5	300.0
5.5	10.2	300.0	10.9	300.0	13.1	300.0	15.2	300.0	17.3	300.0	19.4	300.0
6.0	10.0	300.0	10.7	300.0	12.9	300.0	15.0	300.0	17.2	300.0	19.2	300.0
7.0	9.4	260.0	10.2	260.0	12.5	260.1	14.7	260.2	16.8	260.3	18.9	260.4
8.0	8.8	227.7	9.6	227.7	11.9	227.8	14.2	227.9	16.4	227.9	18.6	228.0
9.0	7.9	202.1	8.8	202.1	11.3	202.2	13.7	202.3	15.9	202.4	18.1	202.5
10.0	6.9	181.2	7.9	181.2	10.6	181.4	13.0	181.5	15.4	181.6	17.7	181.7

オールテレーンクレーン[油圧伸縮ジブ型]【100t吊】（1／2）

作業半径 (m)	11.1		12.0		14.0		16.0		18.0		20.0		22.0		24.0		26.0		28.0		30.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.3	13.0	100.0																				
2.5	12.9	90.0																				
3.0	12.8	81.6	13.7	77.4	15.7	62.9	17.8	56.4	19.8	56.0	21.4	60.4	23.6	55.9								
3.5	12.7	74.6	13.2	74.4	15.3	64.3	17.3	59.2	19.4	57.9	21.8	52.1	23.8	47.0	24.1	37.8	26.2	34.2	28.2	30.5		
4.0	12.5	68.3	13.0	68.8	15.2	62.4	17.2	59.0	19.3	57.4	21.3	53.8	23.4	49.5	25.7	43.9	27.4	42.9	28.1	30.5		
4.5	12.3	62.6	12.9	63.6	15.0	60.0	17.1	57.1	19.2	54.7	21.2	52.2	23.3	49.4	25.3	46.3	26.3	49.0	29.3	37.6	31.3	32.7
5.0	12.0	57.8	12.6	58.8	14.8	56.8	16.9	55.1	19.0	53.5	21.1	51.3	23.2	48.6	25.2	44.9	27.2	41.0	28.3	36.8	30.3	38.5
5.5	11.7	53.9	11.1	49.1	13.3	48.1	15.4	47.1	17.5	46.0	19.6	45.0	21.7	41.0	23.8	37.1	25.8	33.1	27.9	29.1	29.9	26.2
6.0	11.5	50.0	12.1	50.2	14.4	48.8	16.6	48.0	18.7	47.6	20.8	47.1	22.9	46.3	25.0	41.8	27.0	37.2	29.1	34.8	31.1	32.0
7.0	10.7	42.5	11.5	42.8	13.9	42.2	16.1	41.9	18.3	41.6	20.5	41.2	22.6	40.7	24.7	37.7	26.8	34.6	28.8	32.4	30.9	30.1
8.0	9.8	36.6	10.7	36.9	13.2	36.5	15.6	36.3	17.9	36.3	20.1	36.3	22.2	36.3	24.4	34.3	26.5	32.3	28.6	31.0	30.6	29.3
9.0	8.6	24.9	10.0	26.9	12.8	30.0	15.0	31.9	17.3	31.9	19.6	32.0	21.8	32.3	24.0	31.2	26.1	30.0	28.2	29.4	30.4	28.1
10.0							14.2	28.3	16.7	28.3	19.1	28.4	21.3	28.7	23.6	28.3	25.7	27.9	28.0	30.0	30.0	27.2
12.0							12.3	21.3	15.2	21.7	17.7	21.9	20.2	22.1	22.5	22.6	24.8	22.9	27.0	27.9	29.2	22.1
14.0											16.0	18.5	18.7	18.6	21.2	18.5	23.6	18.3	26.0	18.1	28.3	17.7
16.0											13.7	14.9	16.8	15.2	19.6	15.1	22.2	15.0	24.7	14.8	27.1	14.8
18.0															17.6	12.7	20.5	12.6	23.2	12.5	25.7	12.4
20.0															15.4	9.8	18.7	10.5	21.3	10.6	24.1	10.5
22.0																	16.0	9.1	19.1	9.0	22.1	9.0
24.0																			16.2	7.0	20.1	7.5
26.0																					17.1	6.6
28.0																						
30.0																						
32.0																						
34.0																						
36.0																						
38.0																						
40.0																						
42.0																						
44.0																						
46.0																						
48.0																						

オールテレーンクレーン[油圧伸縮ジブ型]【100t吊】（2／2）

作業半径 (m) ブーム長さ (m)	32.0		34.0		36.0		38.0		40.0		42.0		44.0		46.0		48.0		50.0		52.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.3																						
2.5																						
3.0																						
3.5																						
4.0																						
4.5	32.1	24.3	34.1	21.2	36.1	18.1																
5.0	32.0	24.3	34.0	21.2	36.1	18.1	38.1	16.1	40.1	14.8	42.1	13.5	44.1	12.2								
5.5	31.9	23.4	34.0	20.7	36.0	18.0	38.0	16.1	40.0	14.8	42.0	13.5	44.1	12.2								
6.0	33.2	28.2	34.2	30.0	36.2	27.2	37.9	16.1	40.0	14.8	42.0	13.5	44.0	12.2								
7.0	33.0	27.3	35.0	24.5	37.0	22.2	39.1	20.0	41.1	17.9	41.8	13.5	43.8	12.2								
8.0	32.7	26.6	34.8	24.1	36.8	21.9	38.9	19.8	40.9	17.8	43.0	16.1	45.0	14.5								
9.0	32.4	25.1	34.5	22.8	36.6	21.3	38.7	19.5	40.7	17.6	42.8	16.0	44.8	14.4	46.9	12.9	47.8	14.8				
10.0	32.1	23.8	34.2	21.3	36.3	20.1	38.4	18.7	40.5	17.3	42.5	15.8	44.6	14.3	46.6	12.8	48.7	11.3	50.7	10.3	51.7	11.0
12.0	31.4	19.8	33.5	18.2	35.7	17.4	37.8	16.6	39.9	15.8	42.0	14.8	44.1	13.9	46.2	12.6	48.2	11.2	50.3	10.2	51.3	10.6
14.0	30.5	16.9	32.7	16.0	34.9	15.2	37.1	14.5	39.2	14.0	41.3	13.4	43.4	12.9	45.6	12.0	47.7	11.0	49.7	10.1	50.8	10.2
16.0	29.4	14.7	31.7	14.2	34.0	13.2	36.2	12.6	38.4	12.3	40.6	12.0	42.7	11.6	44.9	11.1	47.0	10.6	49.1	9.8	50.2	9.8
18.0	28.2	12.5	30.6	12.3	32.9	11.6	35.2	11.2	37.5	10.8	39.7	10.6	41.9	10.4	44.1	10.1	46.2	9.7	48.4	9.3	49.5	9.2
20.0	26.7	10.6	29.2	10.6	31.7	10.3	34.0	10.0	36.4	9.6	38.7	9.4	40.9	9.4	43.2	9.1	45.4	8.8	47.6	8.4	48.7	8.5
22.0	25.0	9.1	27.7	9.2	30.2	9.2	32.7	8.9	35.1	8.5	37.5	8.4	39.8	8.5	42.1	8.3	44.4	8.0	46.6	7.7	47.8	7.8
24.0	22.9	7.8	25.8	7.9	28.6	8.0	31.2	7.8	33.7	7.5	36.2	7.5	38.6	7.6	41.0	7.4	43.3	7.1	45.6	7.0	46.8	6.9
26.0	20.4	6.8	23.6	6.9	26.6	7.0	29.4	6.8	32.1	6.5	34.7	6.6	37.2	6.8	39.7	6.6	42.1	6.4	44.5	6.3	45.7	6.1
28.0	17.3	4.7	21.0	6.1	24.4	6.2	27.4	6.1	30.3	5.8	33.0	5.9	35.7	6.0	38.2	5.9	40.7	5.7	43.2	5.6	44.5	5.4
30.0			17.7	5.6	21.6	5.5	25.1	5.5	28.2	5.3	31.1	5.3	33.9	5.4	36.6	5.3	39.2	5.1	41.7	5.0	43.2	4.7
32.0							22.2	4.9	25.7	4.8	28.9	4.7	31.9	4.7	34.8	4.6	37.5	4.5	40.2	4.5	41.7	4.1
34.0							18.7	4.5	22.8	4.4	26.4	4.3	29.7	4.2	32.7	4.1	35.6	4.0	38.4	4.0	40.0	3.5
36.0											23.4	3.9	27.0	3.8	30.4	3.6	33.5	3.5	36.4	3.5	38.2	3.1
38.0											19.6	3.5	23.9	3.3	27.7	3.2	31.1	3.1	34.2	3.1	36.2	2.7
40.0															24.5	2.9	28.3	2.7	31.7	2.7	33.9	2.3
42.0															20.5	2.5	25.0	2.4	28.9	2.4	31.4	2.0
44.0																	21.3	2.2	25.5	2.1	28.4	1.6
46.0																			21.4	1.0	24.9	1.3
48.0																					20.0	1.2

オールテレーンクレーン[油圧伸縮ジブ型]【120t吊】(1/4)

作業半径 (m)	11.4		12.0		14.0		16.0		18.0		20.0		22.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5	12.3	120.0	13.0	110.8	15.0	80.3	17.0	63.5	19.1	63.5	21.1	62.3	23.1	60.3
3.0	12.2	105.3	13.1	87.6	14.9	79.1	16.9	71.2	19.0	68.9	21.0	66.2	23.2	64.0
3.5	12.1	96.7	10.5	88.2	12.8	78.8	14.9	71.9	17.9	69.6	20.5	60.5	22.5	57.2
4.0	11.9	84.8	10.9	76.6	13.1	73.1	15.2	69.6	18.1	67.7	20.2	65.7	22.2	63.5
4.5	11.7	75.0	9.9	71.9	12.2	69.4	14.4	66.6	17.7	64.9	19.7	63.1	21.8	61.4
5.0	11.5	67.1	10.4	65.0	12.7	63.5	14.9	61.4	17.9	60.4	20.0	59.1	22.0	57.4
5.5	11.2	61.2	10.0	60.8	12.5	65.1	14.6	60.8	16.7	56.5	18.8	52.2	20.9	48.2
6.0	10.9	55.2	9.7	56.7	12.1	55.6	14.4	54.1	17.6	53.0	19.7	52.1	21.8	51.4
7.0	10.2	46.7	8.9	49.0	11.5	48.6	13.9	47.8	17.2	47.3	19.3	46.8	21.5	46.1
8.0	9.3	40.2	7.7	42.3	10.6	42.1	13.2	41.7	16.7	41.7	18.9	41.6	21.1	41.2
9.0	8.2	35.2	4.9	38.3	8.7	38.1	11.7	37.8	16.2	36.8	18.5	36.8	20.7	36.9
10.0					10.6	32.8	10.6	33.3	15.6	32.6	18.0	32.8	20.2	33.3
12.0							7.8	27.0	14.1	26.3	16.7	26.4	19.0	26.5
14.0									12.1	23.6	14.6	22.6	17.6	21.6
16.0											12.3	18.9	15.7	18.0
18.0													13.9	11.3
20.0														
22.0														
24.0														
26.0														
28.0														
30.0														
32.0														
34.0														
36.0														
38.0														
40.0														
42.0														
44.0														
46.0														
48.0														
50.0														
52.0														
54.0														
56.0														

オールテレーンクレーン[油圧伸縮ジブ型]【120t吊】 (2/4)

作業半径 (m)	24.0		26.0		28.0		30.0		32.0		34.0		36.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5														
3.0	25.3	58.4	27.0	48.4										
3.5	24.5	52.0	26.6	45.7	28.6	40.8	31.0	36.9						
4.0	24.9	54.3	26.9	49.7	28.9	45.6	30.9	37.8						
4.5	23.8	58.1	25.9	53.9	28.4	40.8	30.9	36.9	32.9	32.8	34.9	28.9	36.9	25.9
5.0	24.1	54.7	26.1	51.2	28.1	47.2	30.2	42.9	32.8	35.4	34.4	29.5	36.5	26.6
5.5	23.0	44.6	25.0	40.9	27.1	37.3	29.1	33.8	31.1	31.5	33.2	29.3	35.2	27.0
6.0	23.8	50.2	25.9	48.2	27.9	44.6	30.0	40.5	32.0	36.7	33.7	33.8	35.8	31.1
7.0	23.6	45.3	25.6	44.2	27.7	41.4	29.8	38.1	31.8	34.8	33.9	31.5	35.9	29.0
8.0	23.2	40.7	25.3	40.0	27.4	38.2	29.5	36.1	31.6	33.0	33.6	29.9	35.7	27.7
9.0	22.8	36.6	25.0	36.0	27.1	35.1	29.2	34.0	31.3	31.1	33.4	28.2	35.5	26.2
10.0	22.4	33.2	24.6	32.9	26.7	32.4	28.9	31.8	31.0	29.5	33.1	27.1	35.2	25.0
12.0	21.4	26.4	23.7	26.2	25.9	25.9	28.1	25.6	30.3	24.9	32.4	24.1	34.5	22.5
14.0	20.1	21.5	22.5	21.4	24.8	21.2	27.1	21.1	29.4	21.0	31.6	20.7	33.8	19.8
16.0	18.5	17.9	21.1	17.9	23.6	17.9	26.0	17.8	28.3	17.7	30.6	17.5	32.8	17.1
18.0	16.5	15.1	19.4	15.3	22.0	15.2	24.6	15.1	27.1	15.0	29.4	15.0	31.8	14.8
20.0	13.6	13.9	17.3	13.1	20.3	13.2	23.0	13.2	25.6	13.1	28.1	12.9	30.5	12.7
22.0			15.5	9.0	18.0	11.4	21.0	11.5	23.8	11.4	26.5	11.3	29.1	11.0
24.0					14.4	10.5	18.6	10.2	21.8	10.1	24.7	10.0	27.4	9.9
26.0							16.2	8.0	19.2	8.8	22.5	8.9	25.5	8.8
28.0									15.5	8.5	19.9	8.0	23.3	7.9
30.0											16.7	7.2	20.6	7.2
32.0														
34.0														
36.0														
38.0														
40.0														
42.0														
44.0														
46.0														
48.0														
50.0														
52.0														
54.0														
56.0														

オールテレーンクレーン[油圧伸縮ジブ型]【120t吊】 (3/4)

作業半径 (m)	38.0			40.0			42.0			44.0			46.0			48.0		
	フックの 地上高さ (m)	定格 総荷重 (t)		フックの 地上高さ (m)	定格 総荷重 (t)		フックの 地上高さ (m)	定格 総荷重 (t)		フックの 地上高さ (m)	定格 総荷重 (t)		フックの 地上高さ (m)	定格 総荷重 (t)		フックの 地上高さ (m)	定格 総荷重 (t)	
2.5																		
3.0																		
3.5																		
4.0																		
4.5																		
5.0	38.5	23.5		40.9	20.6													
5.5	37.2	24.8		40.6	21.0													
6.0	38.3	23.9		40.4	21.4													
7.0	37.6	27.1		39.6	24.7		42.4	19.1		44.4	17.2		45.2	14.9				
8.0	37.7	25.4		39.8	23.1		41.5	21.7		43.5	20.1		46.1	15.1		48.7	13.3	
9.0	37.5	24.2		39.6	22.2		41.6	20.3		43.7	18.8		45.4	17.6		47.5	15.8	
10.0	37.3	23.0		39.3	21.2		41.4	19.6		43.4	18.2		45.5	16.6		47.6	14.9	
12.0	36.7	21.0		38.8	19.4		40.8	18.0		42.9	16.9		45.0	15.6		47.1	14.2	
14.0	35.9	18.8		38.1	17.6		40.2	16.6		42.3	15.6		44.4	14.6		46.6	13.5	
16.0	35.1	16.6		37.3	15.7		39.4	15.1		41.6	14.4		43.7	13.7		45.9	12.8	
18.0	34.1	14.6		36.3	14.1		38.5	13.7		40.7	13.2		42.9	12.6		45.2	11.8	
20.0	32.9	12.5		35.2	12.4		37.5	12.1		39.8	11.9		42.0	11.5		44.3	11.0	
22.0	31.6	10.8		34.0	10.8		36.4	10.8		38.7	10.7		41.0	10.4		43.3	10.1	
24.0	30.1	9.8		32.6	9.6		35.1	9.5		37.5	9.4		39.8	9.3		42.2	9.2	
26.0	28.3	8.7		31.0	8.6		33.6	8.5		36.1	8.5		38.5	8.5		41.0	8.3	
28.0	26.3	7.7		29.2	7.6		31.9	7.6		34.5	7.6		37.1	7.5		39.6	7.4	
30.0	24.0	7.1		27.1	7.0		30.0	6.9		32.8	6.8		35.5	6.6		38.1	6.4	
32.0	21.2	6.4		24.6	6.2		27.8	6.0		30.8	5.9		33.6	5.8		36.4	5.6	
34.0	17.6	5.6		21.7	5.5		25.3	5.4		28.5	5.3		31.6	5.2		34.5	5.1	
36.0				17.0	3.8		22.2	4.9		25.9	4.8		29.2	4.7		32.4	4.6	
38.0							18.5	4.4		22.8	4.4		26.6	4.3		30.0	4.1	
40.0													23.4	3.9		27.2	3.7	
42.0													19.1	3.8		23.6	3.7	
44.0																		
46.0																		
48.0																		
50.0																		
52.0																		
54.0																		
56.0																		

オールテレーンクレーン[油圧伸縮ジブ型]【120t吊】（4／4）

作業半径 (m)	50.0		52.0		54.0		56.0		58.0		60.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5												
3.0												
3.5												
4.0												
4.5												
5.0												
5.5												
6.0												
7.0	50.3	16.7										
8.0	50.6	11.9	52.6	10.7	54.6	9.6	56.7	8.4				
9.0	50.4	11.9	52.4	10.7	54.4	9.6	56.5	8.5	58.5	8.0	60.5	7.4
10.0	49.6	13.3	51.3	12.1	54.3	9.6	56.3	8.5	58.3	8.0	60.4	7.4
12.0	49.2	12.8	50.9	11.5	53.9	9.6	55.9	8.5	58.0	8.0	60.0	7.4
14.0	48.7	12.2	50.4	11.0	53.4	9.6	55.4	8.5	57.5	8.0	59.5	7.4
16.0	48.0	11.6	49.8	10.5	52.8	9.6	54.9	8.5	57.0	8.0	59.0	7.4
18.0	47.3	10.9	49.1	10.1	52.1	9.6	54.2	8.5	56.3	8.0	58.4	7.4
20.0	46.5	10.2	48.3	9.5	51.4	9.1	53.5	8.5	55.6	8.0	57.8	7.4
22.0	45.6	9.5	47.4	9.0	50.5	8.9	52.7	8.5	54.9	7.9	57.0	7.4
24.0	44.5	8.8	46.4	8.6	49.6	8.5	51.8	7.9	54.0	7.6	56.2	7.3
26.0	43.4	8.0	45.4	8.0	48.5	7.9	50.8	7.3	53.1	7.0	55.3	6.8
28.0	42.1	7.2	44.1	7.5	47.4	7.3	49.7	6.8	52.0	6.6	54.3	6.4
30.0	40.7	6.2	42.8	6.5	46.1	6.9	48.5	6.4	50.8	6.2	53.2	6.0
32.0	39.1	5.6	41.3	5.9	44.7	6.4	47.2	5.9	49.6	5.7	52.0	5.5
34.0	37.3	5.0	39.7	5.3	43.2	5.9	45.7	5.5	48.2	5.3	50.6	5.1
36.0	35.4	4.5	37.8	4.8	41.5	5.3	44.1	5.1	46.7	5.0	49.2	4.8
38.0	33.2	4.0	35.8	4.3	39.6	4.8	42.3	4.6	45.0	4.6	47.6	4.5
40.0	30.7	3.6	33.5	3.9	37.5	4.3	40.4	4.1	43.2	4.1	45.9	4.1
42.0	27.8	3.3	31.0	3.5	35.1	3.8	38.2	3.6	41.2	3.6	44.1	3.6
44.0	24.4	2.9	28.0	3.2	32.5	3.4	35.8	3.2	39.0	3.2	42.0	3.1
46.0	19.9	2.9	24.6	2.8	29.5	3.0	33.1	2.8	36.5	2.8	39.7	2.7
48.0			20.0	2.5	26.0	2.6	30.0	2.4	33.8	2.4	37.2	2.4
50.0							26.4	2.1	30.6	2.1	34.4	2.0
52.0							22.0	1.8	26.9	1.8	31.1	1.7
54.0											27.4	1.4
56.0											22.3	1.4

オールテレーンクレーン[油圧伸縮ジブ型]【130t吊】 (1/4)

作業半径 (m)	11.8		12.0		14.0		16.0		18.0		20.0		22.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5	11.8	130.0												
3.0	11.7	120.0	11.9	118.3	14.1	101.5	16.1	86.9	18.2	74.0	20.4	87.0	23.0	83.6
3.5	11.6	110.0	11.8	108.5	13.9	94.4	16.0	82.6	18.0	71.8	20.2	86.9	22.2	84.6
4.0	11.4	101.0	11.6	99.7	13.8	87.6	15.9	79.0	18.0	70.7	20.0	83.4	22.0	80.3
4.5	11.2	89.0	11.4	88.0	13.6	79.8	15.7	73.0	17.8	66.4	19.9	80.5	21.9	77.6
5.0	11.0	79.5	11.2	78.8	13.5	72.6	15.6	67.9	17.7	63.2	19.8	78.8	21.8	76.3
5.5	10.7	72.3	10.9	71.8	13.3	67.6	15.4	64.0	17.5	60.4	19.6	77.0	21.7	74.6
6.0	10.5	65.2	10.7	64.8	13.1	62.6	15.2	60.1	17.4	57.6	19.5	75.2	21.6	72.9
7.0	9.8	56.0	10.0	55.8	12.5	55.7	14.8	54.5	17.0	53.4	19.1	72.2	21.3	69.9
8.0	9.0	47.7	9.2	47.7	11.9	49.2	14.3	48.9	16.5	48.7	18.7	48.5	20.9	46.6
9.0	7.9	41.4	8.2	41.4	11.1	43.2	13.6	42.9	16.0	42.7	18.3	42.6	20.5	41.6
10.0					10.3	41.5	13.0	40.5	15.6	39.9	17.7	37.8	20.0	37.4
12.0									14.0	32.5	16.4	30.4	18.9	30.3
14.0									11.9	26.6	14.7	24.5	17.4	24.6
16.0											12.3	18.5	15.5	20.1
18.0												13.3	18.4	
20.0														
22.0														
24.0														
26.0														
28.0														
30.0														
32.0														
34.0														
36.0														
38.0														
40.0														
42.0														
44.0														
46.0														
48.0														
50.0														
52.0														
54.0														

オールテレーンクレーン[油圧伸縮ジブ型]【130t吊】(2/4)

ブーム長さ (m) 作業半径 (m)	24.0		26.0		28.0		30.0		32.0		34.0		36.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5														
3.0	25.0	78.5												
3.5	24.3	76.9												
4.0	24.1	55.4	26.1	40.7	28.9	61.5								
4.5	24.0	53.5	26.0	49.4	28.2	62.0	30.2	54.7						
5.0	23.9	53.2	25.9	49.9	28.0	44.6	30.0	39.8	32.0	36.5	34.0	33.0		
5.5	23.8	51.9	25.8	49.1	27.9	44.1	29.9	39.5	31.9	36.3	33.9	32.9		
6.0	23.7	50.7	25.7	48.2	27.8	43.5	29.8	39.2	31.8	36.0	33.9	32.9	36.1	38.6
7.0	23.4	47.6	25.5	45.3	27.5	41.8	29.6	38.8	31.6	35.2	33.7	31.6	35.7	28.8
8.0	23.0	44.6	25.2	42.5	27.2	39.9	29.3	37.4	31.4	34.4	33.5	31.4	35.5	28.6
9.0	22.7	40.6	24.8	39.5	26.9	38.2	29.0	36.3	31.1	33.5	33.2	30.5	35.3	27.8
10.0	22.2	36.9	24.4	36.5	26.6	36.1	28.7	34.7	30.8	32.1	32.9	29.5	35.0	26.9
12.0	21.2	30.2	23.5	30.2	25.7	29.9	27.9	29.1	30.1	27.9	32.2	26.7	34.4	25.0
14.0	19.9	24.7	22.3	24.8	24.7	24.7	26.9	24.3	29.2	23.9	31.4	23.5	33.6	22.3
16.0	18.3	20.2	20.9	20.3	23.4	20.2	25.8	20.2	28.1	20.2	30.4	20.3	32.7	19.7
18.0	16.5	19.0	19.4	19.5	21.9	16.9	24.4	17.1	26.9	17.2	29.3	17.2	31.6	17.0
20.0			17.2	17.2	20.0	14.2	22.8	14.3	25.4	14.5	27.9	14.6	30.3	14.5
22.0			14.5	14.7	17.7	11.9	20.8	12.1	23.7	12.3	26.3	12.5	28.9	12.6
24.0					14.7	8.2	18.4	8.9	21.6	10.5	24.5	10.6	27.2	10.8
26.0							16.1	9.9	19.3	11.2	22.5	11.0	25.3	9.4
28.0							11.9	7.7	16.7	9.2	20.5	9.8	23.0	8.1
30.0											17.2	8.0	20.3	7.0
32.0											12.7	7.2	16.9	5.0
34.0														
36.0														
38.0														
40.0														
42.0														
44.0														
46.0														
48.0														
50.0														
52.0														
54.0														

オールテレーンクレーン[油圧伸縮ジブ型]【130t吊】(3/4)

作業半径 (m)	38.0		40.0		42.0		44.0		46.0		48.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5												
3.0												
3.5												
4.0												
4.5												
5.0												
5.5												
6.0	38.0	34.3										
7.0	37.8	26.6	39.8	24.5	41.8	22.2	43.7	17.0	45.8	15.5	47.8	14.0
8.0	37.6	26.5	39.6	24.4	41.6	22.4	43.7	20.3	45.7	18.2	47.6	14.0
9.0	37.3	25.7	39.4	23.9	41.4	22.2	43.5	20.3	45.5	18.4	47.6	16.5
10.0	37.1	24.9	39.1	23.2	41.2	21.7	43.3	20.0	45.3	18.3	47.4	16.5
12.0	36.5	23.1	38.6	21.6	40.7	20.4	42.7	19.1	44.8	17.8	46.9	16.4
14.0	35.7	20.6	37.9	19.4	40.0	18.4	42.1	17.5	44.2	16.7	46.3	15.8
16.0	34.9	18.3	37.1	17.3	39.2	16.4	41.4	15.5	43.5	15.4	45.7	15.2
18.0	33.9	16.0	36.1	15.3	38.4	14.7	40.6	14.1	42.7	14.0	44.9	13.9
20.0	32.7	14.0	35.1	13.5	37.3	13.2	39.6	12.8	41.8	12.6	44.0	12.5
22.0	31.4	12.3	33.8	12.0	36.2	11.8	38.5	11.5	40.8	11.3	43.1	11.2
24.0	29.9	10.8	32.4	10.7	34.9	10.6	37.3	10.5	39.7	10.2	42.0	10.0
26.0	28.1	9.5	30.8	9.6	33.4	9.5	35.9	9.5	38.4	9.3	40.8	9.1
28.0	26.1	8.3	29.0	8.4	31.7	8.4	34.4	8.4	36.9	8.3	39.4	8.2
30.0	23.7	7.2	26.9	7.3	29.8	7.4	32.6	7.5	35.3	7.4	37.9	7.3
32.0	20.9	5.2	24.4	6.3	27.6	6.4	30.6	6.5	33.5	6.6	36.2	6.6
34.0	18.1	6.6	21.7	7.2	25.3	7.1	28.3	5.8	31.4	5.9	34.3	5.9
36.0	13.3	5.5	18.6	6.0	22.8	6.3	25.7	5.0	29.1	5.2	32.2	5.3
38.0					19.1	5.5	22.6	4.4	26.3	4.4	29.7	4.5
40.0					14.0	5.2	18.7	3.7	23.1	3.8	26.9	3.9
42.0							13.4	1.4	19.1	2.2	23.7	3.4
44.0											19.6	2.8
46.0												
48.0												
50.0												
52.0												
54.0												

オールテレーンクレーン[油圧伸縮ジブ型]【130t吊】 (4/4)

作業半径 (m)		50.0		52.0		54.0		56.0		58.0		60.0	
ブーム長さ (m)	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	
2.5													
3.0													
3.5													
4.0													
4.5													
5.0													
5.5													
6.0													
7.0													
8.0	49.7	13.0	51.7	12.0									
9.0	49.6	14.9	51.5	12.0									
10.0	49.4	15.1	51.4	13.7	53.6	14.8	55.6	13.2					
12.0	49.0	15.0	51.0	13.6	53.3	14.7	55.3	13.2	57.4	11.9	59.3	10.6	
14.0	48.4	14.7	50.5	13.6	52.8	14.6	54.8	13.2	56.9	11.9	58.9	10.6	
16.0	47.8	14.2	49.9	13.3	52.2	14.1	54.3	13.0	56.4	11.8	58.4	10.6	
18.0	47.1	13.4	49.2	12.8	51.5	13.3	53.6	12.4	55.7	11.4	57.8	10.5	
20.0	46.2	12.2	48.4	11.9	50.8	12.5	52.9	11.8	55.0	11.1	57.1	10.4	
22.0	45.3	10.9	47.5	10.6	49.9	11.5	52.1	11.1	54.3	10.4	56.3	9.6	
24.0	44.3	9.8	46.5	9.6	49.0	10.6	51.2	10.3	53.4	9.6	55.5	8.8	
26.0	43.1	8.9	45.4	8.7	47.9	9.8	50.2	9.7	52.5	8.9	54.6	8.0	
28.0	41.8	8.0	44.2	7.8	46.8	9.0	49.1	8.9	51.4	8.1	53.6	7.3	
30.0	40.4	7.3	42.9	7.2	45.5	8.2	47.9	8.1	50.2	7.4	52.5	6.7	
32.0	38.8	6.5	41.4	6.5	44.1	7.5	46.6	7.4	49.0	6.9	51.3	6.2	
34.0	37.1	5.8	39.8	5.7	42.6	6.8	45.1	6.8	47.6	6.3	50.0	5.7	
36.0	35.1	5.2	37.9	5.2	40.9	6.3	43.5	6.3	46.1	5.8	48.5	5.3	
38.0	32.9	4.6	35.9	4.7	39.0	5.8	41.7	5.6	44.4	5.3	47.0	4.9	
40.0	30.4	4.1	33.6	4.2	36.9	5.3	39.8	5.1	42.6	4.8	45.2	4.5	
42.0	27.5	3.5	31.1	3.7	34.5	4.8	37.6	4.6	40.6	4.4	43.4	4.2	
44.0	24.2	3.0	28.1	3.1	31.9	4.3	35.2	4.1	38.4	4.0	41.3	3.9	
46.0	20.8	3.7	24.7	2.7	28.9	3.9	32.5	3.7	35.9	3.6	39.0	3.6	
48.0			20.4	2.8	25.3	3.5	29.4	3.3	33.2	3.3	36.5	3.4	
50.0					21.6	2.7	25.8	2.9	30.0	2.9	33.7	3.0	
52.0							21.3	2.7	26.2	2.7	30.5	2.6	
54.0											26.7	2.3	

オールテレーンクレーン[油圧伸縮ジブ型]【150t吊】 (1/4)

作業半径 (m)	12.3		14.0		16.0		18.0		20.0		22.0		24.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0	11.8	150.0	13.9	107.5	16.0	84.8	18.0	79.7	20.0	79.0	22.1	77.2	24.1	74.9
3.5	11.7	111.3	13.4	95.9	15.5	77.8	17.5	73.9	19.6	73.5	21.6	73.0	23.6	72.5
4.0	11.5	101.6	13.7	85.4	15.8	76.9	17.8	74.8	19.9	74.2	21.9	73.5	23.9	72.9
4.5	11.3	92.8	13.1	85.1	15.2	76.0	17.3	73.9	19.4	73.5	21.4	73.0	23.5	72.5
5.0	11.1	85.7	13.3	75.9	15.5	72.2	17.6	71.0	19.6	70.4	21.7	69.8	23.7	69.2
5.5	10.9	80.8	13.1	72.3	15.3	69.6	17.4	68.5	19.5	67.8	21.6	66.9	23.6	66.0
6.0	10.6	75.9	12.9	68.6	15.1	67.0	17.2	66.0	19.3	65.1	21.4	64.0	23.5	62.9
7.0	10.0	67.0	12.4	60.8	14.6	59.6	16.8	59.1	19.0	58.8	21.1	58.0	23.2	57.0
8.0	9.2	57.4	11.7	53.2	14.1	53.1	16.4	53.1	18.6	53.2	20.8	52.6	22.9	51.7
9.0	8.3	49.9	11.0	46.1	13.5	46.9	15.8	47.1	18.1	47.2	20.3	46.9	22.5	46.6
10.0	7.1	40.4	9.7	42.0	12.4	43.9	15.2	42.4	17.6	42.5	19.9	42.5	22.1	42.5
12.0							13.7	34.4	16.3	34.6	18.7	34.9	21.0	35.1
14.0							11.6	26.5	14.5	28.3	17.2	29.1	19.8	29.3
16.0											15.4	24.7	18.1	24.6
18.0											12.9	19.4	16.1	20.4
20.0														
22.0														
24.0														
26.0														
28.0														
30.0														
32.0														
34.0														
36.0														
38.0														
40.0														
42.0														
44.0														
46.0														
48.0														
50.0														
52.0														

オールテレーンクレーン[油圧伸縮ジブ型]【150t吊】 (2/4)

作業半径 (m)	26.0		28.0		30.0		32.0		34.0		36.0		38.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0														
3.5	25.7	70.1	27.7	66.8										
4.0	25.9	69.6	28.0	64.7										
4.5	25.5	70.1	27.5	66.8	29.5	61.6	31.6	55.0						
5.0	25.8	66.9	27.8	63.6	29.8	58.5	31.9	52.1						
5.5	25.7	64.3	27.7	62.1	29.7	57.7	31.8	51.7						
6.0	25.6	61.7	27.6	60.6	29.7	57.0	31.7	51.4	33.7	46.8	35.8	43.0	37.4	41.9
7.0	25.3	56.0	27.4	55.0	29.4	52.7	31.5	49.4	33.5	46.0	35.6	42.6	37.6	38.7
8.0	25.0	50.9	27.1	50.1	29.2	48.7	31.2	46.9	33.3	44.6	35.4	41.8	37.4	38.3
9.0	24.7	46.2	26.8	45.8	28.9	45.2	31.0	44.5	33.0	43.0	35.1	40.7	37.2	37.4
10.0	24.3	42.3	26.4	41.9	28.5	41.4	30.7	40.9	32.8	39.8	34.8	38.0	36.9	35.3
12.0	23.3	35.1	25.6	34.8	27.8	34.6	29.9	34.4	32.1	33.5	34.2	32.1	36.3	30.3
14.0	22.2	29.3	24.5	29.2	26.8	29.0	29.0	28.7	31.2	28.1	33.4	27.1	35.6	26.1
16.0	20.8	24.6	23.2	24.5	25.6	24.3	28.0	24.1	30.3	23.6	32.5	23.1	34.7	22.5
18.0	19.0	20.7	21.7	20.6	24.3	20.4	26.7	20.2	29.1	20.0	31.4	19.9	33.7	19.7
20.0	16.9	17.7	19.9	17.6	22.6	17.4	25.2	17.2	27.8	17.2	30.2	17.4	32.6	17.4
22.0	14.1	14.6	17.6	15.0	20.7	15.3	23.5	15.4	26.2	15.4	28.8	15.3	31.2	15.1
24.0					18.3	13.4	21.4	13.6	24.3	13.6	27.1	13.4	29.7	13.2
26.0					15.2	11.6	18.9	12.0	22.2	12.1	25.2	11.8	28.0	11.7
28.0					11.6	7.7	16.3	9.2	19.5	10.7	22.9	10.5	25.9	10.3
30.0									16.3	9.3	20.2	9.4	23.6	9.4
32.0									12.3	7.2	17.3	7.8	20.8	8.6
34.0													17.2	7.5
36.0													13.0	5.5
38.0														
40.0														
42.0														
44.0														
46.0														
48.0														
50.0														
52.0														

オールテレーンクレーン[油圧伸縮ジブ型]【150t吊】 (3/4)

作業半径 (m)	40.0		42.0		44.0		46.0		48.0		50.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0												
3.5												
4.0												
4.5												
5.0												
5.5												
6.0	39.4	37.0										
7.0	39.6	34.3	41.3	32.9	43.3	29.6						
8.0	39.5	34.0	41.5	30.3	43.5	27.3	45.2	26.6	47.2	24.0		
9.0	39.2	33.3	41.3	29.8	43.3	27.1	45.4	24.5	47.4	22.1	49.1	21.4
10.0	39.0	31.8	41.1	28.8	43.1	26.5	45.2	24.2	47.2	21.9	49.2	19.7
12.0	38.4	28.3	40.5	26.4	42.6	24.7	44.7	23.0	46.7	21.3	48.8	19.5
14.0	37.7	25.0	39.9	23.9	42.0	22.6	44.1	21.3	46.2	20.0	48.3	18.6
16.0	36.9	21.9	39.1	21.2	41.2	20.4	43.4	19.5	45.5	18.5	47.6	17.4
18.0	36.0	19.4	38.2	19.0	40.4	18.5	42.6	17.8	44.8	16.9	46.9	16.0
20.0	34.9	17.1	37.2	16.7	39.5	16.3	41.7	15.8	43.9	15.4	46.1	14.8
22.0	33.7	14.9	36.0	14.6	38.4	14.4	40.7	14.2	42.9	13.9	45.2	13.5
24.0	32.3	13.0	34.7	12.8	37.1	12.7	39.5	12.5	41.8	12.3	44.1	12.1
26.0	30.7	11.6	33.2	11.5	35.8	11.3	38.2	11.2	40.6	11.1	43.0	11.0
28.0	28.8	10.3	31.6	10.2	34.2	10.1	36.8	10.1	39.2	10.0	41.7	9.9
30.0	26.7	9.3	29.7	9.3	32.4	9.2	35.1	9.1	37.7	9.0	40.3	8.9
32.0	24.3	8.5	27.5	8.4	30.5	8.3	33.3	8.2	36.0	8.1	38.7	8.0
34.0	21.3	7.6	24.9	7.6	28.2	7.5	31.2	7.3	34.1	7.2	36.9	7.1
36.0	18.3	6.0	21.9	6.9	25.6	6.9	28.9	6.8	32.0	6.6	35.0	6.5
38.0			18.1	6.2	22.4	6.2	26.2	6.1	29.6	6.0	32.8	5.9
40.0			13.6	5.2	19.1	5.1	23.0	5.6	26.8	5.5	30.3	5.4
42.0							19.0	5.1	23.5	5.0	27.4	5.0
44.0											24.0	4.5
46.0											19.9	4.1
48.0												
50.0												
52.0												

オールテレーンクレーン[油圧伸縮ジブ型]【150t吊】 (4/4)

作業半径 (m)	52.0		54.0		56.0		58.0		60.0		62.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0												
3.5												
4.0												
4.5												
5.0												
5.5												
6.0												
7.0												
8.0												
9.0	51.1	19.1										
10.0	51.3	17.7	53.0	17.0	55.0	15.5	57.0	13.9	59.0	12.3		
12.0	50.9	17.6	52.9	15.8	55.0	14.4	57.0	13.0	58.7	12.1	60.7	11.2
14.0	50.3	17.0	52.4	15.5	54.5	14.2	56.5	12.8	58.2	11.9	60.3	11.0
16.0	49.7	16.1	51.8	14.9	53.9	13.7	56.0	12.5	57.7	11.5	59.8	10.8
18.0	49.0	15.1	51.2	14.1	53.3	13.1	55.4	12.0	57.1	11.0	59.2	10.5
20.0	48.3	14.1	50.4	13.3	52.6	12.5	54.7	11.6	56.5	10.4	58.6	10.1
22.0	47.4	13.0	49.6	12.4	51.8	11.7	53.9	11.0	55.7	9.8	57.9	9.7
24.0	46.4	11.9	48.6	11.6	50.9	11.0	53.1	10.3	54.9	9.3	57.1	9.2
26.0	45.3	10.9	47.6	10.7	49.9	10.2	52.1	9.7	54.0	8.8	56.2	8.7
28.0	44.1	9.8	46.4	9.6	48.8	9.4	51.1	9.0	53.0	8.3	55.2	8.3
30.0	42.7	8.8	45.2	8.6	47.5	8.5	49.9	8.3	51.9	7.8	54.1	7.9
32.0	41.2	7.9	43.8	7.7	46.2	7.6	48.6	7.5	50.6	7.4	53.0	7.5
34.0	39.6	7.1	42.2	7.1	44.8	6.9	47.2	6.8	49.3	6.8	51.7	6.9
36.0	37.8	6.4	40.5	6.3	43.2	6.2	45.7	6.1	47.9	6.2	50.4	5.5
38.0	35.8	5.8	38.6	5.7	41.4	5.6	44.1	5.5	46.3	5.7	48.9	5.4
40.0	33.5	5.3	36.5	5.1	39.5	5.0	42.3	4.9	44.6	5.1	47.3	4.7
42.0	30.9	4.8	34.2	4.6	37.3	4.5	40.3	4.3	42.7	4.6	45.5	4.2
44.0	28.0	4.4	31.6	4.2	34.9	4.1	38.0	3.9	40.7	4.1	43.6	3.8
46.0	24.5	4.0	28.5	3.8	32.2	3.6	35.6	3.5	38.4	3.8	41.5	3.5
48.0			25.0	3.4	29.1	3.3	32.8	3.2	35.9	3.4	39.1	3.1
50.0			20.7	3.1	25.5	3.0	29.7	2.9	33.1	3.1	36.5	2.8
52.0							25.6	2.9	29.8	2.9	33.7	2.6

オールテレーンクレーン[油圧伸縮ジブ型]【160t吊】(1/2)

作業半径 (m)	13.2		14.0		16.0		18.0		20.0		22.0		24.0		26.0		28.0		30.0		32.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0	14.6	160.0	15.4	139.7	17.5	88.9	19.5	47.2	21.5	42.0	23.5	37.1	25.6	38.7	27.6	40.3						
3.5	14.5	149.8	15.0	132.7	17.1	88.6	19.1	52.0	21.2	46.9	23.2	42.1	25.5	36.4	27.5	38.2	29.5	36.6	31.5	34.4		
4.0	14.3	138.7	14.9	123.0	17.0	83.0	19.0	49.8	21.1	44.8	23.1	40.2	25.4	34.2	27.4	36.0	29.5	34.5	31.5	32.4		
4.5	14.1	129.1	14.7	114.7	16.8	78.2	18.9	47.9	20.9	43.0	23.0	38.4	25.3	32.0	27.3	33.7	29.4	32.4	31.4	30.6	33.4	30.2
5.0	14.0	120.5	14.5	107.0	16.7	73.7	18.8	46.1	20.8	41.3	22.9	36.8	25.2	30.0	27.3	31.6	29.3	30.5	31.3	29.0	33.3	28.7
5.5	13.7	110.1	14.3	98.2	16.5	68.5	18.6	43.9	20.7	39.2	22.8	34.9	25.0	31.8	27.0	32.8	29.0	31.5	31.1	29.8	33.3	27.1
6.0	13.5	99.7	14.1	89.4	16.3	63.3	18.4	41.6	20.5	37.2	22.6	33.0	24.7	33.6	26.8	34.1	28.8	32.6	30.9	30.6	33.2	25.6
7.0	12.9	83.9	13.6	76.0	15.8	55.3	18.0	37.9	20.2	33.7	22.3	29.7	24.4	30.4	26.5	31.0	28.6	29.7	30.6	28.1	32.7	27.9
8.0	12.2	72.1	12.9	65.8	15.3	49.0	17.6	34.7	19.8	30.7	22.0	26.8	24.1	27.4	26.2	28.0	28.3	26.9	30.4	25.4	32.4	25.4
9.0	11.4	62.9	12.2	57.8	14.7	43.8	17.0	31.9	19.3	28.1	21.5	24.6	23.7	25.2	25.9	25.6	28.0	24.5	30.1	23.2	32.2	23.3
10.0	10.4	50.6	11.3	48.0	13.9	38.2	16.4	29.6	18.8	25.9	21.1	22.5	23.3	23.0	25.5	23.4	27.6	22.5	29.7	21.2	31.9	21.4
12.0							15.2	22.8	17.5	22.4	19.9	19.1	22.2	19.5	24.5	20.0	26.8	19.1	29.0	18.1	31.1	18.3
14.0							13.1	20.9	15.7	19.7	18.4	16.4	21.0	16.9	23.4	17.3	25.7	16.6	28.0	15.6	30.2	15.9
16.0									11.3	27.5	16.6	14.3	19.3	14.8	22.0	15.1	24.4	14.5	26.8	13.6	29.2	13.9
18.0											14.4	11.0	17.3	13.2	20.2	13.5	22.9	12.9	25.5	12.1	27.9	12.3
20.0													12.5	20.8	15.9	21.6	21.1	11.3	23.8	10.7	26.4	11.0
22.0																	19.1	9.0	22.1	8.2	24.7	9.7
24.0																					22.6	8.7
26.0																					20.1	7.9
28.0																					14.8	12.6
30.0																						
32.0																						
34.0																						
36.0																						
38.0																						
40.0																						
42.0																						
44.0																						
46.0																						
48.0																						

オールテレーンクレーン[油圧伸縮ジブ型]【160t吊】（2/2）

作業半径 (m)	34.0		36.0		38.0		40.0		42.0		44.0		46.0		48.0		50.0		52.0		54.0		56.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0																								
3.5																								
4.0																								
4.5	35.4	30.4																						
5.0	35.4	29.0																						
5.5	35.3	27.6																						
6.0	35.2	26.3	37.2	26.5	39.3	26.3	41.3	25.4	43.3	23.5														
7.0	34.7	28.3	35.8	28.3	38.8	28.0	40.8	27.2	43.2	22.9	45.2	21.7	47.2	20.6	49.2	19.5	51.1	18.6						
8.0	34.5	26.2	35.6	26.4	38.6	26.2	40.7	25.8	42.7	25.2	44.7	24.3	47.0	20.6	48.6	21.3	50.6	19.9	53.0	17.8	55.0	17.4	57.0	17.1
9.0	34.2	24.1	35.3	24.5	38.4	24.3	40.4	24.2	42.5	24.2	44.5	24.0	46.6	22.8	48.6	24.3	50.4	19.9	52.8	17.8	54.8	17.4	56.8	17.1
10.0	34.0	22.2	35.0	22.6	38.1	22.6	40.2	22.6	42.3	22.6	44.3	22.5	46.4	21.9	48.4	21.1	50.4	19.9	52.3	17.7	54.4	17.4	56.4	17.1
12.0	33.3	19.1	35.4	19.5	37.5	19.7	39.6	19.8	41.7	19.9	43.8	20.0	45.9	19.8	47.9	19.7	50.0	19.3	52.3	17.7	54.4	17.4	56.4	17.1
14.0	32.4	16.6	34.6	17.0	36.8	17.2	38.9	17.4	41.1	17.6	43.2	17.8	45.3	17.8	47.4	17.7	49.5	17.6	51.8	16.6	53.9	16.5	56.0	16.4
16.0	31.5	14.5	33.7	15.0	35.9	15.2	38.1	15.5	40.3	15.7	42.4	16.0	44.6	16.0	46.7	16.0	48.8	16.0	51.2	15.2	53.3	15.2	55.4	15.1
18.0	30.3	12.9	32.6	13.3	34.9	13.6	37.2	13.9	39.4	14.2	41.6	14.4	43.8	14.5	46.0	14.6	48.1	14.6	50.5	14.0	52.7	14.0	54.8	14.0
20.0	29.0	11.5	31.4	11.9	33.8	12.3	36.1	12.6	38.4	12.9	40.7	13.2	42.9	13.3	45.1	13.4	47.3	13.4	49.7	13.0	51.9	13.0	54.0	13.0
22.0	27.4	10.3	30.0	10.8	32.4	11.1	34.9	11.4	37.2	11.7	39.6	12.0	41.9	12.2	44.1	12.3	46.4	12.4	48.9	12.1	51.1	12.1	53.2	12.2
24.0	25.5	9.3	28.3	9.7	30.9	10.0	33.5	10.3	35.9	10.7	38.3	11.1	40.7	11.2	43.0	11.3	45.3	11.5	47.9	11.3	50.1	11.3	52.3	11.4
26.0	23.4	8.4	26.4	8.8	29.2	9.1	31.9	9.4	34.4	9.9	37.0	10.2	39.4	10.4	41.8	10.5	44.2	10.7	46.8	10.6	49.1	10.7	51.3	10.8
28.0	18.6	12.8	24.1	8.0	27.2	8.2	30.0	8.5	32.8	9.0	35.4	9.4	38.0	9.7	40.4	9.8	42.9	10.0	45.6	9.9	47.9	10.0	50.2	10.1
30.0			21.6	6.9	25.1	7.0	28.2	7.3	30.9	8.3	33.6	8.7	36.3	8.9	38.9	9.1	41.5	9.3	44.2	9.4	46.6	9.5	49.0	9.6
32.0							25.7	6.7	28.7	7.6	31.7	8.0	34.5	8.2	37.2	8.3	39.9	8.6	42.7	8.7	45.2	8.8	47.7	8.7
34.0							22.8	6.2	26.1	6.9	29.4	7.3	32.4	7.5	35.3	7.6	38.1	8.0	41.1	8.3	43.7	8.2	46.2	8.0
36.0							19.2	5.8	23.1	6.4	26.8	6.8	30.1	6.9	33.2	7.0	36.2	7.4	39.3	7.8	42.0	7.7	44.6	7.4
38.0									17.2	6.6	23.6	6.3	27.4	6.4	30.8	6.4	34.0	6.8	37.2	7.3	40.1	7.1	42.9	6.7
40.0											20.1	5.8	24.2	5.9	28.0	6.0	31.5	6.4	35.0	6.8	38.0	6.6	40.9	6.2
42.0													18.0	5.1	24.7	5.6	28.6	5.9	32.4	6.3	35.7	6.1	38.8	5.7
44.0															20.9	5.2	25.2	5.4	29.5	5.9	33.0	5.7	36.4	5.3
46.0																	18.9	3.9			26.5	4.9	30.6	4.5
48.0																								

オールテレンクレーン[油圧伸縮ジブ型]【170t吊】 (1/2)

ブーム長さ (m) 作業半径 (m)		13.33		14.0		16.0		18.0		20.0		22.0		24.0		26.0		28.0		30.0		32.0	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)		
2.5	15.1	170.0																					
3.0	15.0	152.0	15.7	151.0	17.7	148.0	19.8	145.0	21.8	140.7	23.8	136.4	25.8	126.1	27.8	112.9							
3.5	14.9	139.5	15.5	138.9	17.6	136.9	19.7	135.0	21.7	131.8	23.7	128.5	25.7	120.8	27.8	111.0							
4.0	14.7	127.0	15.4	126.7	17.5	125.9	19.6	125.0	21.6	122.9	23.6	120.7	25.7	115.5	27.7	109.0	29.7	100.7	31.7	89.7			
4.5	14.5	118.5	15.3	118.3	17.3	117.6	19.4	117.0	21.5	115.3	23.5	113.6	25.6	110.2	27.6	106.0	29.6	99.4	31.7	89.1			
5.0	14.4	110.0	15.1	109.9	17.2	109.4	19.3	109.0	21.4	107.7	23.4	106.4	25.5	104.8	27.5	103.1	29.6	98.2	31.6	88.5	33.6	79.1	
5.5	14.1	103.0	14.9	102.9	17.0	102.4	19.1	102.0	21.2	101.1	23.3	100.3	25.4	99.2	27.4	98.0	29.5	94.2	31.5	86.4	33.5	78.6	
6.0	13.9	96.0	14.7	95.9	16.8	95.4	19.0	95.0	21.1	94.6	23.2	94.1	25.2	93.6	27.3	92.9	29.4	90.2	31.4	84.2	33.4	78.1	
7.0	13.3	85.0	14.1	84.9	16.4	84.4	18.6	84.0	20.7	84.0	22.9	84.0	25.0	83.7	27.0	83.3	29.1	81.5	31.2	77.8	33.2	73.9	
8.0	12.7	76.0	13.5	75.8	15.9	75.2	18.1	74.5	20.3	74.7	22.5	74.9	24.6	75.0	26.7	75.0	28.8	74.1	30.9	71.9	33.0	69.5	
9.0	11.8	67.5	12.7	67.4	15.2	67.2	17.6	67.0	19.9	67.2	22.1	67.4	24.3	67.7	26.4	67.9	28.5	67.6	30.6	66.5	32.7	65.0	
10.0	10.8	54.0	11.8	55.0	14.5	58.0	17.0	61.0	19.3	61.0	21.6	61.0	23.8	61.2	26.0	61.4	28.2	61.5	30.3	61.5	32.4	61.1	
12.0									18.0	51.0	20.4	51.0	22.8	51.2	25.1	51.4	27.3	51.7	29.5	52.1	31.7	52.2	
14.0									16.3	40.9	19.0	42.9	21.5	43.7	23.9	43.9	26.3	44.2	28.5	44.6	30.8	44.9	
16.0													19.9	37.7	22.5	37.9	25.0	38.2	27.4	38.6	29.7	39.0	
18.0													17.9	30.9	20.8	32.2	23.5	33.2	26.0	33.6	28.5	34.0	
20.0																	21.6	29.2	24.4	29.6	27.0	30.1	
22.0																	19.3	24.4	22.4	25.5	25.2	26.6	
24.0																	16.4	16.6	20.0	20.0	23.2	23.1	
26.0																					20.7	19.9	
28.0																						14.3	
30.0																							
32.0																							
34.0																							
36.0																							
38.0																							
40.0																							
42.0																							
44.0																							
46.0																							
48.0																							
50.0																							

オールテレーンクレーン[油圧伸縮ジブ型]【170t吊】（2／2）

作業半径 (m)	34.0		36.0		38.0		40.0		42.0		44.0		46.0		48.0		50.0		52.0		54.0		56.0	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重		
2.5	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)		
3.0																								
3.5																								
4.0																								
4.5																								
5.0	35.6	71.1	37.7	63.2																				
5.5	35.6	70.9	37.6	63.1																				
6.0	35.5	70.6	37.5	63.1	39.5	56.5	41.6	50.1																
7.0	35.3	68.3	37.3	62.8	39.4	56.3	41.4	49.7	43.4	45.1	45.4	41.5	38.0	49.3	34.7	51.4	31.5	53.4	28.6	55.4	25.8			
8.0	35.1	64.8	37.1	60.2	39.2	54.2	41.2	48.1	43.2	44.0	45.3	41.0	47.3	47.1	38.0	49.2	34.7	51.2	31.5	53.2	28.6	25.8		
9.0	34.8	61.1	36.9	57.1	38.9	51.6	41.0	45.9	43.0	42.6	45.1	40.5	46.9	46.9	38.0	49.0	34.7	51.0	31.5	53.0	28.6	55.1		
10.0	34.5	57.3	36.6	53.6	38.7	48.7	40.7	43.7	42.8	41.2	44.9	39.9	45.8	45.8	38.0	49.0	34.7	51.0	31.5	53.0	28.6	55.1		
12.0	33.8	49.8	35.9	47.4	38.1	43.5	40.2	39.4	42.3	37.4	44.3	36.6	46.4	46.4	35.3	48.5	33.1	50.5	31.0	52.6	28.3	54.7		
14.0	33.0	43.5	35.2	42.2	37.3	39.1	39.5	35.7	41.6	33.8	43.7	32.7	45.8	45.8	31.6	47.9	30.3	50.0	29.0	52.1	27.2	54.2		
16.0	32.0	38.5	34.3	38.1	36.5	35.7	38.7	32.9	40.8	31.2	43.0	29.9	45.1	45.1	28.7	47.3	27.6	49.4	26.5	51.5	25.0	53.6		
18.0	30.8	34.3	33.2	34.5	35.5	32.6	37.7	30.3	40.0	28.4	42.2	26.7	44.3	44.3	25.2	46.5	24.4	48.7	23.5	50.8	22.6	52.9		
20.0	29.5	30.5	31.9	30.9	34.3	29.4	36.6	27.6	38.9	25.9	41.2	24.2	43.4	43.4	22.8	45.6	22.1	47.8	21.5	50.0	20.8	52.2		
22.0	27.9	27.0	30.5	27.4	33.0	26.7	35.4	25.8	37.8	24.2	40.1	22.3	42.4	42.4	20.8	44.7	20.1	46.9	19.5	49.1	18.9	51.3		
24.0	26.1	23.5	28.8	23.9	31.5	23.8	34.0	23.6	36.5	22.2	38.9	20.2	41.2	41.2	18.6	43.6	18.0	45.9	17.4	48.1	17.0	50.4		
26.0	23.9	20.4	26.9	20.9	29.7	21.4	32.4	21.9	35.0	20.7	37.5	18.7	40.0	40.0	17.1	42.4	16.6	44.7	16.0	47.0	15.7	49.3		
28.0	21.3	16.3	24.6	18.2	27.7	18.8	30.6	19.2	33.3	18.3	35.9	16.8	38.5	38.5	15.6	41.0	15.1	43.4	14.6	45.8	14.3	48.2		
30.0					25.3	16.8	28.5	17.2	31.4	16.5	34.2	15.4	36.9	36.9	14.4	39.5	13.9	42.0	13.4	44.5	13.1	46.9		
32.0					22.5	13.8	26.0	15.1	29.2	14.9	32.2	14.1	35.1	35.1	13.4	37.8	12.9	40.4	12.4	43.0	12.1	45.5		
34.0									26.7	13.6	29.9	13.0	33.0	33.0	12.5	35.9	12.0	38.7	11.5	41.3	11.2	44.0		
36.0									23.6	11.5	27.3	11.6	30.6	30.6	11.5	33.8	10.9	36.7	10.3	39.5	10.1	42.3		
38.0													27.9	27.9	10.6	31.3	9.9	34.5	9.2	37.5	9.0	40.4		
40.0													24.7	24.7	9.3	28.5	8.9	32.0	8.6	35.2	8.4	38.3		
42.0																								
44.0																		29.1	8.0	32.7	7.8	35.9		
46.0																		25.8	7.5	29.7	7.3	33.3		
48.0																		21.6	5.1	26.3	5.7	30.3		
50.0																								

オールテレレンクレーン[油圧伸縮ジブ型]【200t吊】(1/3)

ブーム長さ (m) 作業半径 (m)	13.2		14.0		16.0		18.0		20.0		22.0		24.0		26.0		28.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.7	14.2	200.0																
3.0	14.1	154.5	13.4	175.7	15.4	146.6	17.5	118.1	21.0	101.2	23.0	90.6	25.1	83.4	27.1	76.1		
3.5	14.0	142.5	13.3	162.8	15.4	140.6	17.4	118.5	20.9	101.2	23.0	90.6	25.0	83.4	27.0	76.1	29.0	71.8
4.0	13.8	132.3	13.2	151.7	15.2	135.1	17.3	118.3	19.3	114.2	21.4	110.9	24.9	83.4	26.9	76.1	29.0	71.8
4.5	13.7	123.3	13.0	142.1	15.1	130.3	17.2	118.1	19.2	114.2	21.3	110.9	24.8	83.4	26.9	76.1	28.9	71.8
5.0	13.5	115.4	12.8	133.5	14.9	125.5	17.0	117.0	19.1	113.7	21.2	110.9	23.2	103.6	25.3	93.6	27.3	84.5
5.5	13.2	108.6	12.6	126.1	14.8	120.4	16.9	114.6	19.0	112.2	21.0	109.9	23.1	102.6	25.1	92.8	27.2	84.0
6.0	13.0	101.8	12.4	118.6	14.6	115.4	16.7	112.2	18.8	110.6	20.9	109.0	23.0	101.7	25.0	92.1	27.1	83.5
7.0	12.4	88.1	11.9	105.1	14.1	102.4	16.3	99.9	18.5	98.6	20.6	97.4	22.7	92.4	24.8	86.0	26.9	79.1
8.0	11.8	76.2	11.2	92.5	13.6	91.0	15.9	89.6	18.1	88.2	20.2	86.7	22.4	83.8	24.5	80.2	26.6	74.9
9.0	10.9	66.9	10.5	82.5	13.0	80.7	15.3	78.9	17.6	78.2	19.8	77.4	22.0	75.7	24.1	73.6	26.3	70.5
10.0	9.9	54.8	9.5	72.2	12.2	71.6	14.7	70.9	17.1	70.4	19.3	69.9	21.6	69.2	23.7	68.4	25.9	67.2
12.0							14.7	47.6	15.7	57.6	18.2	57.2	20.5	56.8	22.8	56.2	25.0	55.5
14.0							12.6	38.1	14.0	46.8	16.7	46.4	19.2	46.3	21.7	46.2	24.0	46.1
16.0									11.9	36.3	15.9	34.5	17.6	38.8	20.2	39.2	22.7	39.3
18.0											13.9	27.3	15.6	33.0	18.5	33.4	21.2	33.7
20.0													12.3	28.1	15.7	29.1	19.3	28.2
22.0																	18.6	20.8
24.0																		
26.0																		
28.0																		
30.0																		
32.0																		
34.0																		
36.0																		
38.0																		
40.0																		
42.0																		
44.0																		
46.0																		
48.0																		
50.0																		
52.0																		
54.0																		

オールテレーンクレーン[油圧伸縮ジブ型]【200t吊】(2/3)

ブーム長さ (m) 作業半径 (m)	30.0		32.0		34.0		36.0		38.0		40.0		42.0		44.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.7																
3.0																
3.5	31.1	68.1														
4.0	31.0	68.1														
4.5	30.9	68.1	32.9	63.7	35.0	58.9										
5.0	29.3	75.6	32.9	63.7	34.9	58.9										
5.5	29.2	75.3	32.8	63.7	34.8	58.9										
6.0	29.1	75.1	32.7	63.7	34.7	58.9	36.8	53.4	38.8	47.2	40.8	41.8	42.8	37.9		
7.0	28.9	72.2	31.0	66.0	33.0	63.5	35.1	60.8	37.1	57.8	39.1	55.0	42.7	37.9	44.7	34.0
8.0	28.7	69.2	30.7	64.6	32.8	62.4	34.8	60.0	36.9	57.5	38.9	55.0	40.9	49.3	43.0	43.5
9.0	28.4	67.2	30.5	64.0	32.5	61.4	34.6	59.0	36.7	56.9	38.7	54.6	40.8	50.5	42.8	44.9
10.0	28.0	65.9	30.1	63.8	32.2	60.5	34.3	57.5	36.4	54.7	38.5	52.0	40.5	48.3	42.6	43.8
12.0	27.2	54.7	29.4	53.7	31.6	52.0	33.7	49.9	35.8	47.3	37.9	45.0	40.0	42.6	42.1	39.8
14.0	26.3	46.0	28.5	45.7	30.7	44.8	32.9	43.3	35.1	41.3	37.2	39.5	39.3	37.7	41.5	35.5
16.0	25.1	39.4	27.5	39.3	29.7	38.4	32.0	37.3	34.2	36.1	36.4	34.9	38.6	33.3	40.7	31.4
18.0	23.7	33.9	26.2	34.0	28.6	33.3	30.9	32.6	33.2	31.8	35.5	31.0	37.7	29.7	39.9	28.2
20.0	22.1	28.8	24.7	29.3	27.2	28.8	29.7	28.3	32.1	27.8	34.4	27.3	36.7	26.5	38.9	25.5
22.0	21.7	20.7	23.0	25.6	25.7	25.2	28.2	24.9	30.7	24.5	33.2	24.2	35.5	23.6	37.8	22.8
24.0			20.9	22.3	23.8	22.1	26.6	22.0	29.2	21.9	31.7	21.7	34.2	21.2	36.6	20.5
26.0			18.4	19.5	21.7	19.7	24.6	19.8	27.5	19.8	30.1	19.8	32.7	19.3	35.2	18.5
28.0			15.2	16.5	19.0	17.2	22.4	17.6	25.4	17.7	28.3	17.8	31.0	17.5	33.7	16.8
30.0							21.2	13.2	24.6	13.0	27.7	12.8	29.1	15.8	31.9	15.4
32.0							17.7	11.9	21.7	11.8	25.3	11.7	26.9	14.1	29.9	13.9
34.0											22.3	11.1	24.4	12.8	27.7	12.7
36.0											18.7	10.1	21.4	11.5	25.0	11.5
38.0													17.0	10.5	21.9	10.1
40.0															19.6	8.4
42.0																
44.0																
46.0																
48.0																
50.0																
52.0																
54.0																

オールテレーンクレーン[油圧伸縮ジブ型]【200t吊】 (3/3)

作業半径 (m)	46.0		48.0		50.0		52.0		54.0		56.0		58.0		60.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.7																
3.0																
3.5																
4.0																
4.5																
5.0																
5.5																
6.0																
7.0	46.7	31.0	48.7	27.9												
8.0	45.0	38.5	47.0	34.9	49.1	31.5	52.6	22.8								
9.0	44.9	39.8	46.9	35.9	48.9	32.1	52.5	22.8	54.5	20.8	56.5	19.0				
10.0	44.6	39.4	46.7	35.7	48.7	32.1	52.3	22.8	54.3	20.8	56.4	19.0	58.4	17.2	60.4	15.5
12.0	44.2	36.9	46.2	34.3	48.3	31.9	51.9	22.7	53.9	20.8	56.0	19.0	58.0	17.2	60.0	15.5
14.0	43.6	33.5	45.7	32.1	47.7	30.9	51.3	21.9	53.4	20.4	55.5	18.8	57.5	17.2	59.6	15.5
16.0	42.9	29.7	45.0	28.5	47.1	27.4	50.7	20.5	52.8	19.2	54.9	18.0	57.0	16.8	59.1	15.5
18.0	42.1	26.8	44.2	25.8	46.4	24.8	50.0	19.1	52.2	18.1	54.3	17.1	56.4	16.3	58.5	15.5
20.0	41.2	24.4	43.4	23.4	45.6	22.4	49.3	17.8	51.4	16.9	53.6	16.1	55.7	15.4	57.8	14.7
22.0	40.1	22.0	42.4	21.2	44.6	20.3	48.4	16.7	50.6	15.9	52.8	15.2	54.9	14.5	57.1	13.8
24.0	39.0	20.0	41.3	19.3	43.6	18.5	47.4	15.7	49.6	14.9	51.9	14.2	54.1	13.5	56.2	12.8
26.0	37.7	17.9	40.1	17.3	42.5	16.7	46.3	14.6	48.6	14.1	50.9	13.4	53.1	12.7	55.3	11.8
28.0	36.2	16.2	38.7	15.6	41.2	15.2	45.1	13.6	47.4	13.2	49.8	12.7	52.0	11.9	54.3	10.9
30.0	34.6	14.9	37.2	14.4	39.7	14.0	43.7	12.1	46.2	12.0	48.5	11.9	50.9	11.2	53.2	10.1
32.0	32.8	13.6	35.5	13.2	38.2	12.8	42.2	10.9	44.8	11.0	47.2	11.1	49.6	10.5	52.0	9.4
34.0	30.7	12.6	33.6	12.2	36.4	11.8	40.6	10.1	43.2	10.1	45.8	10.1	48.2	9.6	50.7	8.8
36.0	28.4	11.4	31.5	11.1	34.4	10.9	38.8	9.4	41.5	9.3	44.2	9.2	46.7	8.8	49.3	8.2
38.0	25.7	10.2	29.1	10.1	32.2	10.1	36.8	8.7	39.6	8.5	42.4	8.3	45.1	8.0	47.7	7.6
40.0	22.4	9.3	26.2	9.1	29.7	9.3	34.5	7.9	37.5	7.7	40.4	7.5	43.3	7.3	46.0	7.1
42.0	17.5	8.8	23.0	8.3	26.9	8.5	31.9	7.2	35.2	7.0	38.3	6.8	41.3	6.7	44.1	6.6
44.0			20.4	6.6	24.5	7.1	29.0	6.6	32.6	6.4	35.9	6.2	39.0	6.1	42.0	6.1
46.0					19.5	6.6			29.5	5.8	33.2	5.6	36.6	5.5	39.8	5.6
48.0									26.0	5.3	30.1	5.1	33.8	5.0	37.3	5.0
50.0													30.6	4.5	34.4	4.5
52.0													26.9	4.0	31.2	4.1
54.0													22.4	3.7	27.4	3.7

オールテレンクレーン[油圧伸縮ジブ型]【220t吊】 (1/3)

ブーム長さ (m) 作業半径 (m)	13.2		14.0		16.0		18.0		20.0		22.0		24.0		26.0		28.0		
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	
2.5	12.5	220.0																	
3.0	12.4	180.0	13.3	181.5	15.3	147.2	17.3	121.5	19.4	120.6	21.3	107.3	23.3	100.3					
3.5	12.2	169.5	13.0	160.8	15.0	139.4	17.1	121.9	19.3	120.6	21.3	119.0	23.3	114.6	25.3	110.3	27.3	87.7	
4.0	12.1	160.0	12.8	149.8	14.9	133.6	17.0	120.2	19.0	118.7	21.0	117.1	23.3	111.4	25.3	106.3	27.2	87.7	
4.5	11.9	150.5	12.7	138.9	14.8	126.6	16.8	116.5	18.9	115.1	20.9	113.5	23.2	107.3	25.2	102.6	27.2	98.2	
5.0	11.7	135.5	12.5	128.7	14.6	120.9	16.7	114.3	18.8	113.0	20.8	111.4	22.9	106.1	24.9	100.1	27.0	94.5	
5.5	11.5	124.0	12.3	120.1	14.4	115.1	16.5	110.7	18.6	109.8	20.7	108.5	22.8	103.7	24.8	98.2	26.9	92.4	
6.0	11.3	112.5	12.1	111.4	14.2	109.2	16.4	107.1	18.5	106.6	20.6	105.6	22.7	101.3	24.7	96.2	26.8	90.2	
7.0	10.7	96.2	11.5	97.6	13.8	96.5	16.0	95.5	18.1	94.9	20.3	94.3	22.4	93.0	24.5	90.7	26.5	85.4	
8.0	10.0	83.5	10.9	86.1	13.3	85.4	15.5	84.7	17.7	84.3	19.9	83.9	22.0	83.0	24.2	81.7	26.2	79.5	
9.0	9.2	73.3	10.1	76.3	12.6	76.3	15.0	76.1	17.3	75.6	19.5	75.2	21.7	74.6	23.8	73.9	25.9	73.1	
10.0	8.1	65.2	9.2	67.4	11.9	68.1	14.4	68.5	16.7	68.2	19.0	67.9	21.2	67.6	23.4	67.3	25.6	66.8	
12.0					11.4	69.2	13.0	54.6	15.4	56.0	17.9	55.9	20.2	56.0	22.5	56.2	24.7	56.1	
14.0							10.9	44.8	13.7	46.5	16.4	47.0	18.9	47.1	21.3	47.2	23.7	47.3	
16.0									10.7	41.9	14.5	40.1	17.3	40.2	19.9	40.4	22.4	40.5	
18.0											12.2	33.2	15.3	34.1	18.2	34.5	20.9	34.7	
20.0													12.0	30.0	15.9	28.6	19.0	29.7	
22.0															13.4	24.2	16.9	26.0	
24.0																	14.1	19.4	
26.0																			
28.0																			
30.0																			
32.0																			
34.0																			
36.0																			
38.0																			
40.0																			
42.0																			
44.0																			
46.0																			
48.0																			
50.0																			
52.0																			
54.0																			
56.0																			

オールテレーンクレーン[油圧伸縮ジブ型]【220t吊】（2／3）

作業半径 (m)	30.0		32.0		34.0		36.0		38.0		40.0		42.0		44.0		46.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5																		
3.0																		
3.5	29.3	82.0																
4.0	29.3	82.0																
4.5	29.2	93.7	31.2	76.1	33.2	70.3	35.2	63.0	37.2	55.6								
5.0	29.0	88.9	31.1	76.0	33.2	70.3												
5.5	28.9	86.6	31.1	78.7	33.1	73.9	35.1	63.0	37.1	55.6								
6.0	28.8	84.2	31.0	81.4	33.0	77.6	35.0	63.0	37.0	55.6	39.1	50.1	41.1	44.8				
7.0	28.6	80.2	30.6	75.3	32.7	69.5	34.7	62.2	36.8	54.1	38.7	40.3	40.9	44.8	43.0	40.3	45.0	36.0
8.0	28.3	77.3	30.4	71.7	32.5	64.7	34.5	59.0	36.6	52.7	38.6	45.8	40.6	42.4	42.6	38.6	44.6	38.6
9.0	28.0	72.4	30.1	67.6	32.2	61.0	34.3	55.8	36.3	50.1	38.4	44.1	40.4	41.4	42.5	41.4	44.5	40.3
10.0	27.7	66.3	29.8	63.9	31.9	59.4	34.0	53.6	36.1	47.2	38.1	41.6	40.2	39.6	42.3	40.2	44.3	39.7
12.0	26.9	55.9	29.1	55.9	31.2	53.6	33.4	48.0	35.5	41.8	37.6	37.2	39.7	36.1	41.7	37.5	43.8	37.6
14.0	25.9	47.4	28.2	47.4	30.4	47.3	32.6	45.5	34.7	43.5	36.9	41.6	39.0	39.7	41.1	37.6	43.2	35.2
16.0	24.8	40.6	27.1	40.6	29.4	40.6	31.7	39.9	33.9	39.0	36.1	37.1	38.2	35.3	40.4	33.9	42.5	32.5
18.0	23.4	34.8	25.9	34.9	28.3	35.0	30.6	34.9	32.9	34.8	35.1	33.2	37.4	31.4	39.6	30.3	41.7	29.3
20.0	21.8	29.9	24.4	30.4	26.9	30.8	29.3	30.7	31.7	30.6	34.1	29.5	36.3	28.1	38.6	27.2	40.8	26.5
22.0	20.0	26.4	22.7	26.8	25.3	26.9	27.9	26.8	30.4	26.8	32.8	26.1	35.2	25.2	37.5	24.5	39.8	23.9
24.0	17.6	23.4	20.6	23.9	23.5	24.0	26.2	23.8	28.9	23.6	31.4	23.1	33.9	22.5	36.3	22.1	38.7	21.6
26.0	14.5	21.0	18.1	21.2	21.3	21.3	24.3	21.1	27.1	20.9	29.8	20.5	32.4	20.2	34.9	19.9	37.4	19.6
28.0			14.8	17.5	18.6	19.2	22.0	18.9	25.1	18.6	28.0	18.4	30.7	18.2	33.4	18.0	35.9	17.9
30.0							19.5	17.0	22.9	16.6	26.0	16.5	28.8	16.7	31.6	16.6	34.3	16.3
32.0							16.2	14.8	20.2	15.5	23.6	15.1	26.6	15.3	29.6	15.1	32.5	14.7
34.0											20.7	13.9	24.1	14.0	27.3	13.7	30.4	13.4
36.0											17.1	12.5	20.9	12.8	24.7	12.5	28.1	12.1
38.0													16.5	11.0	21.6	11.4	25.3	11.1
40.0															18.0	10.8	22.0	10.6
42.0																	17.5	8.9
44.0																		
46.0																		
48.0																		
50.0																		
52.0																		
54.0																		
56.0																		

オールテレーンクレーン[油圧伸縮ジブ型]【220t吊】(3/3)

作業半径 (m)	48.0		50.0		52.0		54.0		56.0		58.0		60.0		62.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5																
3.0																
3.5																
4.0																
4.5																
5.0																
5.5																
6.0																
7.0																
8.0	46.6	34.7	48.7	31.2												
9.0	46.4	34.7	48.5	31.2	50.8	27.1	52.8	24.5	54.6	22.0	56.7	20.0	58.4	19.5	60.3	16.3
10.0	46.4	36.2	48.4	32.7	50.6	29.3	52.6	24.5	54.3	23.8	56.3	21.6	58.4	19.5	59.9	16.3
12.0	45.9	34.6	48.0	31.7	50.2	28.5	52.2	26.1	53.8	23.1	55.9	21.2	57.9	19.2	59.9	16.3
14.0	45.3	32.7	47.4	30.2	49.7	27.2	51.7	25.2	53.8	22.2	55.3	20.5	57.4	18.8	59.4	16.3
16.0	44.7	30.5	46.8	28.4	49.1	25.3	51.2	23.8	53.2	22.2	55.3	20.5	57.4	18.8	59.4	16.3
18.0	43.9	28.0	46.1	26.7	48.4	23.5	50.5	22.1	52.6	20.8	54.7	19.6	56.8	18.2	58.9	16.2
20.0	43.0	25.6	45.2	24.6	47.6	21.9	49.8	20.7	51.9	19.5	54.0	18.4	56.1	17.2	58.2	15.8
22.0	42.1	23.2	44.3	22.6	46.7	20.4	48.9	19.3	51.1	18.3	53.2	17.2	55.4	16.2	57.5	15.3
24.0	41.0	21.2	43.3	20.7	45.7	18.8	48.0	18.0	50.2	17.1	52.4	16.2	54.6	15.3	56.7	14.4
26.0	39.8	19.3	42.1	18.9	44.6	17.5	46.9	16.8	49.2	16.1	51.4	15.2	53.7	14.4	55.8	13.7
28.0	38.4	17.7	40.8	17.3	43.4	16.2	45.8	15.7	48.1	15.0	50.4	14.3	52.6	13.6	54.8	12.9
30.0	36.9	16.0	39.4	15.8	42.1	15.0	44.5	14.5	46.9	14.0	49.2	13.4	51.5	12.8	53.8	12.2
32.0	35.2	14.5	37.8	14.4	40.6	13.9	43.1	13.5	45.5	13.1	48.0	12.6	50.3	12.1	52.6	11.5
34.0	33.3	13.2	36.1	13.2	38.9	12.9	41.5	12.6	44.1	12.3	46.6	11.8	49.0	11.3	51.4	10.9
36.0	31.2	12.1	34.1	12.2	37.1	11.9	39.8	11.7	42.5	11.5	45.1	11.1	47.6	10.7	50.0	10.2
38.0	28.7	11.1	31.9	11.2	35.1	11.0	38.0	10.7	40.7	10.5	43.4	10.3	46.0	10.0	48.5	9.6
40.0	25.9	10.3	29.4	10.3	32.8	10.2	35.9	9.8	38.8	9.7	41.6	9.6	44.3	9.4	46.9	9.0
42.0	22.7	9.6	26.5	9.5	30.3	9.4	33.5	9.1	36.6	8.9	39.6	8.9	42.4	8.8	45.1	8.4
44.0	18.8	8.0	23.2	8.4	27.3	8.6	30.9	8.3	34.2	8.1	37.4	8.2	40.4	8.2	43.2	7.8
46.0			18.3	7.2	23.8	8.0	27.9	7.7	31.5	7.5	34.9	7.5	38.1	7.5	41.1	7.3
48.0					19.6	6.9	24.3	6.9	28.4	6.8	32.1	6.9	35.6	6.9	38.8	6.8
50.0																
52.0																
54.0																
56.0																

オールテレーンクレーン[油圧伸縮ジブ型]【250t吊】(1/3)

作業半径 (m)	13.1		14.0		16.0		18.0		20.0		22.0		24.0		26.0		28.0	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
3.0	12.4	250.0	13.3	223.0	15.3	162.9	17.4	120.8	19.4	120.5								
3.5	12.2	142.2	13.2	137.9	15.2	128.4	17.3	121.6	19.3	121.2	21.3	120.9						
4.0	12.1	140.3	13.0	136.6	15.1	128.4	17.2	122.6	19.2	122.0	21.2	121.3	23.3	119.7	25.3	118.0		
4.5	11.9	138.1	12.9	135.1	15.0	128.5	17.0	123.6	19.1	123.0	21.1	121.1	23.2	119.1	25.2	118.8		
5.0	11.7	134.7	12.7	131.7	14.8	125.0	16.9	120.2	19.0	119.9	21.0	119.0	23.1	117.7	25.1	117.0	27.2	113.7
5.5	11.5	127.3	12.5	124.4	14.6	118.0	16.7	113.4	18.8	113.3	20.9	112.5	23.0	111.2	25.0	110.6	27.1	108.2
6.0	11.3	119.8	12.3	117.1	14.4	111.0	16.6	106.7	18.7	106.6	20.8	106.0	22.8	104.7	24.9	104.1	27.0	102.8
7.0	10.7	106.5	11.7	104.3	14.0	99.4	16.2	95.9	18.3	96.0	20.5	95.1	22.6	94.8	24.7	96.0	26.7	94.4
8.0	10.0	95.2	11.1	93.4	13.5	89.3	15.7	86.5	17.9	86.6	20.1	85.7	22.2	85.6	24.3	87.1	26.4	85.7
9.0	9.1	84.9	10.3	83.6	12.8	80.7	15.2	78.7	17.5	78.7	19.7	77.8	21.9	77.8	24.0	79.4	26.1	78.4
10.0	8.1	74.5	9.4	74.0	12.1	72.8	14.6	72.0	16.9	72.1	19.2	71.1	21.4	71.0	23.6	72.7	25.8	72.2
12.0							13.0	61.0	15.6	61.3	18.1	60.6	20.4	60.4	22.7	61.7	24.9	61.5
14.0							10.9	52.7	13.9	52.8	16.6	52.0	19.1	51.7	21.5	52.9	23.9	52.8
16.0											14.7	44.7	17.5	44.4	20.1	45.8	22.6	45.6
18.0											12.3	38.9	15.5	38.5	18.4	39.9	21.1	39.7
20.0											8.8	28.1	12.9	32.8	16.2	35.1	19.2	34.9
22.0															13.5	31.0	16.9	30.8
24.0															9.6	23.2	14.0	25.1
26.0																		
28.0																		
30.0																		
32.0																		
34.0																		
36.0																		
38.0																		
40.0																		
42.0																		
44.0																		
46.0																		
48.0																		
50.0																		
52.0																		
54.0																		
56.0																		

オールテレーンクレーン【油圧伸縮ジブ型】【250t吊】（2／3）

作業半径 (m)	30.0		32.0		34.0		36.0		38.0		40.0		42.0		44.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0																
3.5																
4.0																
4.5																
5.0	29.2	110.5														
5.5	29.1	105.9														
6.0	29.0	101.4	31.0	97.6	33.1	93.3										
7.0	28.8	92.7	30.8	90.6	32.9	88.5	34.9	81.9	37.0	73.5						
8.0	28.5	84.3	30.6	82.7	32.7	81.0	34.7	75.9	36.8	69.4	38.8	63.6	40.8	58.7		
9.0	28.2	77.5	30.3	76.1	32.4	74.6	34.5	70.4	36.5	64.9	38.6	60.1	40.6	56.2	42.7	52.3
10.0	27.9	71.7	30.0	70.4	32.1	69.0	34.2	65.2	36.3	60.3	38.3	56.3	40.4	53.3	42.5	50.2
12.0	27.1	61.3	29.3	60.7	31.4	60.0	33.6	57.0	35.7	53.1	37.8	50.1	39.9	48.0	41.9	45.8
14.0	26.1	52.6	28.4	52.4	30.6	52.1	32.8	50.0	34.9	47.1	37.1	44.7	39.2	42.8	41.3	40.9
16.0	25.0	45.4	27.3	45.1	29.6	44.8	31.9	43.6	34.1	42.0	36.3	40.3	38.4	38.4	40.6	36.8
18.0	23.6	39.5	26.1	39.2	28.5	38.9	30.8	38.4	33.1	37.7	35.3	36.5	37.6	34.6	39.8	33.1
20.0	22.0	34.7	24.6	34.4	27.1	34.1	29.5	34.0	31.9	34.1	34.3	33.3	36.5	31.6	38.8	30.2
22.0	20.0	30.6	22.8	30.3	25.5	30.0	28.1	30.1	30.6	30.4	33.0	29.9	35.4	28.8	37.7	27.7
24.0	17.6	26.9	20.8	27.4	23.7	27.5	26.4	27.4	29.1	27.2	31.6	26.9	34.1	26.4	36.5	25.8
26.0			18.3	24.6	21.5	24.9	24.5	24.8	27.3	24.5	30.0	24.3	32.6	24.2	35.1	23.8
28.0			15.1	21.4	18.9	22.3	22.2	22.4	25.3	22.1	28.2	21.9	30.9	21.8	33.6	21.5
30.0							19.5	20.4	22.9	20.1	26.1	19.9	29.0	19.8	31.8	19.6
32.0							16.1	17.7	20.1	18.0	23.6	18.3	26.8	18.3	29.8	18.3
34.0											20.7	16.9	24.3	16.9	27.5	16.9
36.0											17.0	15.4	21.2	15.5	24.9	15.5
38.0															21.8	14.3
40.0															17.9	13.0
42.0																
44.0																
46.0																
48.0																
50.0																
52.0																
54.0																
56.0																

オールテレーンクレーン[油圧伸縮ジブ型]【250t吊】(3/3)

作業半径 (m)	46.0		48.0		50.0		52.0		54.0		56.0		58.0		60.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0																
3.5																
4.0																
4.5																
5.0																
5.5																
6.0																
7.0																
8.0																
9.0	44.7	48.5														
10.0	44.5	46.9	46.6	43.5	48.6	39.7										
12.0	44.0	43.4	46.1	40.8	48.1	37.6	50.2	34.4	52.3	29.8	54.3	28.6	56.4	26.5	58.4	24.5
14.0	43.4	39.3	45.5	37.5	47.6	35.0	49.7	32.4	51.8	28.1	53.8	27.3	55.9	25.5	58.0	23.6
16.0	42.7	35.5	44.9	34.1	47.0	32.2	49.1	30.2	51.2	26.1	53.3	25.7	55.4	24.2	57.4	22.5
18.0	41.9	32.1	44.1	31.0	46.3	29.7	48.4	28.3	50.5	24.4	52.6	24.2	54.7	22.9	56.8	21.4
20.0	41.0	29.2	43.2	28.2	45.4	27.4	47.6	26.4	49.8	22.7	51.9	22.8	54.1	21.6	56.2	20.3
22.0	40.0	26.7	42.3	25.8	44.5	25.2	46.7	24.4	48.9	21.1	51.1	21.5	53.3	20.4	55.4	19.2
24.0	38.9	24.8	41.2	23.9	43.5	23.3	45.7	22.6	48.0	19.6	50.2	20.3	52.4	19.2	54.6	18.1
26.0	37.6	23.0	40.0	22.2	42.3	21.6	44.6	20.9	46.9	18.3	49.2	19.1	51.5	18.1	53.7	17.0
28.0	36.1	21.1	38.6	20.6	41.0	20.0	43.4	19.4	45.8	17.1	48.1	18.0	50.4	17.0	52.7	16.1
30.0	34.5	19.4	37.1	19.1	39.6	18.6	42.1	18.0	44.5	16.1	46.9	16.9	49.2	16.1	51.6	15.2
32.0	32.7	18.2	35.4	17.9	38.0	17.3	40.6	16.7	43.1	15.1	45.6	15.8	48.0	15.1	50.4	14.3
34.0	30.6	16.8	33.5	16.6	36.3	16.2	39.0	15.7	41.6	14.2	44.1	14.9	46.6	14.3	49.0	13.5
36.0	28.2	15.4	31.4	15.3	34.3	15.0	37.1	14.7	39.9	13.3	42.5	13.9	45.1	13.5	47.6	12.8
38.0	25.5	14.1	28.9	14.0	32.1	13.8	35.1	13.6	38.0	12.5	40.7	13.0	43.4	12.7	46.0	12.1
40.0	22.3	13.1	26.1	13.1	29.6	13.0	32.8	12.9	35.9	11.9	38.8	12.3	41.6	12.0	44.3	11.5
42.0			22.8	12.2	26.7	12.0	30.3	11.9	33.6	11.1	36.7	11.4	39.6	11.3	42.5	10.9
44.0			18.8	11.1	23.4	11.0	27.3	11.0	30.9	10.5	34.3	10.6	37.4	10.6	40.4	10.3
46.0			13.3	5.7	19.2	8.0	23.9	10.2	27.9	9.9	31.5	9.7	34.9	9.8	38.1	9.7
48.0							19.6	9.4	24.3	9.4	28.5	9.1	32.2	9.1	35.6	9.0
50.0							13.9	6.0	20.0	8.0	24.8	8.4	29.0	8.4	32.8	8.3
52.0											20.4	7.6	25.3	7.8	29.5	7.7
54.0													20.8	6.4	25.8	7.1
56.0															21.2	6.5

オールテレーンクレーン[油圧伸縮ジブ型]【300t吊】（1／3）

作業半径 (m)	13.6		14.0		16.0		18.0		20.0		22.0		24.0		26.0		28.0	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
2.5	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
3.0	13.0	300.0																
3.5	12.9	230.0	13.3	220.3	15.7	207.2	17.7	165.4	20.1	171.8	22.1	167.0	24.1	163.8				
4.0	12.8	210.0	13.2	202.1	16.2	181.4	18.2	149.8	19.6	144.6	21.7	143.5	24.1	163.8				
4.5	12.7	190.0	13.1	183.9	16.0	169.1	18.1	144.8	20.1	128.7	22.2	127.7	24.4	128.0	25.8	144.8	28.0	148.9
5.0	12.5	175.0	12.9	170.2	15.9	159.5	18.0	140.8	20.0	128.5	22.1	127.6	24.3	128.0	25.8	144.8	28.0	148.9
5.5	12.3	162.0	12.7	158.3	15.8	150.8	17.8	136.9	19.9	128.0	22.0	127.3	24.0	125.6	26.1	116.7	28.1	102.2
6.0	12.1	149.5	12.5	146.8	15.6	144.0	17.7	133.3	19.8	126.3	21.8	125.8	23.9	124.3	26.0	115.8	28.0	101.8
6.5	11.9	136.9	12.3	135.2	15.4	137.3	17.5	129.7	19.6	124.6	21.7	124.3	23.8	123.1	25.9	114.9	27.9	101.3
7.0	11.3	119.4	11.8	118.1	14.9	123.5	17.1	120.7	19.3	119.1	21.4	118.9	23.5	118.0	25.6	110.5	27.7	98.2
8.0	10.7	105.4	11.2	104.3	14.4	110.4	16.7	109.0	18.9	108.3	21.0	107.9	23.2	107.0	25.3	101.2	27.4	91.7
9.0	9.9	94.1	10.4	93.2	13.8	98.7	16.1	97.5	18.4	96.9	20.6	96.4	22.8	95.8	24.9	91.8	27.1	85.0
10.0	8.9	84.8	9.5	84.0	13.0	88.9	15.5	87.8	17.9	87.3	20.1	86.9	22.4	86.4	24.6	83.9	26.7	79.2
12.0					11.3	73.5	14.1	73.7	16.6	71.4	19.0	71.1	21.3	71.0	23.6	70.8	25.9	69.4
14.0									14.9	57.8	17.5	59.1	20.0	59.1	22.5	59.4	24.8	58.8
16.0									12.9	52.2	15.8	51.9	18.4	50.1	21.0	50.5	23.5	50.2
18.0											12.8	41.2	16.4	42.6	19.3	43.3	22.0	43.1
20.0													14.2	38.3	17.3	38.6	20.3	38.2
22.0															14.6	31.8	18.0	32.3
24.0																	14.1	21.8
26.0																		
28.0																		
30.0																		
32.0																		
34.0																		
36.0																		
38.0																		
40.0																		
42.0																		
44.0																		
46.0																		
48.0																		
50.0																		
52.0																		
54.0																		

オールテレーンクレーン[油圧伸縮ジブ型]【300t吊】(2/3)

作業半径 (m)		30.0		32.0		34.0		36.0		38.0		40.0		42.0		44.0		46.0	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)		
2.5																			
3.0																			
3.5																			
4.0		30.0	139.9																
4.5		30.0	139.9																
5.0		30.1	91.4	32.4	82.1	33.9	127.4												
5.5		30.0	91.3	32.3	81.8	33.8	117.4												
6.0		29.9	91.2	32.1	81.6	33.6	107.5	35.6	97.8	37.7	81.7	39.9	86.3						
7.0		29.7	89.0	31.8	78.1	33.8	74.1	35.9	70.4	37.9	65.7	39.9	63.5	41.7	80.2	43.8	75.1		
8.0		29.5	85.1	31.5	76.7	33.6	72.9	35.7	69.4	37.7	65.0	39.7	63.3	41.8	59.2	43.8	54.0	45.9	49.2
9.0		29.2	80.9	31.3	75.1	33.3	71.6	35.4	68.5	37.5	64.0	39.5	62.4	41.6	58.5	43.6	53.5	45.7	48.8
10.0		28.8	77.1	30.9	73.5	33.0	70.5	35.1	67.7	37.2	63.0	39.3	61.3	41.3	57.6	43.4	52.7	45.5	48.2
12.0		28.0	70.3	30.2	70.2	32.4	67.9	34.5	65.6	36.6	61.2	38.7	59.6	40.8	56.1	42.9	51.4	45.0	47.1
14.0		27.1	60.2	29.3	61.2	31.5	59.6	33.7	57.7	35.9	53.7	38.0	52.2	40.1	50.9	42.3	48.7	44.4	45.9
16.0		25.9	51.6	28.3	52.6	30.6	51.3	32.8	50.0	35.0	46.9	37.2	46.1	39.4	45.3	41.5	43.7	43.7	41.9
18.0		24.6	44.4	27.0	45.2	29.4	44.4	31.7	43.5	34.0	41.2	36.3	40.9	38.5	40.5	40.7	39.1	42.9	37.8
20.0		23.1	39.2	25.5	39.3	28.0	38.8	30.5	38.3	32.9	36.4	35.2	36.5	37.5	36.3	39.7	35.3	42.0	34.1
22.0		21.1	33.8	23.8	34.5	26.5	34.2	29.0	33.9	31.5	32.5	34.0	32.7	36.3	32.5	38.7	31.7	41.0	30.7
24.0		17.7	28.1	21.7	30.3	24.6	30.2	27.4	30.2	30.0	29.0	32.6	29.5	35.0	29.4	37.4	28.6	39.8	27.7
26.0				19.2	26.6	22.5	26.8	25.5	27.0	28.3	26.1	30.9	26.7	33.5	26.6	36.0	26.0	38.5	25.2
28.0				16.0	23.4	19.8	23.7	23.2	24.0	26.2	23.4	29.1	24.0	31.9	24.0	34.5	23.6	37.0	22.9
30.0								20.2	20.6	23.5	18.1	27.2	21.7	29.9	21.6	32.7	21.4	35.4	20.9
32.0								16.8	18.7	20.6	16.5	24.7	19.4	27.8	19.5	30.8	19.5	33.6	19.2
34.0												21.9	17.7	25.2	17.6	28.5	17.8	31.5	17.6
36.0												18.3	15.9	22.2	15.9	25.9	16.0	29.2	15.9
38.0														17.8	13.8	22.1	14.0	26.5	14.5
40.0																		23.3	13.0
42.0																		19.4	10.7
44.0																			
46.0																			
48.0																			
50.0																			
52.0																			
54.0																			

オールテレレンクレーン[油圧伸縮ジブ型]【300t吊】 (3/3)

作業半径 (m)	48.0		50.0		52.0		54.0		56.0		58.0		60.0		62.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5																
3.0																
3.5																
4.0																
4.5																
5.0																
5.5																
6.0																
7.0																
8.0	47.9	44.8														
9.0	47.7	44.2	49.7	39.8	52.0	38.6	54.0	36.0								
10.0	47.5	43.9	49.5	39.7	51.7	38.5	53.8	35.9	55.2	40.4	57.4	39.3	59.5	34.5		
12.0	47.0	43.0	49.1	39.0	51.3	37.9	53.4	35.5	54.8	39.9	56.9	35.7	58.9	31.2	60.5	21.0
14.0	46.5	41.9	48.6	38.1	50.8	36.9	52.9	34.6	54.4	36.7	56.4	34.0	58.5	31.0	60.1	20.9
16.0	45.8	39.5	47.9	37.2	50.2	35.7	52.3	33.1	53.8	33.7	55.9	31.2	58.0	28.4	59.6	20.7
18.0	45.0	36.2	47.2	34.7	49.5	32.4	51.6	29.7	53.2	31.0	55.3	28.8	57.4	26.3	59.0	20.3
20.0	44.2	32.5	46.4	31.0	48.7	29.1	50.9	26.7	52.5	28.6	54.6	26.5	56.7	24.1	58.4	18.9
22.0	43.2	29.3	45.5	28.0	47.8	26.2	50.0	24.1	51.6	26.5	53.8	24.7	56.0	22.6	57.7	17.7
24.0	42.1	26.4	44.4	25.3	46.8	23.7	49.1	21.9	50.7	24.6	52.9	23.0	55.1	21.2	56.9	16.5
26.0	40.9	24.0	43.3	22.9	45.7	21.5	48.0	19.9	49.7	22.8	52.0	21.5	54.2	20.0	56.0	15.4
28.0	39.5	21.8	42.0	20.8	44.5	19.6	46.9	18.1	48.6	21.3	50.9	20.2	53.2	19.0	55.0	14.3
30.0	38.0	19.9	40.6	19.0	43.2	17.8	45.6	16.5	47.4	19.3	49.8	18.8	52.1	18.1	53.9	13.4
32.0	36.3	18.4	39.0	17.6	41.7	16.4	44.2	15.1	46.1	17.6	48.5	17.3	50.9	16.9	52.8	12.6
34.0	34.4	16.8	37.2	16.2	40.1	15.1	42.7	13.9	44.6	16.1	47.1	15.9	49.6	15.6	51.5	11.7
36.0	32.3	15.4	35.3	14.9	38.2	13.9	41.0	12.8	43.0	14.8	45.6	14.5	48.1	14.2	50.2	10.9
38.0	29.9	14.1	33.0	13.7	36.2	12.9	39.1	11.8	41.3	13.5	44.0	13.3	46.6	13.0	48.7	10.3
40.0	27.1	12.9	30.6	12.6	33.9	11.9	37.0	10.9	39.3	12.5	42.1	12.2	44.9	11.9	47.1	9.7
42.0	23.8	11.3	27.7	11.7	31.4	11.1	34.7	10.1	37.2	11.5	40.1	11.3	43.0	11.0	45.3	9.2
44.0	18.9	6.7	24.3	10.6	28.4	10.3	32.0	9.3	34.8	10.7	37.9	10.4	40.9	10.1	43.4	8.7
46.0			20.2	9.6	25.0	9.4	29.0	8.6	32.1	9.9	35.5	9.6	38.7	9.3	41.3	8.3
48.0					20.1	10.0	24.9	9.5	29.0	9.1	32.7	8.9	36.1	8.7	38.9	7.9
50.0									25.5	8.3	29.5	8.2	33.3	7.9	36.3	7.5
52.0									21.1	7.6	25.8	7.6	30.1	7.3	33.4	7.1
54.0											20.9	6.4	26.3	6.6	30.1	6.7

オールテレーンクレーン[油圧伸縮ジブ型]【360t吊】 (1/3)

作業半径 (m)	13.7		14.0		16.0		18.0		20.0		22.0		24.0		26.0		28.0	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
2.8	14.9	360.0																
3.0	14.9	200.0	15.0	256.4	17.1	222.0	19.1	187.6										
3.5	14.7	192.0	14.6	252.8	16.0	209.6	18.1	177.1	19.4	169.1								
4.0	14.6	184.0	14.8	196.3	16.4	186.2	18.5	171.5	20.5	165.2	22.6	163.5	24.5	166.6	27.2	163.0		
4.5	14.4	173.0	14.3	194.2	15.8	182.2	17.8	169.4	19.9	161.8	21.9	159.0	23.3	167.0	26.8	153.8		
5.0	14.3	162.0	14.4	165.6	16.1	163.0	18.2	156.7	20.3	153.4	22.3	151.3	24.4	148.4	26.4	144.6	28.4	143.8
5.5	14.0	152.3	14.2	154.7	15.9	152.9	18.1	147.9	20.1	145.6	22.2	144.4	24.3	141.9	26.3	138.4	28.3	135.7
6.0	13.8	142.5	14.0	143.8	15.8	142.8	17.9	139.1	20.0	137.8	22.1	137.4	24.2	135.4	26.2	132.3	28.3	127.6
7.0	13.3	127.0	13.5	128.3	14.7	129.3	16.9	116.1	19.0	103.7	21.2	98.3	23.3	93.2	26.0	120.8	28.0	117.9
8.0	12.6	113.5	12.8	115.2	14.2	116.6	16.4	105.1	18.6	94.4	20.8	89.2	22.9	84.4	25.0	81.6	27.1	81.2
9.0	11.8	101.5	12.1	103.7	13.5	105.9	15.9	95.9	18.2	86.4	20.4	81.5	22.6	76.9	24.7	74.3	26.8	74.0
10.0	10.9	89.7	11.1	92.5	12.8	96.4	15.3	88.0	17.6	79.6	19.9	75.0	22.1	70.5	24.3	68.1	26.5	67.9
12.0			8.3	67.0	10.5	78.9	13.4	73.4	16.3	68.4	18.7	64.3	21.1	60.1	23.4	57.9	25.6	58.1
14.0									15.6	65.2	17.3	56.0	19.8	52.3	22.2	50.3	24.6	50.5
16.0									13.3	50.6	15.4	49.2	18.2	46.2	20.8	44.3	23.3	44.5
18.0											12.4	39.8	16.2	40.5	19.1	39.3	21.8	39.5
20.0													14.6	39.3	16.9	34.4	19.9	35.1
22.0															13.6	26.6	17.6	31.2
24.0																	15.8	32.8
26.0																		
28.0																		
30.0																		
32.0																		
34.0																		
36.0																		
38.0																		
40.0																		
42.0																		
44.0																		
46.0																		
48.0																		
50.0																		
52.0																		
54.0																		
56.0																		
58.0																		

オールテレーンクレーン[油圧伸縮ジブ型]【360t吊】(2/3)

ブーム長さ (m) 作業半径 (m)		30.0		32.0		34.0		36.0		38.0		40.0		42.0		44.0		46.0	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.8																			
3.0																			
3.5																			
4.0																			
4.5																			
5.0	30.5	136.8																	
5.5	30.4	129.7																	
6.0	30.3	122.6		32.3	121.0	34.3	112.3	37.0	106.9										
7.0	30.1	114.1		32.1	108.7	34.2	100.5	36.2	99.1	38.2	92.9	40.3	86.6						
8.0	29.2	80.6		31.9	101.3	34.0	95.1	36.0	90.4	38.1	85.2	40.1	81.2	41.0	72.7	43.0	68.4	45.1	64.2
9.0	28.9	73.5		31.0	71.0	33.1	67.7	35.8	84.6	37.8	80.4	39.9	75.7	41.9	70.4	42.8	64.0	44.9	60.2
10.0	28.6	67.5		30.7	65.5	32.8	63.0	34.9	61.2	37.0	60.2	39.0	59.1	41.1	56.9	43.2	54.4	45.2	52.3
12.0	27.8	58.3		30.0	56.9	32.1	54.8	34.2	53.4	36.4	53.2	38.5	52.9	40.6	51.3	42.6	49.0	44.7	47.6
14.0	26.8	50.7		29.1	49.6	31.3	48.2	33.5	47.3	35.6	46.9	37.8	46.5	39.9	45.2	42.0	43.4	44.1	42.6
16.0	25.7	44.6		28.0	43.8	30.3	42.8	32.6	42.1	34.8	41.8	37.0	41.4	39.1	40.4	41.3	39.0	43.4	38.4
18.0	24.3	39.7		26.8	39.1	29.1	38.3	31.5	37.8	33.8	37.5	36.0	37.2	38.3	36.2	40.5	34.9	42.6	34.5
20.0	22.7	35.3		25.3	34.9	27.8	34.3	30.2	33.9	32.6	33.7	34.9	33.5	37.2	32.6	39.5	31.4	41.7	31.0
22.0	20.7	31.5		23.5	31.3	26.2	30.8	28.8	30.6	31.3	30.5	33.7	30.5	36.1	29.7	38.4	28.6	40.7	28.1
24.0	19.3	35.0		21.5	28.4	24.4	27.8	27.1	27.6	29.8	27.7	32.3	27.7	34.8	27.1	37.2	26.1	39.5	25.8
26.0				19.0	25.7	22.2	25.3	25.2	25.1	28.0	25.2	30.7	25.3	33.3	24.7	35.8	23.9	38.3	23.6
28.0				15.8	22.6	19.6	22.7	22.9	22.8	26.0	23.0	28.9	23.2	31.6	22.7	34.2	21.9	36.8	21.7
30.0				12.7	12.7	17.5	19.0	20.2	20.7	23.6	21.1	26.8	21.4	29.7	21.0	32.5	20.3	35.2	20.1
32.0								16.4	17.4	20.8	19.2	24.3	19.6	27.5	19.3	30.5	18.7	33.4	18.5
34.0										18.5	15.9	22.4	20.4	25.0	17.8	28.2	17.3	31.3	17.2
36.0												18.5	16.5	21.9	16.2	25.6	16.1	28.9	16.0
38.0														17.6	14.0	22.5	15.1	26.2	15.0
40.0																19.7	15.6	23.1	13.6
42.0																14.5	12.0	19.2	12.2
44.0																			
46.0																			
48.0																			
50.0																			
52.0																			
54.0																			
56.0																			
58.0																			

オールテレーンクレーン[油圧伸縮ジブ型]【360t吊】 (3/3)

作業半径 (m)	48.0		50.0		52.0		54.0		56.0		58.0		60.0		62.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.8																
3.0																
3.5																
4.0																
4.5																
5.0																
5.5																
6.0																
7.0																
8.0																
9.0	46.9	56.6	48.9	53.0												
10.0	47.1	48.9	48.7	45.2	50.7	43.5	52.8	41.8	54.9	41.6						
12.0	46.8	46.2	48.8	44.9	50.9	43.0	53.0	41.0	55.6	38.3	57.6	36.5	58.5	33.5		
14.0	46.2	41.8	48.3	41.0	50.4	40.1	52.5	39.0	55.1	35.9	57.2	33.6	59.3	31.3	61.9	30.1
16.0	45.6	37.9	47.7	37.3	49.8	36.7	51.9	35.8	54.6	33.4	56.7	31.3	58.8	29.1	61.4	28.1
18.0	44.8	34.3	47.0	34.0	49.1	33.6	51.2	32.9	54.0	30.8	56.1	29.0	58.2	27.1	60.8	26.2
20.0	43.9	31.1	46.1	31.1	48.3	30.9	50.5	30.5	53.2	28.7	55.4	27.0	57.5	25.3	60.2	24.6
22.0	43.0	28.2	45.2	28.4	47.4	28.4	49.6	28.2	52.4	26.8	54.6	25.3	56.7	23.6	59.5	23.0
24.0	41.9	25.9	44.2	26.1	46.4	26.2	48.7	26.2	51.5	24.9	53.7	23.6	55.9	22.2	58.7	21.8
26.0	40.7	23.8	43.0	24.0	45.3	24.1	47.6	24.1	50.5	23.2	52.8	22.0	55.0	20.8	57.8	20.8
28.0	39.3	21.9	41.7	22.2	44.1	22.3	46.5	22.3	49.4	21.6	51.7	20.6	54.0	19.6	56.8	19.8
30.0	37.8	20.2	40.3	20.4	42.8	20.5	45.2	20.6	48.2	20.1	50.6	19.4	52.9	18.7	55.8	19.1
32.0	36.1	18.8	38.7	19.0	41.3	19.1	43.8	19.1	46.9	18.7	49.3	18.1	51.7	17.6	54.6	18.3
34.0	34.2	17.5	37.0	17.6	39.6	17.7	42.3	17.7	45.4	17.4	47.9	17.0	50.4	16.7	53.4	17.5
36.0	32.1	16.2	35.0	16.5	37.8	16.5	40.6	16.6	43.8	16.4	46.4	16.0	48.9	15.8	52.0	16.8
38.0	29.6	15.2	32.8	15.4	35.8	15.4	38.7	15.4	42.1	15.4	44.7	15.1	47.4	14.9	50.5	16.0
40.0	26.8	14.2	30.3	14.4	33.5	14.5	36.6	14.5	40.1	14.4	42.9	14.1	45.6	14.1	48.9	15.1
42.0	23.5	13.3	27.4	13.6	31.0	13.6	34.2	13.5	38.0	13.5	40.9	13.3	43.8	13.2	47.1	14.2
44.0	19.6	12.6	24.7	13.1	28.0	12.7	31.6	12.7	35.6	12.6	38.7	12.5	41.7	12.4	45.2	13.1
46.0	14.8	9.0	20.9	11.3	24.6	11.9	28.6	12.0	32.9	12.0	36.3	11.7	39.4	11.6	43.1	12.0
48.0					19.7	11.2	25.0	11.2	29.8	11.3	33.5	11.1	36.9	10.9	40.8	11.1
50.0							21.7	9.6	26.6	10.3	30.3	10.4	34.1	10.2	38.2	10.3
52.0											26.1	9.5	30.9	9.6	35.3	9.6
54.0											21.6	8.2	27.1	8.9	32.0	8.8
56.0													21.9	7.8		
58.0													15.1	5.9		

オールテレレンクレーン[油圧伸縮ジブ型]【400t吊】(1/3)

作業半径 (m)	13.6		14.0		16.0		18.0		20.0		22.0		24.0		26.0		28.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5	13.3	400.0																
3.0	13.2	360.0	13.6	343.7	15.5	269.8	17.5	180.8	19.2	180.0	21.2	180.0						
3.5	13.1	300.0	13.5	289.0	15.4	238.3	17.4	179.4	19.1	180.0	21.1	180.0						
4.0	12.9	270.0	13.3	261.7	15.3	223.6	17.3	178.7	19.4	172.3	21.4	167.8						
4.5	12.7	245.0	13.2	238.9	15.1	211.8	17.2	178.1	19.2	172.3	21.3	167.8	23.5	158.6	25.5	156.4		
5.0	12.6	225.0	13.0	220.6	15.0	202.1	17.1	177.7	19.1	172.3	21.2	167.8	23.2	164.5	25.3	159.6	27.3	153.1
5.5	12.3	210.0	12.8	206.9	14.7	187.5	16.9	171.4	18.9	166.4	21.1	167.6	23.1	164.4	25.2	159.6	27.2	153.1
6.0	12.1	195.0	12.6	193.2	14.5	172.9	16.7	165.1	18.8	160.5	20.9	167.5	23.0	164.3	25.1	159.6	27.1	153.1
7.0	11.6	170.0	12.0	168.8	14.4	149.6	16.6	148.0	18.8	147.4	20.5	146.0	22.6	144.3	24.7	141.1	26.8	136.3
8.0	10.9	150.0	11.4	149.2	13.9	134.4	16.1	133.5	18.4	132.9	20.5	132.3	22.7	131.7	24.4	128.2	26.5	125.4
9.0	10.1	133.0	10.6	132.6	13.3	121.3	15.6	120.8	17.9	120.5	20.1	120.0	22.3	119.5	24.4	117.9	26.5	114.7
10.0	9.1	117.0	9.7	116.7	12.5	109.9	15.0	109.6	17.3	109.4	19.6	109.0	21.8	108.8	24.0	107.8	26.2	105.8
12.0	6.3	85.0	7.1	85.6	10.6	87.9	13.4	90.4	16.0	91.9	18.5	91.9	20.8	91.8	23.1	91.4	25.3	90.8
14.0							10.7	81.3	14.0	76.2	17.0	78.7	19.5	78.6	21.9	78.5	24.3	78.4
16.0									11.7	60.9	15.1	67.0	17.9	67.9	20.5	68.3	23.0	68.4
18.0									8.3	36.7	12.7	49.8	15.9	57.0	18.8	60.0	21.5	60.1
20.0													13.0	48.7	16.6	52.7	19.6	53.0
22.0															14.0	42.9	17.4	45.4
24.0																14.3	39.8	
26.0																		
28.0																		
30.0																		
32.0																		
34.0																		
36.0																		
38.0																		
40.0																		
42.0																		
44.0																		
46.0																		
48.0																		
50.0																		
52.0																		
54.0																		
56.0																		

オールテレーンクレーン[油圧伸縮ジブ型]【400t吊】(2/3)

作業半径 (m)	30.0		32.0		34.0		36.0		38.0		40.0		42.0		44.0		46.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5																		
3.0																		
3.5																		
4.0																		
4.5																		
5.0	29.3	143.6	31.0	134.4														
5.5	29.2	143.6	31.1	134.3														
6.0	29.2	143.6	31.2	134.2	33.4	125.3	35.4	116.5										
7.0	28.9	129.6	30.9	120.0	33.0	110.6	35.1	117.4	37.1	110.6	39.1	104.1	40.8	100.0				
8.0	28.6	121.2	30.7	115.6	32.7	109.7	34.8	103.1	36.8	96.3	38.9	89.7	41.0	97.2	43.0	90.0	45.1	83.1
9.0	28.6	111.2	30.7	104.6	32.8	97.0	34.5	98.5	36.6	93.1	38.7	88.0	40.7	82.7	42.8	77.1	44.8	71.6
10.0	28.3	103.4	30.4	97.7	32.5	91.0	34.6	85.0	36.7	81.1	38.8	77.4	40.8	73.9	42.9	70.1	44.9	66.2
12.0	27.5	90.3	29.7	86.1	31.8	80.3	34.0	75.0	36.1	71.4	38.2	68.0	40.3	65.3	42.4	62.5	44.4	59.6
14.0	26.6	78.5	28.8	75.3	31.0	70.9	33.2	66.7	35.4	63.3	37.5	59.9	39.6	57.6	41.7	55.3	43.8	52.9
16.0	25.4	68.4	27.7	66.1	30.0	63.1	32.3	59.9	34.5	56.6	36.7	53.3	38.9	51.1	41.0	49.1	43.2	47.0
18.0	24.0	60.1	26.5	58.6	28.9	56.6	31.2	54.1	33.5	50.9	35.7	47.8	38.0	45.8	40.2	43.9	42.4	42.2
20.0	22.4	53.2	25.0	52.3	27.5	51.1	30.0	49.2	32.3	46.2	34.7	43.2	37.0	41.3	39.2	39.7	41.4	38.2
22.0	20.5	47.4	23.3	47.0	25.9	46.6	28.5	45.2	31.0	42.2	33.4	39.2	35.8	37.5	38.1	36.0	40.4	34.6
24.0	17.9	39.7	21.2	42.5	24.1	42.6	26.9	41.5	29.5	38.5	32.0	35.6	34.5	34.1	36.9	32.8	39.3	31.7
26.0			18.7	37.7	21.9	38.6	24.9	38.2	27.7	35.3	30.4	32.4	33.0	31.1	35.5	30.2	38.0	29.2
28.0			15.6	29.6	19.3	33.3	22.7	34.7	25.7	32.2	28.6	29.6	31.3	28.6	34.0	27.7	36.5	26.9
30.0					15.4	22.5	19.9	30.6	23.3	28.6	26.5	26.9	29.4	26.3	32.2	25.6	34.9	25.0
32.0							16.6	25.0	20.6	24.8	24.1	24.3	27.2	24.1	30.2	23.6	33.1	23.1
34.0									16.9	20.8	21.0	22.5	24.7	22.3	28.0	21.9	31.0	21.4
36.0													21.7	20.5	25.3	20.3	28.7	20.0
38.0													17.9	16.6	22.2	17.8	25.9	18.5
40.0																	22.8	17.2
42.0																	18.8	15.8
44.0																		
46.0																		
48.0																		
50.0																		
52.0																		
54.0																		
56.0																		

オールテレーンクレーン[油圧伸縮ジブ型]【400t吊】 (3/3)

作業半径 (m)	48.0		50.0		52.0		54.0		56.0		58.0		60.0		62.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5																
3.0																
3.5																
4.0																
4.5																
5.0																
5.5																
6.0																
7.0																
8.0	47.1	77.2	49.1	71.2												
9.0	46.8	66.3	48.9	60.9												
10.0	47.0	61.8	49.0	57.4	51.1	49.3	53.2	45.7	55.3	44.1	57.4	39.3	59.4	34.5		
12.0	46.5	56.2	48.6	52.7	50.7	46.8	52.8	44.3	54.8	41.4	56.9	37.3	58.9	33.2		
14.0	45.9	50.0	48.0	47.2	50.2	42.2	52.3	40.2	54.3	38.0	56.4	35.5	58.5	33.0	59.9	25.0
16.0	45.3	44.8	47.4	42.6	49.6	38.3	51.7	36.6	53.8	34.7	55.9	32.4	57.9	30.1	59.5	23.6
18.0	44.5	40.5	46.7	38.8	48.9	35.1	51.0	33.6	53.1	32.0	55.2	29.9	57.3	27.8	58.9	22.2
20.0	43.7	36.8	45.9	35.4	48.1	32.3	50.3	31.0	52.4	29.6	54.6	27.6	56.7	25.6	58.2	20.7
22.0	42.7	33.5	44.9	32.5	47.2	29.8	49.4	28.6	51.6	27.3	53.8	25.6	55.9	23.9	57.5	19.4
24.0	41.6	30.8	43.9	30.0	46.2	27.7	48.5	26.6	50.7	25.4	52.9	23.9	55.1	22.4	56.7	18.1
26.0	40.4	28.4	42.7	27.6	45.1	25.5	47.4	24.6	49.7	23.7	52.0	22.4	54.2	21.2	55.8	16.9
28.0	39.0	26.1	41.4	25.3	43.9	23.5	46.3	22.9	48.6	22.1	50.9	21.2	53.2	20.2	54.9	15.8
30.0	37.5	24.2	40.0	23.4	42.6	21.8	45.0	21.3	47.4	20.8	49.7	20.0	52.1	19.2	53.8	14.7
32.0	35.8	22.4	38.4	21.8	41.1	20.2	43.6	19.9	46.1	19.5	48.5	18.7	50.9	18.0	52.7	13.7
34.0	33.9	20.9	36.7	20.3	39.5	18.8	42.1	18.5	44.6	18.1	47.1	17.5	49.5	16.9	51.4	12.8
36.0	31.8	19.5	34.7	18.9	37.6	17.5	40.4	17.2	43.0	16.9	45.6	16.3	48.1	15.8	50.0	11.9
38.0	29.4	18.1	32.5	17.7	35.6	16.4	38.5	16.1	41.2	15.7	43.9	15.2	46.5	14.7	48.5	11.2
40.0	26.6	16.7	30.1	16.2	33.3	15.3	36.4	15.1	39.3	14.7	42.1	14.3	44.8	13.8	46.9	10.5
42.0	23.3	15.5	27.2	15.2	30.8	14.4	34.1	14.1	37.2	13.8	40.1	13.4	43.0	12.9	45.2	9.9
44.0			23.7	15.6	27.8	13.6	31.4	13.3	34.8	13.0	37.9	12.5	40.9	12.1	43.2	9.3
46.0			19.5	13.6	24.4	12.8	28.4	12.5	32.0	12.2	35.4	11.8	38.6	11.4	41.1	8.8
48.0			13.9	6.2	20.1	11.5	24.8	11.6	29.0	11.5	32.7	11.1	36.1	10.7	38.8	8.3
50.0									25.3	10.9	29.5	10.5	33.3	10.1	36.2	7.9
52.0									20.9	10.4	25.8	10.0	30.0	9.6	33.3	7.5
54.0													26.4	9.4		
56.0													21.8	8.9		

オールテレーンクレーン[油圧伸縮ジブ型]【550t吊】(1/3)

作業半径 (m)	14.5		16.0		18.0		20.0		22.0		24.0		26.0		28.0		30.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0	13.2	550.0																
3.5	13.1	430.0	14.6	392.5	16.8	353.6	18.8	325.7	20.7	330.0								
4.0	12.9	388.0	14.5	366.3	16.7	334.3	18.7	319.5	20.7	313.2	23.0	273.5	25.0	273.1				
4.5	12.8	361.0	14.3	349.4	16.5	318.6	18.6	314.3	20.6	312.8	22.9	268.3	25.0	264.1				
5.0	12.6	337.0	14.2	333.3	16.4	313.7	18.5	308.1	20.5	302.9	22.6	282.5	24.6	257.0	26.9	237.3	28.9	217.7
5.5	12.4	323.5	14.0	320.7	16.2	300.9	18.3	296.8	20.4	293.3	22.5	275.6	24.5	252.8	26.7	238.6	28.7	226.1
6.0	12.2	310.0	13.8	308.1	16.1	288.1	18.2	285.4	20.3	283.8	22.3	268.6	24.4	248.7	26.5	239.8	28.5	234.6
7.0	11.7	274.0	13.4	270.6	15.7	252.4	17.8	249.6	20.0	248.2	22.1	243.2	24.1	236.6	26.2	230.7	28.3	225.0
8.0	11.1	240.0	12.9	237.4	15.2	223.2	17.4	219.8	19.6	217.4	21.7	215.0	23.8	212.2	25.9	208.1	28.0	203.6
9.0	10.4	216.0	12.2	214.5	14.7	202.9	17.0	198.6	19.2	194.8	21.4	193.4	23.5	192.4	25.6	189.5	27.7	186.0
10.0	9.5	194.0	11.5	194.0	14.1	185.0	16.4	181.3	18.7	177.7	20.9	176.7	23.1	176.0	25.3	173.5	27.4	170.3
12.0	7.1	143.0	9.6	149.8	12.5	151.6	15.1	151.3	17.5	149.9	19.9	149.5	22.2	149.2	24.4	147.6	26.6	145.7
14.0					10.7	113.6	13.4	127.2	16.1	126.3	18.6	126.6	21.0	126.9	23.4	126.7	25.6	126.2
16.0							11.0	105.7	14.2	106.8	17.0	108.5	19.6	108.8	22.1	109.3	24.5	109.7
18.0									12.0	78.0	15.0	93.8	17.9	94.6	20.6	95.1	23.1	95.4
20.0									8.5	61.8	12.4	74.6	15.7	81.3	18.7	83.3	21.5	83.6
22.0															16.4	72.9	19.5	73.8
24.0															13.5	59.1	17.1	64.7
26.0																		
28.0																		
30.0																		
32.0																		
34.0																		
36.0																		
38.0																		
40.0																		
42.0																		
44.0																		
46.0																		
48.0																		
50.0																		
52.0																		
54.0																		
56.0																		
58.0																		

オールテレンクレーン[油圧伸縮ジブ型]【550t吊】(2/3)

作業半径 (m)	32.0		34.0		36.0		38.0		40.0		42.0		44.0		46.0		48.0	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0																		
3.5																		
4.0																		
4.5																		
5.0																		
5.5																		
6.0	30.8	182.6	32.8	172.9	34.8	163.3												
7.0	30.6	170.5	32.6	160.5	34.7	150.5	36.7	142.0	38.7	134.7	40.8	127.4						
8.0	30.3	158.6	32.4	148.9	34.5	139.3	36.5	131.4	38.5	124.9	40.6	118.3	42.6	112.2	44.7	106.0		
9.0	30.1	146.7	32.1	138.3	34.2	129.8	36.3	122.6	38.3	116.5	40.4	110.3	42.4	104.9	44.5	99.5	46.5	93.9
10.0	29.8	135.9	31.8	128.2	33.9	120.5	36.0	114.0	38.1	108.7	40.1	103.3	42.2	98.3	44.3	93.3	46.3	88.1
12.0	29.0	117.0	31.2	110.5	33.3	103.9	35.4	98.9	37.5	95.0	39.6	91.2	41.7	86.6	43.8	82.0	45.8	77.7
14.0	28.1	101.2	30.3	95.8	32.5	90.4	34.7	86.3	36.8	83.2	39.0	80.2	41.1	76.4	43.2	72.5	45.3	69.1
16.0	27.1	90.3	29.4	85.7	31.6	81.1	33.8	77.1	36.0	73.6	38.2	70.2	40.3	67.1	42.5	64.0	44.6	61.3
18.0	25.8	77.6	28.2	74.9	30.5	72.2	32.8	68.7	35.1	64.4	37.3	60.2	39.5	58.5	41.7	57.0	43.9	55.3
20.0	24.3	67.8	26.8	66.2	29.3	64.7	31.7	62.1	34.0	58.6	36.3	55.2	38.5	53.0	40.8	50.9	43.0	49.0
22.0	22.6	59.9	25.3	59.1	27.8	58.4	30.3	56.2	32.8	52.9	35.1	49.7	37.5	47.5	39.8	45.4	42.0	43.7
24.0	20.5	52.9	23.4	52.1	26.2	51.4	28.8	49.6	31.4	47.1	33.8	44.6	36.2	43.0	38.6	41.5	40.9	40.0
26.0	18.0	46.4	21.3	45.8	24.3	45.3	27.1	43.9	29.8	42.0	32.3	40.1	34.8	39.1	37.3	38.1	39.7	37.0
28.0	14.8	41.4	18.6	40.6	22.0	39.9	25.0	39.0	27.9	38.0	30.7	37.1	33.3	36.1	35.8	35.1	38.3	34.0
30.0	10.5	35.9	15.4	35.6	19.3	35.2	22.7	34.8	25.8	34.4	28.7	34.0	31.5	33.1	32.1	32.1	36.8	31.1
32.0							19.8	31.1	23.4	31.3	26.6	31.5	29.6	30.7	32.4	29.9	35.1	28.9
34.0							16.3	28.1	20.4	28.7	24.0	29.3	27.3	28.5	30.3	27.6	33.2	26.7
36.0													24.7	25.9	28.0	25.3	31.1	24.5
38.0													21.5	23.3	25.3	22.7	28.7	22.1
40.0													17.7	20.8	22.1	20.2	25.9	19.7
42.0																	22.6	17.7
44.0																	18.5	15.7
46.0																	13.1	10.7
48.0																		
50.0																		
52.0																		
54.0																		
56.0																		
58.0																		

オールテレーンクレーン[油圧伸縮ジブ型]【550t吊】(3/3)

作業半径 (m)	50.0		52.0		54.0		56.0		58.0		60.0		62.0		64.0	
	フックの地上高さ (m)	定格総荷重 (t)	フックの地上高さ (m)	定格総荷重 (t)	フックの地上高さ (m)	定格総荷重 (t)	フックの地上高さ (m)	定格総荷重 (t)	フックの地上高さ (m)	定格総荷重 (t)	フックの地上高さ (m)	定格総荷重 (t)	フックの地上高さ (m)	定格総荷重 (t)	フックの地上高さ (m)	定格総荷重 (t)
3.0																
3.5																
4.0																
4.5																
5.0																
5.5																
6.0																
7.0																
8.0																
9.0	48.5	87.7	50.6	81.5												
10.0	48.3	82.7	50.4	77.4	52.4	73.1	54.5	69.3								
12.0	47.9	73.8	49.9	70.0	52.0	66.4	54.1	62.9	56.1	59.5	58.1	56.0	60.2	52.6	62.2	49.8
14.0	47.4	66.4	49.4	63.7	51.5	60.4	53.6	56.9	55.6	53.6	57.7	50.9	59.8	48.2	61.8	45.9
16.0	46.7	59.4	48.8	57.5	50.9	54.8	53.0	52.0	55.1	49.1	57.2	46.6	59.3	44.1	61.3	42.1
18.0	46.0	53.4	48.1	51.5	50.3	49.4	52.4	47.3	54.5	45.2	56.6	42.9	58.7	40.5	60.8	38.7
20.0	45.2	47.7	47.4	46.3	49.5	44.9	51.7	43.3	53.8	41.7	55.9	39.6	58.0	37.5	60.1	35.8
22.0	44.3	42.7	46.5	41.7	48.7	40.6	50.9	39.5	53.0	38.2	55.2	36.3	57.3	34.4	59.5	32.9
24.0	43.2	38.7	45.5	37.3	47.7	36.4	49.9	35.7	52.2	34.8	54.3	33.2	56.5	31.7	58.7	30.5
26.0	42.1	35.4	44.4	33.9	46.7	33.1	49.0	32.5	51.2	31.8	53.4	30.5	55.6	29.1	57.8	28.1
28.0	40.8	32.7	43.2	31.3	45.5	30.5	47.9	29.9	50.1	29.2	52.4	28.1	54.7	26.9	56.9	26.1
30.0	39.4	30.0	41.8	28.9	44.3	28.2	46.6	27.7	49.0	27.1	51.3	26.0	53.6	24.9	55.9	24.1
32.0	37.8	27.8	40.3	26.7	42.9	26.1	45.3	25.7	47.7	25.1	50.1	24.1	52.5	23.1	54.8	22.3
34.0	36.0	25.7	38.7	24.7	41.3	24.1	43.9	23.8	46.3	23.4	48.8	22.4	51.2	21.4	53.6	20.6
36.0	34.1	23.7	36.9	22.8	39.6	22.4	42.2	22.1	44.8	21.6	47.4	20.6	49.8	19.6	52.3	18.8
38.0	31.8	21.5	34.8	20.9	37.7	20.6	40.5	20.4	43.2	20.0	45.8	18.9	48.3	17.8	50.9	17.1
40.0	29.4	19.4	32.6	19.2	35.6	19.0	38.5	18.8	41.4	18.4	44.1	17.3	46.7	16.1	49.3	15.6
42.0	26.5	17.6	30.0	17.5	33.3	17.4	36.4	17.3	39.4	17.0	42.2	16.0	45.0	15.0	47.6	14.5
44.0	23.1	15.9	27.1	16.0	30.7	15.9	34.0	15.8	37.1	15.6	40.1	14.7	43.0	13.8	45.8	13.3
46.0	18.9	12.4	23.6	14.1	27.6	14.5	31.3	14.4	34.7	14.3	37.9	13.5	40.9	12.7	43.9	12.2
48.0					24.1	13.0	28.2	13.1	31.9	13.0	35.4	12.3	38.6	11.6	41.7	11.2
50.0					19.7	10.2	24.6	11.1	28.7	11.7	32.5	11.1	36.0	10.6	39.3	10.2
52.0									25.0	10.5	29.3	10.1	33.1	9.6	36.7	9.3
54.0									20.5	9.4	25.5	9.0	29.8	8.7	33.7	8.5
56.0									14.5	5.8	20.9	6.5	26.0	7.3	30.3	7.6
58.0															26.4	6.8

ラフテレーンクレーン[油圧伸縮ジブ型]【4.9t吊】(1/2)

作業半径 (m)	ブーム長 (m)	4.9		5.5		6.5		7.5		9.5		11.5	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
1.0		5.6	4.9	6.4	4.9	7.4	4.9	8.5	4.9				
1.5		5.5	4.9	6.3	4.9	7.3	4.9	8.4	4.9	10.4	4.9	12.4	4.9
2.0		5.3	4.9	6.1	4.9	7.2	4.9	8.2	4.9	10.3	4.9	12.3	4.9
2.5		5.0	4.9	5.9	4.9	7.0	4.9	8.1	4.9	10.2	4.9	12.2	4.9
3.0		4.7	4.9	5.6	4.9	6.8	4.9	7.9	4.9	10.0	4.9	12.1	4.9
3.5		4.2	4.9	5.3	4.9	6.5	4.9	7.7	4.9	9.8	4.9	12.0	4.9
4.0				4.8	4.9	6.1	4.9	7.4	4.9	9.6	4.9	11.8	4.9
4.5										9.4	4.8	11.6	4.8
5.0										9.1	4.7	11.4	4.6
5.5										8.8	4.2	11.1	4.1
6.0										8.4	3.8	10.8	3.7
7.0										7.4	3.1	10.1	3.1
8.0												9.1	1.8
9.0												8.0	1.5
10.0													
12.0													
14.0													
16.0													
18.0													
20.0													

ラフテレーンクレーン[油圧伸縮ジブ型]【4.9t吊】

(2/2)

作業半径 (m)	ブーム長 (m)	13.5		15.5		17.5		19.5		21.5		23.5	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
1.0													
1.5		14.2	4.3										
2.0		14.4	4.9	16.4	4.9								
2.5		14.3	4.9	16.3	4.8	18.3	4.7	20.4	4.6				
3.0		14.2	4.9	16.2	4.8	18.3	4.7	20.3	4.6	22.5	2.5		
3.5		14.1	4.9	16.1	4.8	18.2	4.7	20.2	4.5	22.2	4.0	24.2	3.3
4.0		13.9	4.9	16.0	4.8	18.1	4.7	20.1	4.6	22.1	4.0	24.2	3.3
4.5		13.7	4.8	15.9	4.8	17.9	4.6	20.0	4.3	22.0	3.8	24.1	3.2
5.0		13.6	4.6	15.7	4.5	17.8	4.3	19.9	3.9	21.9	3.6	24.0	3.2
5.5		13.3	4.1	15.5	4.0	17.6	3.9	19.7	3.6	21.8	3.4	23.9	3.2
6.0		13.1	3.7	15.3	3.6	17.5	3.5	19.6	3.3	21.7	3.1	23.7	3.0
7.0		12.6	3.0	14.8	3.0	17.1	3.0	19.2	2.8	21.3	2.7	23.4	2.5
8.0		11.9	2.5	14.3	2.5	16.6	2.5	18.8	2.4	21.0	2.3	23.1	2.2
9.0		11.1	2.0	13.6	2.1	16.0	2.2	18.3	2.1	20.5	2.1	22.7	2.0
10.0		10.1	1.7	12.9	1.8	15.4	1.8	17.8	1.9	20.1	1.8	22.3	1.7
12.0				10.6	1.1	13.8	1.4	16.4	1.4	18.9	1.4	21.2	1.4
14.0						11.5	1.0	14.6	1.0	17.3	1.1	19.9	1.1
16.0									0.6	15.4	0.8	18.2	0.9
18.0										12.8	0.6	16.1	0.7
20.0											0.4		

ラフデレックレーン[油圧伸縮ジブ型]【7t吊】

作業半径 (m)	5.1		5.5		6.5		7.5		9.5		11.5		13.5		15.5		17.5		19.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
1.0	5.8	7.0	6.2	6.8	7.2	6.1	8.2	5.5												
1.5	5.7	7.0	6.1	6.8	7.1	6.1	8.1	5.5	10.2	4.9	12.2	4.9								
2.0	5.5	7.0	5.9	6.8	7.0	6.1	8.0	5.5	10.1	4.9	12.1	4.9								
2.5	5.2	7.0	5.7	6.8	6.8	6.1	7.9	5.5	10.0	4.9	12.0	4.9	14.1	4.5	16.1	4.1				
3.0	4.9	7.0	5.4	6.8	6.6	6.1	7.7	5.5	9.8	4.9	11.9	4.9	14.0	4.5	16.0	4.1	18.0	3.5	20.1	2.7
3.5	4.5	7.0	5.0	6.8	6.3	6.1	7.4	5.5	9.6	4.9	11.8	4.9	13.8	4.5	15.9	4.1	17.9	3.5	20.0	2.7
4.0									9.4	4.5	11.6	4.5	13.7	4.1	15.8	3.8	17.8	3.2	19.9	2.6
4.5									9.2	3.9	11.4	3.9	13.5	3.6	15.6	3.4	17.7	3.0	19.8	2.5
5.0									8.9	3.3	11.2	3.4	13.3	3.2	15.5	3.1	17.6	2.8	19.6	2.4
5.5									8.5	3.0	10.9	3.0	13.1	2.9	15.3	2.9	17.4	2.6	19.5	2.3
6.0									8.2	2.6	10.6	2.7	12.9	2.6	15.1	2.6	17.2	2.4	19.4	2.2
7.0													12.3	2.1	14.6	2.2	16.8	2.1	19.0	1.9
8.0													11.7	1.8	14.1	1.8	16.4	1.8	18.6	1.7
9.0													10.9	1.5	13.4	1.6	15.8	1.6	18.1	1.5
10.0													9.9	1.3	12.6	1.4	15.2	1.4	17.5	1.3
12.0																	13.5	1.0	16.2	1.0
14.0																	11.3	0.7	14.4	0.8

ラフテレーンクレーン[油圧伸縮ジブ型]【10t吊】

(1/2)

作業半径 (m)	フーム長 (m)	5.1		5.5		6.5		7.5		9.5		11.5	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
1.0		6.1	10.0	6.6	9.6	7.6	8.2	8.7	6.7				
1.5		6.0	10.0	6.4	9.8	7.5	8.4	8.5	7.0	10.5	5.0	12.5	5.0
2.0		5.8	10.0	6.3	9.8	7.3	8.4	8.4	7.0	10.4	5.0	12.5	5.0
2.5		5.5	7.0	6.0	9.8	7.1	8.4	8.2	7.0	10.3	5.0	12.4	5.0
3.0		5.2	6.1	5.7	7.9	6.9	7.0	8.0	6.2	10.2	5.0	12.2	5.0
3.5		4.8	5.3	5.4	6.1	6.6	5.7	7.8	5.4	10.0	5.0	12.1	5.0
4.0				4.9	5.2	6.2	5.1	7.4	5.1	9.8	5.0	11.9	5.0
4.5										9.5	4.8	11.7	4.5
5.0										9.2	4.3	11.5	4.1
5.5										8.9	3.8	11.2	3.7
6.0										8.5	3.4	10.9	3.3
7.0										7.6	2.8	10.3	2.8
8.0													
9.0													
10.0													
12.0													
14.0													
16.0													
18.0													
20.0													
22.0													

ラフテレーンクレーン[油圧伸縮ジブ型]【10t吊】 (2/2)

作業半径 (m)	ブーム長 (m)	13.5		15.5		17.5		19.5		21.5		23.5	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
1.0													
1.5													
2.0	14.5		4.7	16.5	4.2								
2.5	14.4		4.7	16.4	4.2	18.5	3.8	20.6	3.5				
3.0	14.3		4.7	16.3	4.2	18.4	3.9	20.4	3.8	22.5	2.7		
3.5	14.2		4.7	16.2	4.2	18.3	3.9	20.3	3.8	22.4	3.0	24.3	2.3
4.0	14.0		4.7	16.1	4.2	18.2	3.9	20.2	3.8	22.3	3.0	24.3	2.3
4.5	13.9		4.3	16.0	4.1	18.0	3.9	20.1	3.6	22.2	2.9	24.2	2.3
5.0	13.7		3.9	15.8	3.7	17.9	3.5	20.0	3.3	22.0	2.8	24.1	2.3
5.5	13.5		3.5	15.6	3.4	17.8	3.2	19.8	3.0	21.9	2.6	23.9	2.3
6.0	13.2		3.2	15.4	3.1	17.6	3.0	19.7	2.8	21.8	2.5	23.8	2.3
7.0	12.7		2.7	15.0	2.6	17.2	2.5	19.3	2.4	21.5	2.2	23.5	2.0
8.0	12.0		2.2	14.4	2.2	16.7	2.1	18.9	2.0	21.1	1.9	23.2	1.8
9.0	11.2		1.9	13.8	1.9	16.1	1.8	18.4	1.8	20.7	1.7	22.8	1.6
10.0	10.2		1.5	13.0	1.6	15.5	1.6	17.9	1.6	20.2	1.5	22.4	1.4
12.0						13.9	1.2	16.5	1.2	19.0	1.2	21.3	1.2
14.0						11.6	0.8	14.7	0.9	17.5	0.9	20.0	1.0
16.0										15.5	0.7	18.3	0.7
18.0										12.9	0.5	16.2	0.5
20.0												13.4	0.4
22.0												9.4	0.3

ラフテレーンクレーン[油圧伸縮ジブ型]【12t吊】 (1/2)

作業半径 (m)	ブーム長 (m)	5.2		5.5		6.5		7.5		9.5		11.5	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
	1.0	6.0	12.0	6.3	11.7	7.4	10.4	8.4	9.2				
	1.5	5.9	12.0	6.2	11.7	7.3	10.4	8.3	9.2	10.3	7.1	12.3	6.6
	2.0	5.7	12.0	6.1	11.7	7.1	10.4	8.2	9.2	10.2	7.1	12.3	6.6
	2.5	5.5	11.0	5.8	10.2	6.9	9.4	8.0	8.6	10.1	7.1	12.2	6.6
	3.0	5.2	10.0	5.6	8.7	6.7	8.1	7.8	7.6	10.0	6.8	12.0	6.6
	3.5	4.8	8.6	5.2	7.5	6.4	7.1	7.6	6.8	9.8	6.4	11.9	6.3
	4.0			4.7	6.1	6.1	6.1	7.3	6.0	9.6	6.1	11.7	6.0
	4.5									9.3	5.4	11.5	5.3
	5.0									9.0	4.7	11.3	4.7
	5.5									8.7	4.2	11.0	4.1
	6.0									8.3	3.8	10.8	3.7
	7.0									7.4	3.0	10.1	3.0
	8.0											9.2	2.5
	9.0											8.1	2.1
	10.0											6.6	1.7
	12.0												
	14.0												
	16.0												
	18.0												

ラフテレーンクレーン[油圧伸縮ジブ型]【12t吊】 (2/2)

作業半径 (m)	ブーム長 (m)	13.5		15.5		17.5		19.5		21.5		23.5	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
1.0													
1.5	14.3		5.9										
2.0	14.3		5.8	16.3	5.2	18.3	5.0						
2.5	14.2		5.8	16.2	5.2	18.3	4.9	20.3	4.3				
3.0	14.1		5.8	16.1	5.2	18.2	4.9	20.2	4.3	22.2	3.0	24.2	3.0
3.5	14.0		5.7	16.0	5.2	18.1	4.9	20.1	4.3	22.2	3.7	24.2	3.2
4.0	13.8		5.6	15.9	5.2	18.0	4.9	20.0	4.3	22.1	3.7	24.1	3.2
4.5	13.7		5.2	15.8	5.0	17.9	4.7	19.9	4.1	22.0	3.6	24.0	3.2
5.0	13.5		4.6	15.6	4.5	17.7	4.3	19.8	3.8	21.9	3.4	23.9	3.1
5.5	13.3		4.1	15.4	4.0	17.6	3.9	19.6	3.5	21.7	3.3	23.8	3.1
6.0	13.0		3.7	15.2	3.6	17.4	3.5	19.5	3.3	21.6	3.1	23.7	3.0
7.0	12.5		3.0	14.8	3.0	17.0	2.9	19.1	2.8	21.3	2.7	23.4	2.5
8.0	11.8		2.5	14.2	2.5	16.5	2.4	18.7	2.4	20.9	2.3	23.0	2.2
9.0	11.0		2.0	13.6	2.1	15.9	2.1	18.2	2.1	20.5	2.0	22.6	1.9
10.0	10.0		1.7	12.8	1.7	15.3	1.8	17.7	1.8	20.0	1.8	22.2	1.7
12.0				10.7	1.1	13.7	1.3	16.3	1.3	18.8	1.3	21.1	1.3
14.0						11.4	0.9	14.5	1.0	17.3	1.0	19.8	1.1
16.0						8.0	0.5	12.1	0.6	15.3	0.7	18.2	0.8
18.0										12.7	0.6	16.0	0.6

ラフテレーンクレーン[油圧伸縮ジブ型]【13t吊】 (1/2)

作業半径 (m)	ブーム長 (m)	5.3		5.5		6.5		7.5		9.5		11.5	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
1.0		5.6	13.0	5.8	12.6	6.8	10.7	7.8	8.8				
1.5		5.8	13.0	6.1	12.6	7.1	10.7	8.1	8.9	10.1	6.0	12.2	6.0
2.0		5.7	12.0	5.9	11.7	6.9	10.1	8.0	8.5	10.1	6.0	12.1	6.0
2.5		5.4	10.0	5.7	9.8	6.8	8.7	7.8	7.6	9.9	6.0	12.0	6.0
3.0		5.1	8.2	5.4	8.1	6.5	7.5	7.6	6.9	9.8	6.0	11.9	6.0
3.5		4.7	7.0	5.0	7.0	6.2	6.7	7.4	6.4	9.6	6.0	11.7	6.0
4.0		4.2	6.1	4.5	6.1	5.9	6.1	7.1	6.0	9.4	6.0	11.5	6.0
4.5										9.1	5.5	11.3	5.4
5.0										8.8	4.9	11.1	4.9
5.5										8.5	4.4	10.9	4.4
6.0										8.1	4.0	10.6	4.0
7.0										7.2	3.3	9.9	3.3
8.0													
9.0													
10.0													
12.0													
14.0													
16.0													
18.0													

ラフテレーンクレーン[油圧伸縮ジブ型]【13t吊】 (2/2)

作業半径 (m) ブーム長 (m)	13.5		15.5		17.5		19.5		21.5		23.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
1.0												
1.5												
2.0	14.1	5.8	16.1	5.3								
2.5	14.0	5.8	16.1	5.3	17.7	4.9	19.7	4.8				
3.0	13.9	5.8	16.0	5.3	18.0	4.9	20.0	4.8				
3.5	13.8	5.8	15.9	5.3	17.9	4.9	19.9	4.8	22.0	4.2	24.0	3.4
4.0	13.7	5.8	15.7	5.3	17.8	4.9	19.9	4.8	21.9	4.2	23.9	3.4
4.5	13.5	5.3	15.6	5.1	17.7	4.9	19.7	4.6	21.8	4.1	23.8	3.4
5.0	13.3	4.8	15.4	4.7	17.5	4.5	19.6	4.2	21.7	3.8	23.7	3.3
5.5	13.1	4.3	15.3	4.2	17.4	4.1	19.5	3.8	21.5	3.5	23.6	3.3
6.0	12.9	3.9	15.1	3.8	17.2	3.7	19.3	3.5	21.4	3.3	23.5	3.0
7.0	12.3	3.2	14.6	3.2	16.8	3.1	19.0	3.0	21.1	2.8	23.2	2.6
8.0	11.6	2.7	14.0	2.7	16.3	2.7	18.5	2.5	20.7	2.4	22.9	2.3
9.0	10.8	2.2	13.4	2.3	15.8	2.3	18.1	2.3	20.3	2.1	22.5	2.0
10.0	9.8	6.1	12.6	3.3	15.1	2.0	17.5	2.0	19.8	1.9	22.0	1.8
12.0					13.5	1.5	16.1	1.5	18.6	1.5	21.0	1.4
14.0					11.3	1.1	14.3	1.1	17.1	1.1	19.6	1.2
16.0									15.1	0.9	18.0	0.9
18.0									12.5	0.7	15.9	0.7

ラフテレーンクレーン[油圧伸縮ジブ型]【16t吊】 (1/2)

作業半径 (m)	フーム長 (m)	6.5		7.5		9.5		11.5		13.5		15.5	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5		6.9	16.0	8.0	15.1	10.1	13.1	12.1	11.4	14.2	10.0	16.2	8.7
3.0		6.7	16.0	7.8	15.1	9.9	13.1	12.0	11.4	14.1	10.0	16.1	8.7
3.5		6.4	14.0	7.5	13.5	9.7	12.6	11.9	11.4	13.9	10.0	16.0	8.7
4.0		6.0	12.5	7.2	12.4	9.5	12.1	11.7	11.4	13.8	10.0	15.9	8.7
4.5		4.9	11.5	6.2	11.4	8.5	11.2	11.5	10.7	13.6	9.7	15.7	8.7
5.0								11.3	10.0	13.4	9.4	15.6	8.6
5.5								11.0	9.2	13.2	8.6	15.4	8.0
6.0								10.7	8.6	13.0	8.0	15.2	7.5
7.0								10.0	6.7	12.4	6.5	14.7	6.4
8.0								9.2	5.2	11.8	5.1	14.2	5.0
9.0												13.5	4.0
10.0												12.7	3.2
12.0												10.7	2.2
14.0													
16.0													
18.0													
20.0													
22.0													
24.0													

ラフテレーンクレーン[油圧伸縮ジブ型]【16t吊】 (2/2)

作業半径 (m)	フーム長 (m)	17.5		19.5		21.5		23.5		25.5		27.5	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.5		18.2	7.8										
3.0		18.1	7.8										
3.5		18.0	7.8	20.1	6.8	22.1	5.9	24.1	4.9	26.2	4.2	28.2	3.5
4.0		17.9	7.8	20.0	6.8	22.0	5.9	24.1	4.9	26.1	4.2	28.1	3.5
4.5		17.8	7.8	19.9	6.8	21.9	5.9	24.0	4.9	26.0	4.2	28.0	3.5
5.0		17.7	7.7	19.8	6.8	21.8	5.9	23.9	4.9	25.9	4.2	27.9	3.5
5.5		17.5	7.5	19.6	6.8	21.7	5.9	23.7	4.9	25.8	4.2	27.8	3.5
6.0		17.3	7.0	19.5	6.5	21.5	5.7	23.6	4.9	25.7	4.2	27.7	3.5
7.0		16.9	6.1	19.1	5.7	21.2	5.2	23.3	4.6	25.4	4.1	27.5	3.5
8.0		16.5	5.1	18.7	5.1	20.9	4.6	23.0	4.1	25.1	3.8	27.2	3.4
9.0		15.9	4.2	18.2	4.2	20.4	4.0	22.6	3.7	24.8	3.4	26.9	3.1
10.0		15.3	3.4	17.6	3.5	19.9	3.4	22.2	3.3	24.4	3.0	26.5	2.8
12.0		13.6	2.3	16.3	2.5	18.7	2.6	21.1	2.6	23.4	2.5	25.6	2.4
14.0				14.5	1.8	17.2	1.8	19.8	1.9	22.2	2.0	24.6	2.0
16.0				12.0	1.3	15.3	1.3	18.1	1.4	20.8	1.5	23.3	1.5
18.0								16.0	1.1	19.0	1.1	21.7	1.1
20.0								13.2	0.8	16.7	0.8	19.8	0.8
22.0												17.4	0.6
24.0												14.3	0.5

ラフデレックレーン[油圧伸縮ジブ型]【20t吊】(2/2)

(m) 作業半径 (m)	6.5		7.5		9.5		11.5		13.5		15.5		17.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5	7.1	20.0	8.1	18.3	10.3	15.1	12.3	12.3	14.4	11.1	16.4	10.0	18.4	8.8
3.0	6.8	18.5	7.9	17.2	10.1	14.6	12.2	12.3	14.2	11.1	16.3	10.0	18.3	8.8
3.5	6.6	16.2	7.7	15.5	9.9	13.8	12.0	12.2	14.1	11.1	16.2	10.0	18.2	8.8
4.0	6.2	14.0	7.4	13.8	9.7	13.1	11.9	12.2	14.0	11.1	16.1	10.0	18.1	8.8
4.5	5.8	12.0	7.1	12.1	9.5	12.1	11.7	11.7	13.8	10.9	15.9	10.0	18.0	8.8
5.0			6.1	14.0	9.2	11.8	11.4	10.9	13.6	10.5	15.8	10.0	17.9	8.8
5.5					9.3	9.9	11.2	10.1	13.4	9.7	15.6	9.3	17.7	8.4
6.0					8.9	8.9	10.9	9.2	13.2	8.9	15.4	8.6	17.5	8.1
7.0							10.2	7.0	12.6	7.0	14.9	6.9	17.1	6.7
8.0							9.3	5.4	11.9	5.4	14.4	5.4	16.6	5.5
9.0							8.2	4.2	11.1	4.2	13.7	4.2	16.1	4.4
10.0											12.9	3.4	15.4	3.6
12.0											10.9	2.2	13.8	2.4
14.0													11.0	2.3
16.0														
18.0														
20.0														
22.0														

ラフデレックレーン[油圧伸縮ジブ型]【20t吊】(2/2)

ブーム長 (m) 作業半径 (m)	19.5		21.5		23.5		25.5		27.5		29.5	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.5	20.4	7.6	22.9	7.0								
3.0	20.4	7.6	22.8	7.0								
3.5	20.3	7.6	22.3	6.9	24.3	6.2	26.3	5.6	28.4	5.1		
4.0	20.2	7.6	22.2	6.9	24.2	6.2	26.3	5.6	28.3	5.1		
4.5	20.1	7.6	22.1	6.9	24.2	6.2	26.2	5.6	28.2	5.2	29.6	5.4
5.0	19.9	7.6	22.0	6.9	24.0	6.2	26.1	5.6	28.1	5.2	29.6	5.4
5.5	19.8	7.6	21.9	6.9	23.9	6.2	26.0	5.6	28.0	5.2	29.5	5.4
6.0	19.6	7.6	21.7	6.9	23.8	6.1	25.9	5.6	27.9	5.1	29.4	5.4
7.0	19.3	6.6	21.4	6.1	23.5	5.5	25.6	5.1	27.7	4.8	29.1	5.4
8.0	18.9	5.5	21.0	5.2	23.2	4.8	25.3	4.5	27.4	4.2	28.9	4.9
9.0	18.4	4.5	20.6	4.4	22.8	4.3	24.9	4.0	27.1	3.7	28.6	4.4
10.0	17.8	3.7	20.1	3.8	22.4	3.8	24.5	3.6	26.7	3.3	28.2	4.0
12.0	16.5	2.6	18.9	2.7	21.3	2.8	23.6	2.7	25.8	2.7	27.4	3.3
14.0	14.7	2.4	17.4	1.9	20.0	2.0	22.4	2.1	24.8	2.1	26.5	2.7
16.0			15.4	1.4	18.3	1.5	20.9	1.5	23.5	1.6	25.3	2.2
18.0			12.2	1.4	16.2	1.4	19.1	1.1	21.9	1.2	23.9	1.7
20.0					13.8	1.0	16.9	0.8	20.0	0.9	22.2	1.3
22.0									17.0	1.0	20.1	1.0

ラフテレックスレーン[油圧伸縮ジブ型]【22t吊】(1/2)

作業半径 (m) ブーム長 (m)	6.7		7.5		9.5		11.5		13.5		15.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0	6.8	22.0	7.7	20.1	9.8	15.5	11.9	12.0	13.9	12.0	16.0	11.8
3.5	6.5	20.0	7.4	18.5	9.6	14.8	11.7	12.0	13.8	12.0	15.9	11.8
4.0	6.2	17.0	7.1	16.1	9.4	13.7	11.6	12.0	13.7	12.0	15.8	11.8
4.5	5.7	15.0	6.8	14.4	9.2	13.1	11.4	12.0	13.5	12.0	15.6	11.8
5.0							11.1	12.0	13.3	12.0	15.5	11.8
5.5							10.9	12.0	13.1	12.0	15.3	11.8
6.0							10.6	11.9	12.9	11.7	15.1	11.3
7.0							9.9	10.4	12.3	10.1	14.6	9.7
8.0							9.0	8.6	11.7	8.4	14.1	8.3
9.0							7.9	6.8	10.8	6.7	13.4	6.7
10.0											12.6	5.4
12.0											10.6	3.7
14.0												
16.0												
18.0												

ラフテレーンクレーン[油圧伸縮ジブ型]【22t吊】 (2/2)

作業半径 (m)	ブーム長 (m)	17.5		19.5		21.5		23.5		25.5		27.5	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0		18.0	10.6	20.1	9.3	22.1	8.1						
3.5		17.9	10.6	20.0	9.3	22.0	8.1						
4.0		17.8	10.6	19.9	9.3	21.9	8.1	23.9	7.5	26.0	7.0	28.0	6.5
4.5		17.7	10.6	19.8	9.3	21.8	8.1	23.9	7.5	25.9	7.0	27.9	6.5
5.0		17.6	10.6	19.6	9.3	21.7	8.1	23.7	7.5	25.8	7.0	27.8	6.5
5.5		17.4	10.6	19.5	9.3	21.6	8.1	23.6	7.5	25.7	7.0	27.7	6.5
6.0		17.2	10.2	19.3	9.2	21.4	8.1	23.5	7.5	25.6	7.0	27.6	6.5
7.0		16.8	9.1	19.0	8.5	21.1	7.9	23.2	7.4	25.3	7.0	27.4	6.5
8.0		16.3	7.9	18.6	7.5	20.7	7.1	22.9	6.7	25.0	6.4	27.1	6.0
9.0		15.8	6.6	18.1	6.5	20.3	6.4	22.5	6.1	24.6	5.7	26.8	5.4
10.0		15.1	5.5	17.5	5.5	19.8	5.6	22.1	5.4	24.2	5.1	26.4	4.9
12.0		13.5	3.9	16.2	4.1	18.6	4.3	21.0	4.2	23.3	4.0	25.5	3.9
14.0								19.7	3.2	22.1	3.2	24.5	3.1
16.0								18.0	2.4	20.6	2.5	23.2	2.5
18.0								15.9	1.8	18.8	1.9	21.6	2.0

ラフテレーンクレーン[油圧伸縮ジブ型]【25t吊】(1/2)

作業半径 (m)	ブーム長 (m)	9.32		9.5		11.5		13.5		15.5		17.5	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5		10.5	25.0	10.5	24.9	12.6	22.5	14.6	20.0	16.7	17.6	18.7	15.8
3.0		10.4	25.0	10.4	24.9	12.5	22.5	14.5	20.0	16.6	17.6	18.6	15.9
3.5		10.2	25.0	10.2	24.9	12.3	22.5	14.4	20.0	16.5	17.6	18.5	15.9
4.0		10.0	23.0	10.0	23.2	12.1	21.3	14.3	19.3	16.3	17.4	18.4	15.9
4.5		9.7	21.2	9.7	21.3	12.0	19.8	14.1	18.3	16.2	16.8	18.3	15.6
5.0		9.4	19.4	9.4	19.5	11.7	18.4	13.9	17.3	16.0	16.2	18.1	15.2
5.5		9.1	17.8	9.1	17.8	11.5	17.0	13.7	16.3	15.9	15.6	18.0	14.8
6.0		8.7	16.3	8.7	16.3	11.2	15.9	13.5	15.5	15.7	15.0	17.8	14.4
7.0				8.1	13.7	10.8	13.5	13.2	13.3	15.5	13.1	17.4	13.2
8.0												16.9	10.9
9.0												16.4	9.0
10.0												15.7	7.5
12.0												14.1	5.3
14.0												12.2	3.7
16.0													
18.0													
20.0													

ラフテレーンクレーン[油圧伸縮ジブ型]【25t吊】 (2/2)

作業半径 (m)	フーム長 (m)	19.5		21.5		23.5		25.5		27.5		29.5	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.5		20.7	14.7	22.7	13.6	25.0	12.5						
3.0		20.6	14.7	22.7	13.6	24.9	12.5						
3.5		20.6	14.7	22.6	13.6	24.6	12.4	26.6	11.1	28.6	9.7	30.7	8.3
4.0		20.5	14.7	22.5	13.6	24.5	12.4	26.6	11.1	28.6	9.7	30.6	8.3
4.5		20.3	14.5	22.4	13.5	24.4	12.4	26.5	11.1	28.5	9.7	30.5	8.3
5.0		20.2	14.3	22.3	13.3	24.3	12.4	26.4	11.1	28.4	9.7	30.4	8.3
5.5		20.1	13.9	22.2	13.0	24.2	12.1	26.3	10.9	28.3	9.6	30.4	8.3
6.0		19.9	13.5	22.0	12.7	24.1	11.8	26.2	10.6	28.2	9.4	30.3	8.2
7.0		19.6	12.3	21.7	11.4	23.8	10.5	25.9	9.7	28.0	8.9	30.0	8.0
8.0		19.2	10.4	21.3	9.9	23.5	9.4	25.6	8.9	27.7	8.4	29.8	7.9
9.0		18.7	8.8	20.9	8.6	23.1	8.5	25.2	8.1	27.4	7.7	29.5	7.3
10.0		18.1	7.5	20.4	7.5	22.6	7.5	24.8	7.2	27.0	6.9	29.1	6.6
12.0		16.7	5.5	19.2	5.6	21.6	5.7	23.9	5.6	26.1	5.5	28.3	5.4
14.0		15.2	3.8	18.0	4.0	20.2	4.3	22.7	4.3	25.0	4.3	27.3	4.3
16.0						18.6	3.3	21.2	3.3	23.7	3.4	26.2	3.5
18.0						16.5	2.6	19.4	2.6	22.2	2.7	24.7	2.7
20.0						13.7	2.0	17.2	2.1	20.2	2.1	23.1	2.2

ラフテレーンクレーン[油圧伸縮ジブ型]【30t吊】(1/2)

作業半径 (m)	ブーム長 (m)	7.7		9.5		11.5		13.5		15.5		17.5	
		フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5		7.7	30.0	9.6	26.0	11.7	21.6	13.7	18.7	15.7	17.9	17.8	17.1
3.0		7.5	30.0	9.4	26.0	11.5	21.6	13.6	18.7	15.6	17.9	17.7	17.1
3.5		7.3	27.8	9.3	24.6	11.4	21.1	13.5	18.7	15.5	17.9	17.6	17.1
4.0		7.0	25.0	9.1	22.8	11.2	20.4	13.3	18.7	15.4	17.9	17.5	17.1
4.5		6.7	22.5	8.8	21.2	11.0	19.8	13.2	18.7	15.3	17.9	17.3	17.1
5.0		6.3	20.3	8.5	19.8	10.8	19.3	13.0	18.6	15.1	17.4	17.2	16.3
5.5								12.8	18.0	14.9	16.7	17.0	15.3
6.0								12.5	16.6	14.7	15.5	16.9	14.4
7.0								12.0	13.8	14.3	13.3	16.5	12.9
8.0								11.3	11.6	13.7	11.5	16.0	11.5
9.0								10.5	9.2	13.1	9.2	15.4	9.3
10.0								9.5	7.3	12.3	7.4	14.8	7.4
12.0													
14.0													
16.0													
18.0													
20.0													
22.0													
24.0													
26.0													
28.0													

ラフデレックレーン[油圧伸縮ジブ型]【30t吊】 (2/2)

作業半径 (m)	ブーム長 (m)	19.5		21.5		23.5		25.5		27.5		29.5		31.5	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.5		19.8	15.2	21.8	13.2										
3.0		19.7	15.2	21.7	13.2										
3.5		19.6	15.2	21.6	13.2	23.7	11.5	25.7	10.3	27.7	9.1				
4.0		19.5	15.2	21.6	13.2	23.6	11.5	25.6	10.3	27.6	9.1				
4.5		19.4	15.2	21.5	13.2	23.5	11.5	25.5	10.3	27.6	9.1	29.6	8.4	31.6	7.3
5.0		19.3	14.7	21.3	13.0	23.4	11.5	25.4	10.3	27.5	9.1	29.5	8.4	31.5	7.3
5.5		19.1	14.1	21.2	12.8	23.3	11.5	25.3	10.3	27.4	9.1	29.4	8.4	31.5	7.3
6.0		19.0	13.5	21.1	12.6	23.2	11.5	25.2	10.3	27.3	9.1	29.3	8.4	31.4	7.3
7.0		18.6	12.2	20.8	11.4	22.9	10.7	25.0	9.9	27.0	9.1	29.1	8.4	31.1	7.3
8.0		18.2	10.9	20.4	10.3	22.5	9.7	24.6	9.1	26.7	8.5	28.8	7.8	30.9	6.9
9.0		17.7	9.1	20.0	9.0	22.1	8.7	24.3	8.2	26.4	7.8	28.5	7.1	30.6	6.5
10.0		17.2	7.6	19.5	7.9	21.7	7.9	23.9	7.5	26.1	7.1	28.2	6.5	30.3	6.0
12.0		15.8	5.3	18.3	5.6	20.6	5.8	22.9	5.9	25.2	6.0	27.4	5.6	29.6	5.1
14.0		14.0	3.8	16.8	4.0	19.3	4.2	21.7	4.4	24.1	4.5	26.4	4.6	28.7	4.4
16.0						17.6	3.1	20.3	3.3	22.8	3.4	25.2	3.5	27.6	3.7
18.0						15.5	2.3	18.5	2.5	21.2	2.6	23.8	2.7	26.3	2.9
20.0						12.8	1.8	16.3	1.9	19.3	2.0	22.1	2.1	24.8	2.3
22.0												20.1	1.7	23.0	1.8
24.0												17.6	1.2	20.8	1.4
26.0														18.2	1.1
28.0														14.9	0.8

ラフテレーンクレーン[油圧伸縮ジブ型]【35t吊】 (1/2)

(m) 作業半径 (m)	7.5		9.5		11.5		13.5		15.5		17.5		19.5		21.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.6	8.5	35.0	10.6	28.6	12.7	22.2	14.7	18.6	16.7	17.8	18.8	17.0	20.8	15.0	22.8	13.0
3.0	8.3	32.0	10.1	33.3	12.3	29.5	14.5	21.5	16.5	19.8	18.6	18.3	20.6	16.1	22.6	14.0
3.5	8.1	28.8	9.9	29.4	12.1	26.9	14.4	21.0	16.4	19.6	18.5	18.3	20.5	16.1	22.5	14.0
4.0	7.8	26.0	9.7	26.6	11.9	25.0	14.2	20.6	16.3	19.5	18.4	18.3	20.4	16.1	22.5	14.0
4.5	7.5	23.0	9.5	24.0	11.7	22.8	14.1	19.8	16.2	18.9	18.2	17.8	20.3	15.9	22.4	13.9
5.0	7.1	20.5	9.2	21.8	11.5	21.0	13.9	19.2	16.0	18.4	18.1	17.4	20.2	15.6	22.2	13.8
5.5			8.7	20.3	11.2	19.6	13.7	18.3	15.8	17.3	17.9	16.3	20.0	14.9	22.1	13.4
6.0			8.4	18.6	10.9	18.1	13.4	16.9	15.6	16.1	17.8	15.2	19.9	14.1	22.0	13.0
7.0			7.3	14.5	10.2	14.4	12.9	14.2	15.2	13.9	17.4	13.4	19.5	12.7	21.7	11.9
8.0							12.3	11.7	14.7	11.6	16.9	11.9	19.1	11.3	21.3	10.7
9.0							11.5	9.3	14.1	9.3	16.3	9.7	18.6	9.5	20.9	9.3
10.0							10.5	7.5	13.3	7.5	15.7	8.0	18.1	8.1	20.4	8.2
12.0											14.1	5.5	16.7	5.7	19.2	6.0
14.0											12.0	3.7	15.0	3.9	17.8	4.1
16.0																
18.0																
20.0																
22.0																
24.0																
26.0																

ラフテレックレーン[油圧伸縮ジブ型]【35t吊】 (2/2)

(m) 作業半径 (m)	23.5		25.5		27.5		29.5		31.5		33.5		35.5	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.6														
3.0	24.9	15.0	26.9	13.4	28.9	11.7	30.9	10.0						
3.5	24.6	12.2	26.6	10.9	28.6	9.7	30.3	10.1	32.9	9.1	34.9	8.2	36.9	7.3
4.0	24.5	12.3	26.5	11.0	28.5	9.8	30.3	10.1	32.3	9.1	34.3	8.2	36.3	7.4
4.5	24.4	12.3	26.4	11.0	28.5	9.8	30.5	8.8	32.5	7.9	34.2	8.2	36.2	7.4
5.0	24.3	12.3	26.3	11.0	28.4	9.8	30.4	8.8	32.4	8.0	34.2	8.2	36.2	7.4
5.5	24.2	12.1	26.2	10.9	28.3	9.7	30.3	8.8	32.4	8.0	34.1	8.2	36.1	7.4
6.0	24.1	11.9	26.1	10.8	28.2	9.7	30.2	8.8	32.3	8.0	34.0	8.2	36.0	7.4
7.0	23.8	11.1	25.9	10.3	27.9	9.5	30.0	8.8	32.0	8.0	33.8	8.2	35.8	7.4
8.0	23.4	10.1	25.5	9.5	27.6	8.9	29.7	8.3	31.8	7.7	33.6	7.7	35.6	7.2
9.0	23.0	9.0	25.2	8.5	27.3	8.0	29.4	7.5	31.5	7.0	33.4	7.0	35.4	6.5
10.0	22.6	8.1	24.8	7.7	27.0	7.3	29.1	6.8	31.2	6.3	33.1	6.3	35.1	6.0
12.0	21.5	6.1	23.8	6.1	26.1	6.1	28.3	5.7	30.5	5.4	32.4	5.3	34.4	5.0
14.0	20.2	4.6	22.6	4.7	25.0	4.8	27.3	4.7	29.6	4.5	31.5	4.5	33.7	4.3
16.0	18.5	3.5	21.2	3.6	23.7	3.7	26.1	3.8	28.5	3.8	30.5	3.8	32.7	3.7
18.0	16.4	2.6	19.4	2.8	22.1	2.9	24.7	3.0	27.2	3.1	29.3	3.2	31.6	3.2
20.0	13.7	1.9	17.2	2.1	20.2	2.2	23.0	2.3	25.7	2.4	28.0	2.7	30.4	2.8
22.0					18.0	1.6	21.1	1.7	23.9	1.9	26.3	2.2	28.9	2.3
24.0					14.9	1.2	18.6	1.3	21.7	1.4	24.5	1.7	27.2	1.8
26.0							15.3	1.1	18.9	1.2	22.2	1.3	25.2	1.4

ラフテレーンクレーン[油圧伸縮ジブ型]【45t吊】(1/2)

作業半径 (m)	ブーム長 (m)	10.2		11.5		13.5		15.5		17.5		19.5		21.5		23.5	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
3.0		9.2	45.0	11.3	42.2	13.4	37.4	15.4	32.7	17.5	28.0	19.5	25.8	21.5	23.5	23.5	21.3
3.5		9.0	40.8	11.2	38.8	13.3	35.2	15.3	31.6	17.4	28.0	19.4	25.8	21.4	23.5	23.5	21.3
4.0		8.8	37.0	11.0	35.5	13.1	33.0	15.2	30.5	17.3	28.0	19.3	25.8	21.3	23.5	23.4	21.3
4.5		8.6	33.5	10.8	32.6	12.9	31.1	15.0	29.5	17.1	28.0	19.2	25.8	21.2	23.5	23.3	21.3
5.0		8.3	30.2	10.6	29.8	12.8	29.2	14.9	28.6	17.0	28.0	19.1	25.8	21.1	23.5	23.2	21.3
5.5		8.0	27.5	10.3	27.2	12.5	26.8	14.7	26.3	16.8	25.9	18.9	24.2	21.0	22.6	23.1	21.0
6.0		7.7	25.0	10.0	24.8	12.3	24.6	14.5	24.3	16.7	24.0	18.8	22.9	20.9	21.8	22.9	20.7
7.0		6.8	20.7	9.3	20.7	11.8	20.6	14.0	20.5	16.3	20.4	18.4	19.5	20.5	18.7	22.6	17.8
8.0										15.0	17.4	18.0	16.8	20.2	16.2	22.3	15.7
9.0										14.4	15.0	17.5	14.6	19.7	14.2	21.9	13.8
10.0										13.8	12.4	17.0	12.6	19.2	12.4	21.5	12.3
12.0										12.1	8.9	15.6	8.9	18.1	8.8	20.4	8.7
14.0										9.9	6.3	13.8	6.4	16.5	6.3	19.1	6.3
16.0																	
18.0																	
20.0																	
22.0																	
24.0																	
26.0																	
28.0																	

ラフテレーンクレーン[油圧伸縮ジブ型]【45t吊】(2/2)

ブーム長 (m) 作業半径 (m)	25.5			27.5			29.5			31.5			33.5			35.5			37.5		
	フックの 地上高さ	定格 総荷重		フックの 地上高さ	定格 総荷重		フックの 地上高さ	定格 総荷重		フックの 地上高さ	定格 総荷重		フックの 地上高さ	定格 総荷重		フックの 地上高さ	定格 総荷重		フックの 地上高さ	定格 総荷重	
	(m)	(t)		(m)	(t)		(m)	(t)		(m)	(t)		(m)	(t)		(m)	(t)		(m)	(t)	
3.0	26.3	19.3		28.4	17.7		30.4	16.0		32.4	14.3										
3.5	25.5	19.2		27.5	17.4		29.5	15.6		31.5	13.8										
4.0	25.4	19.2		27.4	17.4		29.4	15.6		31.5	13.8		34.3	12.5		36.3	10.7		38.3	8.9	
4.5	25.3	19.2		27.3	17.4		29.4	15.6		31.4	13.8		33.4	12.1		35.4	10.5		37.4	8.8	
5.0	25.2	19.2		27.3	17.4		29.3	15.6		31.3	13.8		33.3	12.1		35.4	10.5		37.4	8.8	
5.5	25.1	19.2		27.2	17.4		29.2	15.6		31.2	13.8		33.3	12.1		35.3	10.5		37.3	8.8	
6.0	25.0	19.2		27.1	17.4		29.1	15.6		31.1	13.8		33.2	12.1		35.2	10.5		37.2	8.8	
7.0	24.7	16.9		26.8	15.7		28.9	14.6		30.9	13.4		33.0	11.9		35.0	10.3		37.1	8.8	
8.0	24.4	15.0		26.5	14.2		28.6	13.4		30.7	12.6		32.7	11.3		34.8	9.9		36.9	8.6	
9.0	24.1	13.3		26.2	12.7		28.3	12.0		30.4	11.3		32.5	10.4		34.6	9.3		36.6	8.3	
10.0	23.7	11.9		25.8	11.4		28.0	10.8		30.1	10.3		32.2	9.6		34.3	8.8		36.4	8.1	
12.0	22.7	8.7		25.0	8.6		27.2	8.6		29.3	8.5		31.5	8.1		33.6	7.5		35.7	7.0	
14.0	21.5	6.4		23.9	6.6		26.2	6.8		28.4	7.0		30.6	6.7		32.8	6.4		35.0	6.0	
16.0	20.1	4.7		22.6	5.0		25.0	5.2		27.3	5.4		29.6	5.4		31.9	5.2		34.1	5.1	
18.0	18.3	3.5		21.0	3.7		23.6	4.0		26.1	4.2		28.5	4.3		30.8	4.3		33.1	4.3	
20.0	16.0	2.6		19.1	2.8		21.9	3.0		24.6	3.3		27.1	3.4		29.5	3.5		31.9	3.7	
22.0													25.5	2.7		28.1	2.8		30.6	2.9	
24.0													23.6	2.0		26.4	2.2		29.0	2.3	
26.0													22.1	1.5		25.2	1.7		28.0	1.8	
28.0													19.4	1.1		22.8	1.2		26.0	1.4	

ラフテレーンクレーン[油圧伸縮ジブ型]【50t吊】 (1/2)

作業半径 (m)		ブーム長 (m)		9.6		11.5		13.5		15.5		17.5		19.5		21.5		23.5	
		フックの 地上高さ		定格 総荷重	フックの 地上高さ		定格 総荷重	フックの 地上高さ		定格 総荷重	フックの 地上高さ		定格 総荷重	フックの 地上高さ		定格 総荷重	フックの 地上高さ		定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)		
2.3		11.1	50.0																
2.5		11.0	45.9	12.5	44.3	37.9	14.6	37.9	31.6	16.6	20.6	24.4	22.7	21.3	24.7	18.5			
3.0		10.9	41.7	12.7	42.8	37.0	14.8	37.0	31.3	16.9	20.9	23.2	22.9	20.4	25.0	17.9			
3.5		10.7	38.8	12.6	37.6	33.6	14.7	33.6	29.6	16.7	20.8	23.2	22.9	20.4	24.9	17.9			
4.0		10.5	36.3	12.4	34.7	31.8	14.5	31.8	28.8	16.6	20.7	23.2	22.8	20.4	24.8	17.9			
4.5		10.2	33.9	12.2	32.2	30.2	14.4	30.2	28.1	16.5	20.6	23.2	22.7	20.4	24.7	17.9			
5.0		10.0	31.7	12.0	29.9	28.6	14.2	28.6	27.4	16.3	20.5	23.1	22.6	20.4	24.6	17.9			
5.5		9.6	29.4	11.7	27.5	26.6	14.0	26.6	25.6	16.1	20.4	22.1	22.4	19.8	24.5	17.7			
6.0		9.3	26.9	11.5	25.2	24.5	13.7	24.5	23.8	15.9	20.2	21.0	22.3	19.2	24.4	17.4			
7.0				10.7	20.8	20.8	13.1	20.8	20.7	15.4	19.8	18.3	22.0	17.1	24.1	15.9			
8.0											17.2	16.5	21.6	15.4	23.7	14.5			
9.0											16.7	13.6	16.7	14.1	23.4	13.4			
10.0											16.0	11.2	16.0	12.2	22.9	12.1			
12.0											14.4	7.7	14.4	8.7	21.9	8.8			
14.0														6.7	20.5	6.4			
16.0															18.9	4.6			
18.0															16.8	3.5			
20.0															14.1	2.8			
22.0																			
24.0																			
26.0																			
28.0																			
30.0																			
32.0																			

ラフデレックレーン[油圧伸縮ジブ型]【50t吊】 (2/2)

作業半径 (m) ジブ長さ (m)		25.5		27.5		29.5		31.5		33.5		35.5		37.5		39.5	
	フックの 地上高さ	定格 総荷重		フックの 地上高さ		定格 総荷重		フックの 地上高さ		定格 総荷重		フックの 地上高さ		定格 総荷重		フックの 地上高さ	
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.3																	
2.5	26.7	15.9	13.4														
3.0	27.0	13.0	12.4	31.1	12.1												
3.5	26.9	16.5	15.3	30.9	14.2			33.0	13.0	35.0	10.4	37.1	9.0				
4.0	26.8	16.5	15.3	30.9	14.2			32.9	13.0	34.9	10.4	36.9	9.3	38.6	8.9		
4.5	26.7	16.5	15.3	30.8	14.2			32.8	13.0	34.8	11.5	36.9	10.1	38.8	8.9	40.7	7.4
5.0	26.7	16.5	15.3	30.7	14.2			32.7	13.0	34.8	11.5	36.8	10.1	38.8	8.9	40.5	7.8
5.5	26.5	16.5	15.3	30.6	14.2			32.7	13.0	34.7	11.5	36.7	10.1	38.7	8.9	40.4	7.8
6.0	26.4	16.4	15.3	30.5	14.2			32.6	13.0	34.6	11.5	36.6	10.1	38.6	8.9	40.3	7.8
7.0	26.2	15.1	14.3	30.3	13.6			32.4	12.6	34.4	11.3	36.5	10.0	38.4	8.9	40.2	7.8
8.0	25.9	14.0	13.4	30.0	12.8			32.1	12.0	34.2	10.9	36.2	9.6	38.2	8.7	40.0	7.8
9.0	25.5	12.9	12.3	29.7	11.7			31.8	11.0	33.9	10.1	36.0	9.2	38.0	8.4	39.8	7.8
10.0	25.1	11.7	11.1	29.4	10.6			31.5	10.0	33.6	9.4	35.7	8.6	37.7	8.2	39.5	7.5
12.0	24.1	8.8	8.7	28.6	8.6			30.8	8.4	32.9	8.0	35.1	7.5	37.1	7.0	38.9	6.5
14.0	23.0	6.5	6.7	27.6	6.9			29.9	7.0	32.1	6.8	34.3	6.5	36.4	6.1	38.2	5.7
16.0	21.5	4.9	5.1	26.4	5.3			28.8	5.4	31.1	5.4	33.3	5.3	35.5	5.2	37.4	5.0
18.0	19.7	3.6	3.8	25.0	4.0			27.5	4.2	29.9	4.3	32.2	4.3	34.5	4.4	36.5	4.4
20.0	17.5	2.7	2.9	23.3	3.1			26.0	3.2	28.5	3.4	31.0	3.5	33.3	3.7	35.4	3.6
22.0	14.4	2.4	2.5	21.0	2.4			24.2	2.5	26.9	2.6	29.5	2.7	32.0	3.0	34.1	2.9
24.0				18.5	1.7			22.1	2.0	25.0	2.0	27.8	2.1	30.4	2.3	32.7	2.4
26.0								19.5	1.6	22.8	1.5	25.8	1.6	28.6	1.7	31.0	1.9
28.0									1.0	20.0	1.0	23.4	1.2	26.5	1.3	29.2	1.5
30.0												20.3	0.9	23.8	1.0	27.0	1.1
32.0														21.0	0.7	24.5	0.8

ラフテレーンクレーン[油圧伸縮ジブ型]【51t吊】 (1/2)

(m) 作業半径 (m)	9.7		11.5		13.5		15.5		17.5		19.5		21.5		23.5		25.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.5	10.0	51.0	11.9	45.0	13.9	38.3	15.9	31.7	18.0	27.6	20.0	24.4	22.0	21.3	24.0	18.6	26.0	16.2
3.0	9.9	51.0	11.8	45.3	13.8	39.0	15.9	32.7	17.9	28.1	19.9	25.1	22.0	22.2	24.0	19.5	26.3	16.7
3.5	9.7	45.0	11.6	40.6	13.7	36.2	15.8	31.7	17.8	28.1	19.8	25.1	21.9	22.2	23.9	19.5	25.9	17.0
4.0	9.5	39.5	11.4	36.8	13.6	33.9	15.6	31.0	17.7	28.1	19.8	25.1	21.8	22.2	23.8	19.5	25.8	17.0
4.5	9.2	35.5	11.2	33.9	13.4	32.2	15.5	30.5	17.6	28.1	19.6	25.1	21.7	22.2	23.7	19.5	25.8	17.0
5.0	8.9	32.0	11.0	31.0	13.2	30.1	15.3	29.3	17.4	27.4	19.5	24.7	21.6	22.0	23.6	19.5	25.7	17.0
6.0	8.3	26.5	10.5	25.9	12.8	25.5	15.0	25.0	17.1	23.9	19.2	22.3	21.3	20.7	23.4	19.0	25.4	16.8
7.0			9.8	21.5	12.2	21.3	14.5	21.1	16.7	20.5	18.9	19.3	21.0	18.2	23.1	17.0	25.2	15.5
8.0									16.2	17.4	18.4	16.7	20.6	15.9	22.8	15.2	24.9	14.3
9.0									15.7	14.8	18.0	14.5	20.2	14.1	22.4	13.7	24.5	13.1
10.0									15.0	12.6	17.4	12.5	19.7	12.5	21.9	12.3	24.1	11.8
12.0									13.4	8.9	16.0	8.9	18.5	8.9	20.9	9.0	23.2	9.0
14.0									9.1	4.0	12.2	4.9	14.9	5.7	19.5	6.5	22.0	6.8
16.0															18.2	4.8	20.5	5.0
18.0															16.1	3.4	18.7	3.7
20.0															13.7	2.5	16.5	2.8
22.0																		
24.0																		
26.0																		
28.0																		
30.0																		
32.0																		

ラフテレーンクレーン[油圧伸縮ジブ型]【51t吊】(2/2)

(m) 作業半径 (m)	27.5		29.5		31.5		33.5		35.5		37.5		39.5		41.5	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.5	28.0	13.8														
3.0	28.3	14.3	30.7	12.4												
3.5	27.9	14.7	30.0	12.8	31.5	12.4	34.0	11.3								
4.0	27.9	14.7	29.9	12.8	31.4	12.4	33.9	11.3	35.9	10.6	37.9	9.4				
4.5	27.8	14.7	29.8	12.8	31.8	12.1	33.9	11.5	35.9	10.9	37.4	9.3				
5.0	27.7	14.7	29.7	12.8	31.8	12.1	33.8	11.5	35.8	10.9	37.8	9.6	39.8	8.1		
6.0	27.5	14.7	29.5	12.8	31.6	12.1	33.6	11.5	35.7	10.9	37.7	9.6	40.0	8.4	42.5	7.8
7.0	27.3	14.0	29.3	12.6	31.4	12.0	33.4	11.5	35.5	10.8	37.5	9.6	39.9	8.4	42.3	7.8
8.0	27.0	13.3	29.1	12.4	31.1	11.9	33.2	11.4	35.3	10.7	37.3	9.6	39.7	8.4	42.1	7.8
9.0	26.7	12.4	28.8	11.8	30.9	11.3	32.9	10.9	35.0	10.4	37.1	9.5	39.5	8.4	41.9	7.8
10.0	26.3	11.3	28.4	10.8	30.5	10.4	32.6	10.0	34.7	9.5	36.8	8.9	39.2	8.3	41.7	7.8
12.0	25.4	9.1	27.6	9.0	29.8	8.7	31.9	8.4	34.1	8.0	36.2	7.6	38.6	7.2	41.1	7.0
14.0	24.3	7.1	26.6	7.2	28.9	7.2	31.1	7.0	33.3	6.8	35.5	6.4	37.9	6.2	40.5	6.0
16.0	23.0	5.3	25.4	5.6	27.8	5.7	30.1	5.8	32.4	5.8	34.6	5.6	37.1	5.4	39.7	5.3
18.0	21.5	4.0	24.0	4.3	26.5	4.5	28.9	4.6	31.3	4.7	33.6	4.8	36.2	4.7	38.8	4.7
20.0	19.6	3.1	22.4	3.3	25.0	3.4	27.5	3.6	30.0	3.8	32.4	3.9	35.1	3.9	37.8	4.0
22.0			20.3	2.4	23.5	2.6	25.9	2.8	28.5	3.0	31.0	3.1	33.8	3.2	36.6	3.4
24.0			17.8	1.8	21.4	1.9	24.0	2.1	26.8	2.2	29.5	2.4	32.4	2.5	35.2	2.7
26.0					19.2	1.4	22.5	1.6	25.2	1.7	28.0	1.9	30.7	2.0	33.7	2.2
28.0									22.5	1.3	25.9	1.4	28.9	1.5	32.0	1.6
30.0									19.6	0.9	23.5	1.0	26.7	1.1	30.1	1.2
32.0													24.2	0.8	27.8	0.8

ラフテレーンクレーン[油圧伸縮ジブ型]【60t吊】 (1/2)

(m) ブーム長 作業半径 (m)	9.8			11.5			13.5			15.5			17.5			19.5			21.5			23.5			25.5		
	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)
2.8	10.1	60.0	11.8	53.2	44.7	15.9	36.1	17.9	30.1	19.9	27.7	22.0	25.4	23.0	26.0	20.0											
3.0	10.0	56.5	12.3	48.1	40.5	16.4	35.3	18.4	32.2	20.5	29.4	22.5	26.3	23.2	26.5	20.1											
3.5	9.8	51.9	12.1	43.2	38.4	16.3	34.7	18.3	32.2	20.4	29.4	22.4	26.3	23.2	26.4	19.8											
4.0	9.6	48.6	12.0	40.6	37.1	16.2	34.2	18.2	32.0	20.3	29.2	22.3	26.1	23.1	26.4	19.8											
4.5	9.4	44.3	11.8	38.0	35.7	16.0	33.3	18.1	31.2	20.2	28.5	22.2	25.7	22.9	26.3	19.8											
5.0	9.1	39.5	11.5	35.2	33.6	15.9	32.0	18.0	30.3	20.0	27.8	22.1	25.3	22.7	26.2	19.8											
5.5	8.8	35.7	11.3	32.4	31.6	15.7	30.7	17.8	29.4	19.9	27.2	22.0	24.8	22.5	26.1	19.8											
6.0	8.4	32.5	11.0	29.8	29.4	15.5	29.1	17.6	28.3	19.7	26.2	21.8	24.0	21.7	26.0	19.3											
7.0			10.5	24.1	24.0	15.2	23.8	17.2	24.0	19.4	22.5	21.5	20.9	19.3	25.7	17.6											
8.0						15.0	20.3	16.7	21.0	19.0	19.7	21.1	18.6	17.4	25.4	16.2											
9.0						14.4	17.3	16.2	17.5	18.5	16.8	20.7	16.3	15.7	25.0	15.0											
10.0						13.6	14.7	15.5	14.6	17.9	14.3	20.2	14.1	13.9	24.6	13.6											
12.0								13.4	9.9	16.6	10.5	19.0	10.3	10.2	23.7	10.2											
14.0										15.3	8.9	18.0	8.8	8.2	22.5	8.0											
16.0														5.3	21.0	6.4											
18.0														3.9	19.2	5.0											
20.0														2.9	17.0	4.0											
22.0															14.6	4.0											
24.0																											
26.0																											
28.0																											
30.0																											
32.0																											
34.0																											

ラフデレーンクレーン[油圧伸縮ジブ型]【60t吊】 (2/2)

作業半径 (m)	27.5		29.5		31.5		33.5		35.5		37.5		39.5		41.5		43.5	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
2.8	28.0	16.9	30.0	13.8														
3.0	28.5	17.7	30.5	15.3	33.1	15.6	35.1	14.1	37.1	12.5								
3.5	28.5	17.5	30.5	15.2	32.7	14.3	34.7	13.3	36.7	12.2	39.1	10.8	41.1	8.2				
4.0	28.4	17.5	30.4	15.2	32.4	13.8	34.4	13.0	36.5	12.1	38.6	11.1	40.7	9.2				
4.5	28.3	17.5	30.3	15.2	32.4	13.8	34.4	13.0	36.4	12.1	38.4	11.1	40.4	9.4	42.0	9.7	43.9	8.4
5.0	28.2	17.5	30.3	15.2	32.3	13.8	34.3	13.0	36.3	12.1	38.4	11.1	40.4	9.4	41.9	9.5	43.9	8.1
5.5	28.1	17.5	30.2	15.2	32.2	13.8	34.2	13.0	36.3	12.1	38.3	11.1	40.3	9.4	41.8	9.5	43.8	8.1
6.0	28.0	17.2	30.1	15.1	32.1	13.8	34.1	13.0	36.2	12.1	38.2	11.1	40.2	9.4	41.7	9.5	43.7	8.1
7.0	27.8	16.1	29.8	14.5	31.9	13.5	33.9	12.9	36.0	12.0	38.0	11.1	40.1	9.4	41.6	9.5	43.6	8.1
8.0	27.5	15.1	29.6	13.9	31.7	13.1	33.7	12.5	35.8	11.8	37.8	11.1	39.9	9.4	41.4	9.5	43.4	8.1
9.0	27.2	14.1	29.3	13.3	31.4	12.6	33.5	12.1	35.5	11.6	37.6	11.0	39.6	9.4	41.2	9.5	43.2	8.1
10.0	26.8	13.1	28.9	12.6	31.1	12.1	33.2	11.5	35.2	11.1	37.3	10.5	39.4	9.2	41.0	9.5	43.0	8.1
12.0	25.9	10.2	28.1	10.2	30.3	10.0	32.5	9.8	34.6	9.5	36.7	9.2	38.8	8.5	40.4	8.7	42.5	7.8
14.0	24.9	8.1	27.2	8.2	29.4	8.3	31.6	8.2	33.8	8.0	36.0	7.8	38.1	7.6	39.8	7.5	41.8	7.0
16.0	23.6	6.5	26.0	6.6	28.3	6.6	30.6	6.6	32.9	6.6	35.1	6.6	37.3	6.4	39.0	6.3	41.1	6.1
18.0	22.0	5.1	24.6	5.2	27.0	5.2	29.4	5.2	31.8	5.3	34.1	5.4	36.3	5.4	38.1	5.4	40.2	5.2
20.0	20.1	4.0	22.9	4.1	25.5	4.1	28.1	4.1	30.5	4.2	32.9	4.3	35.2	4.4	37.0	4.5	39.3	4.5
22.0	18.2	3.9	21.4	3.8	23.7	3.3	26.4	3.3	29.0	3.5	31.6	3.6	34.0	3.6	35.9	3.6	38.2	3.7
24.0					21.1	2.2	24.1	2.4	27.3	2.9	30.0	2.9	32.6	2.9	34.5	2.9	36.9	3.0
26.0					18.5	1.6	21.9	1.8	25.4	2.3	28.2	2.3	30.9	2.3	33.0	2.3	35.5	2.3
28.0							19.9	2.1	23.5	2.3	26.1	1.8	29.0	1.8	31.3	1.7	33.9	1.8
30.0									20.7	1.9	23.7	1.4	26.9	1.4	29.4	1.4	32.1	1.4
32.0											20.7	1.0	24.3	1.0	27.1	1.0	30.1	1.1
34.0											17.6	1.2	21.8	1.0	24.5	0.7	27.8	0.8

ラフテレーンクレーン[油圧伸縮ジブ型]【65t吊】 (1/2)

(m) 作業半径 (m)	10.0		11.5		13.5		15.5		17.5		19.5		21.5		23.5		25.5	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
2.6	10.9	65.0	12.5	57.8	14.5	48.3	16.6	38.7	18.6	31.2	20.6	28.6	22.6	26.0	24.6	23.4	26.6	20.4
3.0	10.8	60.0	12.4	53.9	14.4	45.8	16.5	37.7	18.5	31.2	20.5	28.6	22.6	26.0	24.6	23.4	26.6	20.4
3.5	10.6	54.5	12.2	49.6	14.3	43.1	16.4	36.6	18.4	31.2	20.5	28.6	22.5	26.0	24.5	23.4	26.5	20.4
4.0	10.4	49.2	12.1	45.5	14.2	40.5	16.3	35.5	18.3	31.2	20.4	28.6	22.4	26.0	24.4	23.4	26.5	20.4
4.5	10.2	44.1	11.9	41.5	14.0	38.0	16.1	34.5	18.2	31.2	20.3	28.6	22.3	26.0	24.3	23.4	26.4	20.4
5.0	9.9	39.5	11.6	37.9	13.8	35.7	16.0	33.5	18.0	31.2	20.1	28.6	22.2	26.0	24.2	23.4	26.3	20.4
5.5	9.6	35.7	11.4	34.9	13.6	33.8	15.8	32.8	17.9	31.2	20.0	28.6	22.1	26.0	24.1	23.4	26.2	20.4
6.0	9.3	32.5	11.1	32.1	13.4	31.5	15.6	30.9	17.7	29.8	19.8	27.3	21.9	24.8	24.0	22.4	26.1	19.7
7.0	8.4	26.8	10.4	26.6	12.8	26.4	15.1	26.2	17.3	25.4	19.5	23.5	21.6	21.5	23.7	19.6	25.8	17.6
8.0									16.8	21.6	19.1	20.2	21.2	18.8	23.4	17.4	25.5	16.0
9.0									16.3	17.3	18.6	16.7	20.8	16.1	23.0	15.5	25.1	14.7
10.0									15.6	14.2	18.0	14.1	20.3	14.0	22.5	13.9	24.7	13.6
12.0									14.0	9.7	16.6	9.6	19.1	9.6	21.5	9.5	23.8	9.7
14.0																	22.6	7.0
16.0																	21.1	5.1
18.0																	19.3	3.7
20.0																	17.1	2.7
22.0																		
24.0																		
26.0																		
28.0																		
30.0																		
32.0																		

ラフテレンクレーン[油圧伸縮ジブ型]【65t吊】 (2/2)

(m) 作業半径 (m)	27.5		29.5		31.5		33.5		35.5		37.5		39.5		41.5		43.5	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
2.6	28.7	17.4	30.7	14.3														
3.0	28.6	17.4	30.6	14.3														
3.5	28.6	17.4	30.6	14.3	32.6	12.4	34.6	12.3	36.6	12.2	38.6	12.0						
4.0	28.5	17.4	30.5	14.3	32.5	12.4	34.5	12.3	36.6	12.2	38.6	12.0	40.6	11.0	42.6	10.0		
4.5	28.4	17.4	30.4	14.3	32.5	12.4	34.5	12.3	36.5	12.2	38.5	12.0	40.5	11.0	42.5	10.0	44.5	8.7
5.0	28.3	17.4	30.4	14.3	32.4	12.4	34.4	12.3	36.4	12.2	38.4	12.0	40.5	11.0	42.5	10.0	44.5	8.7
5.5	28.2	17.4	30.3	14.3	32.3	12.4	34.3	12.3	36.4	12.2	38.4	12.0	40.4	11.0	42.4	10.0	44.4	8.7
6.0	28.1	16.9	30.2	14.2	32.2	12.4	34.2	12.3	36.3	12.2	38.3	12.0	40.3	11.0	42.3	10.0	44.4	8.7
7.0	27.9	15.7	29.9	13.7	32.0	12.4	34.0	12.3	36.1	12.2	38.1	12.0	40.2	11.0	42.2	10.0	44.2	8.7
8.0	27.6	14.7	29.7	13.3	31.7	12.4	33.8	12.3	35.9	12.2	37.9	12.0	40.0	11.0	42.0	10.0	44.0	8.7
9.0	27.3	13.8	29.4	13.0	31.5	12.4	33.5	12.3	35.6	12.2	37.7	12.0	39.7	11.0	41.8	10.0	43.8	8.7
10.0	26.9	13.2	29.0	12.7	31.1	12.3	33.3	11.9	35.3	11.4	37.4	10.9	39.5	10.5	41.6	10.0	43.6	8.7
12.0	26.0	9.9	28.2	10.2	30.4	10.2	32.6	9.9	34.7	9.5	36.8	9.2	38.9	8.8	41.0	8.4	43.1	8.1
14.0	24.9	7.3	27.2	7.5	29.5	7.7	31.7	7.7	33.9	7.8	36.1	7.8	38.2	7.5	40.3	7.2	42.5	6.9
16.0	23.6	5.4	26.1	5.6	28.4	5.9	30.7	6.0	33.0	6.2	35.2	6.3	37.4	6.3	39.6	6.2	41.7	5.9
18.0	22.1	4.0	24.7	4.2	27.1	4.5	29.5	4.6	31.9	4.8	34.2	4.9	36.4	5.1	38.7	5.2	40.9	5.1
20.0	20.2	3.0	23.0	3.2	25.6	3.5	28.2	3.6	30.6	3.8	33.0	3.9	35.3	4.0	37.6	4.1	39.9	4.2
22.0					23.8	2.6	26.5	2.8	29.1	2.9	31.6	3.1	34.1	3.2	36.5	3.3	38.8	3.4
24.0					21.7	1.9	24.7	2.0	27.4	2.2	30.1	2.4	32.7	2.5	35.1	2.6	37.6	2.7
26.0					19.1	1.3	22.4	1.5	25.5	1.6	28.3	1.8	31.0	1.9	33.6	2.0	36.2	2.1
28.0													29.1	1.4	31.9	1.6	34.6	1.7
30.0													27.0	1.0	30.0	1.1	32.8	1.2
32.0															27.7	0.8	30.7	0.9

ラフテレーンクレーン[油圧伸縮ジブ型]【70t吊】 (1/2)

作業半径 (m)	9.8		11.5		13.5		15.5		17.5		19.5		21.5		23.5		25.5		27.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
2.1	10.4	70.0																		
2.5	10.2	63.3	12.7	61.9	14.7	50.9	16.8	39.9	18.8	31.6	20.8	29.4	22.8	27.3	24.9	25.3	26.9	21.9	28.9	18.3
3.0	10.1	56.5	12.0	51.1	14.1	43.7	16.1	36.3	18.1	31.0	20.2	28.8	22.2	26.5	24.2	24.2	26.2	20.8	28.2	17.4
3.5	9.9	51.9	11.9	47.4	13.9	41.4	16.0	35.4	18.1	31.0	20.1	28.8	22.1	26.5	24.1	24.2	26.2	20.8	28.2	17.4
4.0	9.7	48.6	11.7	44.6	13.8	39.7	15.9	34.8	17.9	31.0	20.0	28.8	22.0	26.5	24.1	24.2	26.1	20.8	28.1	17.4
4.5	9.5	44.3	11.5	41.3	13.6	37.7	15.7	34.1	17.8	31.0	19.9	28.8	21.9	26.5	24.0	24.2	26.0	20.8	28.0	17.4
5.0	9.2	39.5	11.3	37.7	13.4	35.5	15.6	33.3	17.7	31.0	19.8	28.8	21.8	26.5	23.9	24.2	25.9	20.8	27.9	17.4
5.5	8.9	35.8	11.0	34.8	13.2	33.7	15.4	32.6	17.5	31.0	19.6	28.8	21.7	26.5	23.8	24.2	25.8	20.8	27.8	17.4
6.0	8.5	32.4	10.7	32.2	13.0	31.9	15.2	31.6	17.3	30.4	19.5	28.1	21.6	25.7	23.6	23.4	25.7	20.3	27.7	17.1
7.0			10.6	26.7	13.0	26.6	15.3	26.5	16.9	25.7	19.1	24.0	21.2	22.3	23.3	20.6	25.4	18.2	27.5	15.9
8.0			9.3	23.8	11.9	23.5	14.3	23.1	16.5	21.6	18.7	20.5	20.9	19.4	23.0	18.3	25.1	16.6	27.2	15.0
9.0									15.9	18.0	18.2	17.5	20.4	16.9	22.6	16.4	24.8	15.3	26.9	14.1
10.0									15.3	14.7	17.6	14.6	19.9	14.5	22.2	14.3	24.4	13.8	26.5	13.3
12.0									13.6	10.2	16.3	10.1	18.7	10.0	21.1	9.9	23.4	10.2	25.6	10.4
14.0											14.6	9.2	17.3	9.3	19.7	7.3	22.2	7.5	24.6	7.8
16.0															18.0	5.3	20.8	5.5	23.3	5.8
18.0															15.9	3.9	19.0	4.1	21.7	4.4
20.0															13.1	2.9	16.7	3.1	19.8	3.3
22.0																	13.9	2.8	17.5	2.9
24.0																				
26.0																				
28.0																				
30.0																				
32.0																				
34.0																				

ラフテレーンクレーン[油圧伸縮ジブ型]【70t吊】(2/2)

作業半径 (m)	ブーム長 (m)	29.5		31.5		33.5		35.5		37.5		39.5		41.5		43.5		45.5		47.5	
		フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
		(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.1																					
2.5		30.9	14.7																		
3.0		30.3	14.0	32.2	13.8	34.2	12.8														
3.5		30.2	14.0	32.2	12.4	34.2	12.3	36.2	12.1	38.8	11.9										
4.0		30.1	14.0	32.1	12.4	34.2	12.3	36.2	12.1	38.2	11.9	40.2	10.9	42.8	9.9						
4.5		30.1	14.0	32.1	12.4	34.1	12.3	36.1	12.1	38.1	11.9	40.1	10.9	42.2	9.8	44.2	8.5				
5.0		30.0	14.0	32.0	12.4	34.0	12.3	36.1	12.1	38.1	11.9	40.1	10.9	42.1	9.8	44.1	8.5	46.0	7.4	48.1	7.1
5.5		29.9	14.0	31.9	12.4	34.0	12.3	36.0	12.1	38.0	11.9	40.0	10.9	42.0	9.8	44.1	8.5	46.0	7.4	48.0	7.1
6.0		29.8	13.9	31.8	12.4	33.9	12.3	35.9	12.1	37.9	11.9	39.9	10.9	42.0	9.8	44.0	8.5	45.9	7.4	47.9	7.1
7.0		29.6	13.5	31.6	12.4	33.7	12.3	35.7	12.1	37.7	11.9	39.8	10.9	41.8	9.8	43.8	8.5	45.8	7.4	47.8	7.1
8.0		29.3	13.3	31.4	12.4	33.4	12.3	35.5	12.1	37.5	11.9	39.6	10.9	41.6	9.8	43.7	8.5	45.6	7.4	47.6	7.1
9.0		29.0	13.0	31.1	12.4	33.2	12.3	35.2	12.1	37.3	11.9	39.4	10.9	41.4	9.8	43.5	8.5	45.4	7.4	47.5	7.1
10.0		28.7	12.7	30.8	12.4	32.9	12.3	35.0	12.1	37.0	11.9	39.1	10.9	41.2	9.8	43.2	8.5	45.2	7.4	47.3	7.1
12.0		27.9	10.7	30.0	10.7	32.2	10.6	34.3	10.5	36.4	10.3	38.5	9.9	40.6	9.4	42.7	8.5	44.7	7.4	46.8	7.1
14.0		26.9	8.1	29.1	8.3	31.3	8.4	33.5	8.5	35.7	8.6	37.8	8.4	40.0	8.2	42.1	7.8	44.1	6.7	46.2	6.4
16.0		25.7	6.1	28.0	6.3	30.3	6.4	32.6	6.6	34.8	6.7	37.0	6.8	39.2	6.8	41.4	6.8	43.4	5.9	45.5	5.6
18.0		24.3	4.6	26.8	4.8	29.2	5.0	31.5	5.1	33.8	5.3	36.1	5.4	38.3	5.5	40.5	5.5	42.6	5.0	44.8	4.9
20.0		22.6	3.6	25.2	3.7	27.8	3.9	30.2	4.0	32.6	4.1	35.0	4.2	37.3	4.3	39.5	4.4	41.7	4.0	43.9	4.1
22.0		20.5	1.9	23.4	2.8	26.2	3.0	28.8	3.1	31.3	3.3	33.7	3.4	36.1	3.5	38.4	3.6	40.6	3.2	42.9	3.3
24.0		18.0	0.9	21.3	2.2	24.3	2.3	27.1	2.4	29.7	2.6	32.3	2.7	34.8	2.8	37.2	2.9	39.5	2.5	41.8	2.6
26.0				18.7	1.6	22.0	1.7	25.1	1.9	27.9	2.0	30.6	2.1	33.3	2.2	35.8	2.3	38.2	1.9	40.6	2.0
28.0				15.4	0.7	19.4	1.0	22.7	0.7	25.7	1.6	28.8	1.6	31.5	1.7	34.2	1.8	36.7	1.4	39.2	1.5
30.0										23.3	1.1	26.6	1.2	29.6	1.3	32.4	1.4	35.0	1.0	37.6	1.1
32.0										20.4	0.8	24.0	0.9	27.3	0.9	30.4	1.0	33.2	0.7	35.9	0.8
34.0										17.6	0.5	21.9	0.6	24.6	0.6	27.9	0.7				

ラフテレーンクレーン[油圧伸縮ジブ型]【75t吊】(1/2)

(m) 作業半径 (m)	10.0		11.5		13.5		15.5		17.5		19.5		21.5		23.5		25.5	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.3	10.3	75.0	11.8	66.3	13.9	55.3	15.9	46.6	17.9	39.6	19.9	38.2	22.0	36.8	24.0	35.4		
2.5	10.3	71.0	11.8	63.3	13.8	53.6	15.9	45.8	17.9	39.6	19.9	38.2	21.9	36.8	23.9	35.4	26.0	30.5
3.0	10.1	63.0	11.7	57.3	13.7	50.1	15.8	44.3	17.8	39.6	19.8	38.2	21.9	36.8	23.9	35.4	25.9	30.5
3.5	9.9	57.5	11.5	53.1	13.6	47.7	15.7	43.3	17.7	39.6	19.8	38.2	21.8	36.8	23.8	35.4	25.8	30.5
4.0	9.7	52.0	11.4	49.0	13.5	45.3	15.5	42.3	17.6	39.5	19.7	37.3	21.7	35.2	23.7	33.0	25.8	28.5
4.5	9.5	48.0	11.2	46.0	13.3	43.5	15.4	41.5	17.5	39.3	19.5	36.4	21.6	33.6	23.6	31.0	25.7	26.8
5.0	9.2	43.9	10.9	42.8	13.1	41.3	15.2	40.0	17.3	38.2	19.4	34.9	21.5	31.9	23.5	29.0	25.6	25.2
5.5	8.9	39.9	10.7	39.3	12.9	38.5	15.1	37.6	17.2	36.2	19.3	33.0	21.4	30.1	23.4	27.2	25.5	23.8
6.0	8.6	35.9	10.4	35.7	12.7	35.5	14.9	35.2	17.0	34.2	19.1	31.2	21.2	28.3	23.3	25.6	25.4	22.6
7.0					12.6	29.7	14.9	29.6	16.6	29.8	18.8	27.4	20.9	25.1	23.0	22.8	25.1	20.4
8.0					12.0	25.5	14.4	25.4	16.1	25.5	18.4	23.8	20.5	22.1	22.7	20.3	24.8	18.6
9.0					11.2	22.2	13.7	22.2	15.6	21.2	17.9	20.3	20.1	19.3	22.3	18.4	24.4	17.2
10.0									14.9	17.4	17.3	17.2	19.6	16.9	21.8	16.6	24.0	16.0
12.0									13.3	12.3	15.9	12.3	18.4	12.2	20.8	12.1	23.1	12.1
14.0													17.4	11.1	20.0	11.0	21.9	9.1
16.0													15.5	8.6	18.3	8.5	20.4	6.9
18.0																	18.6	5.4
20.0																	16.4	4.1
22.0																		
24.0																		
26.0																		
28.0																		
30.0																		
32.0																		
34.0																		
36.0																		

ラフテレーンクレーン[油圧伸縮ジブ型]【75t吊】(2/2)

(m) 作業半径 (m)	27.5		29.5		31.5		33.5		35.5		37.5		39.5		41.5		43.5	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.3																		
2.5	28.0	24.5	30.0	18.5														
3.0	27.9	24.5	29.9	18.5														
3.5	27.9	24.5	29.9	18.5	31.9	13.9	33.9	13.6	35.9	13.4	37.9	13.1						
4.0	27.8	23.3	29.8	18.0	31.8	13.9	33.8	13.6	35.8	13.4	37.9	13.1	39.9	12.0	41.9	10.6		
4.5	27.7	22.2	29.7	17.5	31.8	13.9	33.8	13.6	35.8	13.4	37.8	13.1	39.8	12.0	41.8	10.6	43.8	9.2
5.0	27.6	21.2	29.6	17.1	31.7	13.9	33.7	13.6	35.7	13.4	37.7	13.1	39.8	12.0	41.8	10.6	43.8	9.2
5.5	27.5	20.3	29.6	16.7	31.6	13.9	33.6	13.6	35.6	13.4	37.7	13.1	39.7	12.0	41.7	10.6	43.7	9.2
6.0	27.4	19.5	29.5	16.3	31.5	13.9	33.5	13.6	35.6	13.4	37.6	13.1	39.6	12.0	41.6	10.6	43.7	9.2
7.0	27.2	18.1	29.2	15.8	31.3	13.9	33.3	13.6	35.4	13.4	37.4	13.1	39.4	12.0	41.5	10.6	43.5	9.2
8.0	26.9	17.0	29.0	15.3	31.0	13.9	33.1	13.6	35.2	13.4	37.2	13.1	39.3	12.0	41.3	10.6	43.3	9.2
9.0	26.6	16.1	28.7	14.9	30.8	13.9	32.8	13.6	34.9	13.4	37.0	13.1	39.0	12.0	41.1	10.6	43.1	9.2
10.0	26.2	15.3	28.3	14.5	30.4	13.9	32.5	13.4	34.6	12.9	36.7	12.5	38.8	11.5	40.9	10.5	42.9	9.2
12.0	25.3	12.1	27.5	12.1	29.7	12.0	31.9	11.6	34.0	11.2	36.1	10.9	38.2	10.5	40.3	10.3	42.4	9.2
14.0	24.2	9.4	26.5	9.6	28.8	9.7	31.0	9.6	33.2	9.4	35.4	9.2	37.5	9.0	39.6	8.8	41.8	8.3
16.0	22.9	7.2	25.4	7.5	27.7	7.7	30.0	7.8	32.3	7.8	34.5	7.9	36.7	7.8	38.9	7.6	41.0	7.3
18.0	21.4	5.6	23.9	5.8	26.4	6.0	28.8	6.2	31.2	6.3	33.5	6.4	35.7	6.5	38.0	6.5	40.2	6.3
20.0	19.4	4.4	22.3	4.6	24.9	4.8	27.4	5.0	29.9	5.1	32.3	5.2	34.6	5.3	36.9	5.4	39.2	5.4
22.0					23.1	3.9	25.8	4.0	28.4	4.2	30.9	4.3	33.4	4.4	35.8	4.4	38.1	4.5
24.0					21.0	3.1	23.9	3.2	26.7	3.3	29.4	3.5	31.9	3.6	34.4	3.7	36.9	3.8
26.0					18.4	2.3	21.7	2.5	24.7	2.6	27.6	2.8	30.3	2.9	32.9	3.0	35.4	3.1
28.0					15.5	2.3	19.5	2.5	22.9	2.7	26.0	2.9	28.4	2.3	31.2	2.4	33.9	2.5
30.0													26.3	1.8	29.2	1.9	32.1	2.0
32.0													23.7	1.4	27.0	1.5	30.0	1.6
34.0													20.7	1.0	24.4	1.1	27.7	1.2
36.0																	24.9	0.8

ラフテレーンクレーン[油圧伸縮ジブ型]【80t吊】 (1/2)

(m) ブーム長 作業半径 (m)	10.0			11.5			13.5			15.5			17.5			19.5			21.5			23.5			25.5		
	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)	フックの 地上高さ	定格 総荷重	(t)
2.2	10.9	80.0		12.4	60.0		14.4	40.0		16.4	40.0		18.5	39.7		20.5	38.3										
2.5	10.8	71.0		12.3	55.5		14.4	40.0		16.4	40.0		18.4	39.7		20.4	38.3		22.5	36.9		24.5	35.4		26.5	30.5	
3.0	10.6	63.0		12.2	51.5		14.3	40.0		16.3	40.0		18.3	39.7		20.4	38.3		22.4	36.9		24.4	35.4		26.4	30.5	
3.5	10.5	57.5		12.1	48.8		14.1	40.0		16.2	40.0		18.2	39.7		20.3	38.3		22.3	36.9		24.3	35.4		26.4	30.5	
4.0	10.3	52.0		11.9	46.0		14.0	40.0		16.1	40.0		18.1	39.5		20.2	37.5		22.2	35.3		24.3	33.1		26.3	28.5	
4.5	10.0	48.0		11.7	44.0		13.8	40.0		15.9	40.0		18.0	39.0		20.1	35.0		22.1	32.6		24.2	30.8		26.2	26.8	
5.0	9.8	44.0		11.5	42.0		13.6	39.9		15.8	39.4		17.9	37.8		19.9	33.2		22.0	30.6		24.1	28.8		26.1	25.2	
5.5	9.4	40.0		11.2	40.0		13.4	39.6		15.6	38.1		17.7	35.8		19.8	31.2		21.9	28.7		23.9	26.9		26.0	23.8	
6.0	9.1	37.0		10.9	37.0		13.2	36.8		15.4	35.8		17.5	33.9		19.7	29.6		21.7	27.2		23.8	25.4		25.9	22.6	
7.0							12.6	31.2		14.9	30.8		17.1	29.7		19.3	26.3		21.4	24.3		23.5	22.6		25.6	20.4	
8.0							12.0	26.8		14.4	26.3		16.7	25.5		18.9	23.5		21.1	21.8		23.2	20.3		25.3	18.6	
9.0							11.2	23.4		13.7	23.2		16.1	22.7		18.4	21.3		20.6	19.9		22.8	18.5		25.0	17.2	
10.0													15.5	20.3		17.8	19.7		20.1	18.4		22.4	16.9		24.6	16.0	
12.0													13.8	16.5		16.5	16.3		18.9	15.3		21.3	14.2		23.6	13.5	
14.0																			17.4	12.7		20.0	12.1		22.4	11.6	
16.0																			15.5	10.6		18.3	10.4		21.0	10.0	
18.0																									19.2	8.8	
20.0																									16.9	7.2	
22.0																											
24.0																											
26.0																											
28.0																											
30.0																											
32.0																											

ラフテレーンクレーン[油圧伸縮ジブ型]【80t吊】(2/2)

27.5		29.5		31.5		33.5		35.5		37.5		39.5		41.5		43.5	
フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
2.2	24.5	30.5	18.5														
2.5	24.5	30.4	18.5														
3.0	24.5	30.4	18.5	32.4	13.9	34.4	13.6	36.4	13.4	38.4	13.1						
3.5	23.3	30.3	18.0	32.3	13.9	34.4	13.6	36.4	13.4	38.4	13.1	40.4	12.0	42.4	10.6		
4.0	22.2	30.3	17.5	32.3	13.9	34.3	13.6	36.3	13.4	38.3	13.1	40.3	12.0	42.4	10.6	44.4	9.2
4.5	21.2	30.2	17.1	32.2	13.9	34.2	13.6	36.2	13.4	38.3	13.1	40.3	12.0	42.3	10.6	44.3	9.2
5.0	20.3	30.1	16.7	32.1	13.9	34.1	13.6	36.2	13.4	38.2	13.1	40.2	12.0	42.2	10.6	44.2	9.2
5.5	19.5	30.0	16.3	32.0	13.9	34.1	13.6	36.1	13.4	38.1	13.1	40.1	12.0	42.2	10.6	44.2	9.2
6.0	18.1	29.8	15.8	31.8	13.9	33.9	13.6	35.9	13.4	37.9	13.1	40.0	12.0	42.0	10.6	44.0	9.2
7.0	17.0	29.5	15.3	31.6	13.9	33.6	13.6	35.7	13.4	37.7	13.1	39.8	12.0	41.8	10.6	43.9	9.2
8.0	16.1	29.2	14.9	31.3	13.9	33.4	13.6	35.4	13.4	37.5	13.1	39.6	12.0	41.6	10.6	43.7	9.2
9.0	15.3	28.9	14.5	31.0	13.9	33.1	13.5	35.2	13.2	37.2	12.8	39.3	11.8	41.4	10.5	43.4	9.2
10.0	13.0	28.0	12.5	30.2	12.0	32.4	11.7	34.5	11.5	36.6	11.2	38.7	10.8	40.8	10.3	42.9	9.2
12.0	11.1	27.1	10.6	29.3	10.2	31.5	10.0	33.7	9.8	35.9	9.6	38.0	9.3	40.2	9.0	42.3	8.5
14.0	9.7	25.9	9.3	28.2	8.9	30.5	8.7	32.8	8.5	35.0	8.3	37.2	8.1	39.4	8.0	41.5	7.6
16.0	8.5	24.5	8.1	26.9	7.8	29.4	7.5	31.7	7.3	34.0	7.0	36.3	6.9	38.5	6.9	40.7	6.6
18.0	7.2	22.8	7.1	25.4	6.9	28.0	6.7	30.4	6.4	32.8	6.2	35.2	6.0	37.5	5.9	39.7	5.7
20.0				23.6	6.1	26.4	5.9	29.0	5.7	31.5	5.5	33.9	5.3	36.3	5.1	38.6	5.0
22.0				21.5	5.5	24.5	5.3	27.3	5.1	29.9	4.9	32.5	4.7	35.0	4.5	37.4	4.4
24.0				18.9	4.8	22.2	4.6	25.3	4.5	28.1	4.3	30.8	4.2	33.4	4.0	36.0	4.0
26.0				15.5	4.1	19.5	4.0	22.9	3.9	26.0	3.9	29.0	3.8	31.7	3.6	34.4	3.6
28.0												26.8	3.4	29.8	3.2	32.6	3.2
30.0												24.3	3.1	27.5	3.0	30.6	2.9
32.0																	

ラフデレックレーン[油圧伸縮ジブ型]【100t吊】(1/2)

作業半径 (m)	10.2		11.5		13.5		15.5		17.5		19.5		21.5		23.5		25.5		27.5	
	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重	フックの 地上高さ	定格 総荷重
1.6	11.3	100.0																		
2.0	11.3	84.0	12.6	69.5	14.6	47.2	16.6	45.0	18.6	44.6	20.6	41.7	22.7	38.9	24.7	36.0				
2.5	11.1	74.1	12.5	63.3	14.5	46.7	16.5	45.0	18.6	44.6	20.6	41.7	22.6	38.9	24.6	36.0	26.6	31.3	28.6	25.6
3.0	11.0	66.5	12.4	58.5	14.4	46.2	16.5	45.0	18.5	44.6	20.5	41.7	22.5	38.9	24.6	36.0	26.6	31.3	28.6	25.6
3.5	10.8	60.1	12.2	54.5	14.3	45.9	16.4	45.0	18.4	44.6	20.4	41.7	22.5	38.9	24.5	36.0	26.5	31.3	28.5	25.6
4.0	10.6	54.7	12.0	51.1	14.1	45.6	16.2	43.9	18.3	42.7	20.3	41.0	22.4	38.6	24.4	35.0	26.4	30.5	28.5	25.5
4.5	10.4	50.0	11.8	48.1	14.0	45.3	16.1	42.5	18.2	40.2	20.2	40.1	22.3	38.3	24.3	33.9	26.4	29.7	28.4	25.4
5.0	10.1	45.9	11.6	45.6	13.8	45.1	15.9	42.4	18.0	40.0	20.1	39.7	22.2	37.5	24.2	32.4	26.3	28.5	28.3	25.3
5.5	9.8	42.4	11.4	42.3	13.6	42.2	15.7	41.1	17.9	39.8	20.0	38.4	22.0	35.6	24.1	30.6	26.2	27.5	28.2	25.2
6.0	9.5	38.5	11.1	38.4	13.3	38.3	15.5	38.5	17.7	38.4	19.8	36.8	21.9	34.0	24.0	29.1	26.0	26.5	28.1	25.0
7.0	8.7	32.5	10.4	32.4	12.8	32.3	15.1	32.4	17.3	32.5	19.5	32.7	21.6	31.0	23.7	26.5	25.8	24.3	27.8	23.3
8.0							14.5	27.8	16.8	27.9	19.0	28.2	21.2	27.0	23.3	23.8	25.5	22.3	27.6	21.8
9.0							13.9	24.3	16.3	24.4	18.6	24.6	20.8	23.8	23.0	21.7	25.1	20.7	27.2	20.4
10.0							13.1	21.4	15.6	21.5	18.0	21.7	20.3	21.2	22.5	19.8	24.7	19.3	26.9	19.2
12.0									14.0	17.2	16.6	17.4	19.1	17.3	21.5	16.9	23.8	16.9	26.0	17.1
14.0									11.8	13.7	14.8	14.0	17.6	14.1	20.1	14.2	22.6	14.6	24.9	15.1
16.0													15.6	11.7	18.5	12.4	21.1	12.5	23.6	12.3
18.0																	19.3	10.3	22.0	10.1
20.0																	17.1	8.6	20.1	8.5
22.0																				
24.0																				
26.0																				
28.0																				
30.0																				
32.0																				
34.0																				
36.0																				
38.0																				
40.0																				

ラフデレックレーン[油圧伸縮ジブ型]【100t吊】(2/2)

作業半径 (m)	ブーム長 (m)		29.5		31.5		33.5		35.5		37.5		39.5		41.5		43.5		45.5		47.5	
	フックの 地上高さ		定格 総荷重		フックの 地上高さ		定格 総荷重		フックの 地上高さ		定格 総荷重		フックの 地上高さ		定格 総荷重		フックの 地上高さ		定格 総荷重		フックの 地上高さ	
	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)	(m)	(t)
1.6																						
2.0																						
2.5																						
3.0	30.6	22.4																				
3.5	30.5	22.4	32.6	19.9	34.6	19.0																
4.0	30.5	22.4	32.5	19.9	34.5	19.0	36.5	17.6	38.5	15.7												
4.5	30.4	22.4	32.4	19.9	34.4	19.0	36.5	17.6	38.5	15.7												
5.0	30.3	22.4	32.4	19.9	34.4	19.0	36.4	17.6	38.4	15.7	40.4	13.9	42.4	12.3								
5.5	30.2	22.4	32.3	19.9	34.3	19.0	36.3	17.6	38.3	15.7	40.4	13.9	42.4	12.3	44.4	10.9	46.4	9.5	48.4	7.9		
6.0	30.1	22.4	32.2	19.9	34.2	19.0	36.2	17.6	38.3	15.7	40.3	13.9	42.3	12.3	44.3	10.9	46.4	9.5	48.4	7.9		
7.0	29.9	21.6	32.0	19.8	34.0	18.8	36.1	17.4	38.1	15.6	40.1	13.9	42.2	12.3	44.2	10.9	46.2	9.5	48.2	7.9		
8.0	29.6	20.4	31.7	19.0	33.8	17.6	35.8	16.4	37.9	15.3	39.9	13.9	42.0	12.3	44.0	10.9	46.0	9.5	48.1	7.9		
9.0	29.3	19.2	31.4	17.8	33.5	16.4	35.6	15.3	37.7	14.4	39.7	13.4	41.8	12.2	43.8	10.9	45.9	9.5	47.9	7.9		
10.0	29.0	18.0	31.1	16.6	33.2	15.3	35.3	14.2	37.4	13.5	39.5	12.7	41.5	12.0	43.6	10.8	45.6	9.5	47.7	7.9		
12.0	28.2	15.8	30.4	14.5	32.5	13.4	34.7	12.5	36.8	11.8	38.9	11.3	41.0	10.8	43.1	10.1	45.1	9.4	47.2	7.9		
14.0	27.2	14.0	29.5	12.8	31.7	11.9	33.9	11.2	36.0	10.5	38.2	10.0	40.3	9.6	42.4	9.2	44.5	8.7	46.6	7.5		
16.0	26.0	11.9	28.4	11.4	30.7	10.7	32.9	10.1	35.2	9.5	37.4	9.0	39.5	8.6	41.7	8.3	43.8	7.9	46.0	6.8		
18.0	24.6	10.0	27.1	9.8	29.5	9.5	31.9	9.1	34.1	8.6	36.4	8.2	38.6	7.8	40.9	7.6	43.0	7.2	45.2	6.2		
20.0	22.9	8.3	25.6	8.1	28.1	8.1	30.6	8.0	33.0	7.8	35.3	7.5	37.6	7.1	39.9	6.9	42.1	6.6	44.3	5.6		
22.0	20.9	7.3	23.8	7.3	26.5	7.0	29.1	6.8	31.6	6.9	34.1	6.8	36.4	6.5	38.8	6.3	41.1	6.0	43.4	5.0		
24.0	18.4	6.3	21.7	6.4	24.6	6.0	27.4	5.7	30.1	5.8	32.6	5.9	35.1	6.0	37.5	5.8	39.9	5.5	42.2	4.5		
26.0			19.0	5.5	22.4	5.4	25.4	5.2	28.3	5.1	31.0	5.1	33.6	5.2	36.1	5.2	38.6	5.1	41.0	4.1		
28.0			15.7	4.9	19.6	5.0	23.1	4.8	26.2	4.4	29.1	4.4	31.9	4.5	34.5	4.6	37.1	4.5	39.6	3.7		
30.0							20.2	4.3	23.8	4.0	26.9	4.0	29.9	4.2	32.8	4.2	35.5	4.0	38.1	3.4		
32.0											24.4	3.6	27.7	3.7	30.7	3.6	33.6	3.4	36.4	3.0		
34.0											21.4	3.3	25.0	3.3	28.4	3.2	31.5	3.0	34.4	2.7		
36.0															25.7	2.8	29.1	2.6	32.2	2.5		
38.0															22.4	2.4	26.3	2.3	29.8	2.3		
40.0																	22.9	2.0	26.9	2.0		

ホイールクレーン[ラチスジブ型]【65t吊】 (1/2)

ブーム長さ (m)	5.6			7.5			9.5			11.5			13.5			15.5			17.5		
	フックの 地上高さ	定格 総荷重		フックの 地上高さ	定格 総荷重		フックの 地上高さ	定格 総荷重		フックの 地上高さ	定格 総荷重		フックの 地上高さ	定格 総荷重		フックの 地上高さ	定格 総荷重		フックの 地上高さ	定格 総荷重	
	(m)	(t)		(m)	(t)		(m)	(t)		(m)	(t)		(m)	(t)		(m)	(t)		(m)	(t)	
3.0	4.1	65.0																			
3.5	3.9	40.0																			
4.0	3.6	35.0	5.1	44.4																	
4.5	3.3	25.0	4.8	37.4	44.5	7.2	44.5	44.4		9.4	44.4										
5.0	2.8	15.0	4.4	31.0	40.2	6.9	40.2	40.1	40.0	9.2	40.1	11.3	40.0								
5.5	2.3	12.5	3.9	27.8	36.6	6.6	36.6	36.5	36.5	8.9	36.5	11.1	36.5	13.3	36.5	15.4	36.4				
6.0	1.5	10.0	3.3	25.0	33.6	6.2	33.6	33.5	33.4	8.6	33.5	10.9	33.4	13.1	33.4	15.2	33.3				
7.0					28.8	5.2	28.8	28.7	28.6	7.9	28.7	10.3	28.6	12.6	28.6	14.8	28.5				
8.0					24.3	3.9	24.3	25.0	25.0	7.1	25.0	9.7	25.0	12.1	25.0	14.4	24.9				
9.0						1.8	19.9	22.0	22.2	6.0	22.0	8.9	22.2	11.4	22.2	13.8	22.1				
10.0									19.6			7.9	19.6	10.6	20.0	13.2	19.9				
12.0														8.6	16.4	11.5	16.3				
14.0														5.5	13.0	9.3	13.4				
16.0																					
18.0																					
20.0																					
22.0																					
24.0																					
26.0																					

ホイールクレーン【ラチスジブ型】【65t吊】

(2/2)

フォーム長さ (m)	19.5		21.5		23.5		25.5		27.5		29.5		31.5	
	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)	フックの 地上高さ (m)	定格 総荷重 (t)
3.0														
3.5														
4.0														
4.5														
5.0														
5.5														
6.0	17.4	33.2												
7.0	17.0	28.5	19.1	28.5	21.2	28.4	23.3	28.4						
8.0	16.6	24.9	18.8	24.9	20.9	24.8	23.0	24.8	25.1	24.7	27.2	24.6	29.3	22.3
9.0	16.1	22.1	18.3	22.1	20.5	22.0	22.7	22.0	24.8	21.9	26.9	21.8	29.0	20.9
10.0	15.5	19.8	17.8	19.8	20.1	19.7	22.3	19.7	24.4	19.6	26.6	19.6	28.7	19.5
12.0	14.2	16.3	16.6	16.3	19.0	16.2	21.3	16.2	23.5	16.1	25.8	16.0	27.9	16.0
14.0	12.4	13.4	15.1	13.4	17.7	13.3	20.1	13.3	22.5	13.2	24.8	13.2	27.0	13.2
16.0	10.0	10.9	13.2	10.9	16.0	10.9	18.7	10.9	21.2	10.8	23.6	10.8	25.9	10.8
18.0			10.6	9.2	13.9	9.2	16.9	9.2	19.6	9.1	22.2	9.0	24.7	9.0
20.0							14.6	7.8	17.7	7.7	20.5	7.7	23.1	7.7
22.0							11.7	6.8	15.3	6.7	18.5	6.7	21.3	6.7
24.0									12.2	5.9	16.0	5.8	19.2	5.8
26.0													16.6	5.2